

Caterpillar Oil Aeration Test

Version

Form 1

Title / Validity Declaration Page

Conducted For

V =	Valid; The Reference Oil / Non-Reference Oil was evaluated in accordance with the test procedure.
I =	Invalid; The Reference / Non-Reference Oil was not evaluated in accordance with the test procedure.
N =	Results cannot be interpreted as representative of oil performance (Non-Reference Oil) and shall not be used in determining average test results using Multiple Test Criteria.

	NR = Non-Reference Oil Test
	RO = Reference Oil Test

Test Number			
Stand:	Stand Run:	Engine Serial No.	Engine Run:
End of Test Date:		End of Test Time:	
Oil Code / CMIR: ^A			
Formulation / Stand Code: ^B			
Altcode 1:	Altcode 2:	Altcode 3:	

In my opinion the test _____ been conducted in a valid manner in accordance with Test Method D8047 and the appropriate amendments through the information letter system. The remarks included in this report describe the anomalies associated with this test.

^A CMIR or Non-Reference Oil Code ^B ACC-Registered Tests Only

Submitted By: _____

Testing Laboratory

Signature

Typed Name

Title

**Caterpillar Oil Aeration Test
Form 2
Table of Contents**

1. Title / Validity Declaration Page	Form 1
2. Table of Contents	Form 2
3. Summary of Test Method	Form 3
4. Test Information	Form 4
5. Test Aeration Graph	Form 5
6. Micromotion Operational Summary	Form 6
7. Engine Operational Summary	Form 7
8. Oil Analysis Summary	Form 8
9. Downtime Summary	Form 9
10. Test Comments	Form 10
11. Test Fuel Batch Analysis	Form 11
12. Build-Up and Hardware Information	Form 12
13. Conformance Statement	Form 13

**Caterpillar Oil Aeration Test
Form 3
Summary of Test Method**

The CAT Oil Aeration Test is an engine-dynamometer test which evaluates the ability of an engine oil to resist aeration.

The test engine is a CAT C-13 diesel engine with ACERT technology. It is an in-line six cylinder, four stroke, turbocharged engine with electronically controlled fuel injection.

Oil Aeration Test Conditions	
Parameter	Value
Time, h	50
Speed, r/min	1800
Load, Nm	0
Fuel Flow, g/min	Record
Coolant Out Temperature, °C	90
Fuel In Temperature, °C	40
Oil Gallery Temperature, °C	90
Intake Air Temperature, ° C	25
Tailpipe Exhaust Temperature, °C	Record
Intake Air Restriction, kPa Absolute	96
Intake Manifold Pressure, kPa	Record
Exhaust Back Pressure, kPa A	104
Coolant System Pressure, kPa	99 - 107
Oil Gallery Pressure, kPa	Record
Crankcase Pressure, kPaA	103
Oil Sump Temp	Record

**Caterpillar Oil Aeration Test
Form 4
Test Information**

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation / Stand Code:		

Test Results

Date Test Started	
Start Time	
Test Length	
Laboratory Oil Code	
TMC Oil Code ^A	
SAE Viscosity ^B	
Engine Number	
Engine run Hours since last rebuild	

Average Oil Aeration (40-50 Hrs) (%)	
Original Result	
Correction Factor	
Severity Adjustment	
Final Original Unit Result	

Last Stand Reference Results

Last Stand Reference Results	
Test Number:	
Oil Code:	
Test Length	
TMC Oil Code ^A	
EOT Date	
EOT Time	
Number of Tests Since Stand Calibration ^C	
Stand Calibration Expiration Date	
Engine Number	
Engine Hours	
Engine Hours since last reference test	
Engine Serial No.	
Average Oil Aeration (40-50 Hrs) (%)	
Original Result	
Correction Factor	
Final Original Unit Result	

^A Reference Tests Only

^B ACC-Registered Tests Only

^C Operationally valid tests only, including current test.

**Caterpillar Oil Aeration Test
Form 5
Test Aeration Graph**

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation / Stand Code:		



40-50 Hr Aeration Slope	
--------------------------------	--

**Caterpillar Oil Aeration Test
Form 6
Micromotion Operational Summary**

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation / Stand Code:		

Controlled Parameters	Parameter	Units	QI Threshold	EOT QI	Target	Average	Samples	BQD	Over/Under Range
	Sample Oil Temperature	°C	0.000		90				
	Sample Oil Flow Rate	L/min	0.000		1.5				
	Sample Oil Pressure	kPaA	0.000		84				
	Average MM enclosure Temp	°C	0.000		50				

Non-Controlled Parameters	Parameter	Units	Typical Value	Average
	Temperature of Sample Oil – Micromotion In	°C	TBD	
	Temperature of Sample Oil – Micromotion Out	°C	TBD	
	Δ Micromotion Sample Temp	°C	TBD	
	Pressure of Sample Oil – Micromotion In	kPaA	TBD	
	Pressure of Sample Oil – Micromotion Out	kPaA	TBD	
	Average Pressure Regulator Controller Output	%	TBD	
	Average Micropump Controller Output	%	TBD	

**Caterpillar Oil Aeration Test
Form 7
Engine Operational Summary**

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation / Stand Code:		

	Parameter	Units	QI Threshold	EOT QI	Target	Average	Samples	BQD	Over/Under Range
Controlled Parameters	Speed	r/min	0.000		1800				
	Inlet Air Temp.	°C	0.000		25				
	Intake Manifold Temp.	°C	0.000		40				
	Fuel In Temp.	°C	0.000		40				
	Coolant Out Temp.	°C	0.000		90				
	Oil Gallery Temp.	°C	0.000		90				
	Exhaust Back Press.	kPaA	0.000		104				
	Crankcase Pressure	kPaA	0.000		103				
	Inlet Air Pressure	kPaA			96.0 ± 1.5				
	Coolant System Press.	kPa			99-107				
Non-Controlled Parameters	Intake Manifold Press.	kPa			TBD				
	Oil Sump Temp.	°C			TBD				
	Oil Gallery Press.	kPa			TBD				
	Fuel Flow	g/min			TBD				
	Ambient Temp	°C			TBD				
	Post Turbo Ex Temp	°C			TBD				
	Blowby	l/min			TBD				
	Barometric Pressure	kPaA			TBD				
	Oil Pump Outlet Pressure	kPa			TBD				

**Caterpillar Oil Aeration Test
Form 8
Oil Analysis Summary**

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation / Stand Code:		

Hours	Viscosity @ 100 °C mm ² /s (D445)	Fuel Dilution Wt. %, (D3524)

Hours	Metal Elements (mg/kg) (D5185)								
	Fe	Pb	Cu	Cr	Al	Si	Sn	Na	K

D4052 Baseline Density	
Temp	Density
30 °C	
40 °C	
50 °C	
60 °C	
70 °C	
80 °C	
90 °C	
Calculated Baseline Density	
dρ/dT	
Predicted at 90 °C	
R ² Value	

**Caterpillar Oil Aeration Test
Form 11
Test Fuel Batch Analysis**

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation / Stand Code:		
Fuel Supplier:		Fuel Batch ID:

Measurement	Specs.	Batch Analysis	Test Method
Total Sulfur, ppm	7 – 15		D 5453
Gravity, °API	34 – 37		D 4052
Hydrocarbon Composition			
Aromatics, % Weight	26 – 31.5		D 5186
Olefins, % Volume	Report		D 1319
Cetane Index	Report		D 976
Cetane No.	43 – 47		D 613
Copper Strip Corrosion	1 Maximum		D 130
Flash Point, °C	54 Minimum		D 93
Pour Point, °C	-18 Maximum		D 97
Carbon Residue on 10% Residuum, %	0.35 Maximum		D 524 (10% Bottoms)
Water & Sediment, % Volume	0.05 Maximum		D 2709
Viscosity, cSt @ 40°C	2.0 – 2.6		D 445
Total Acid Number	0.05 Maximum		D 664
Strong Acid Number	0.00 Maximum		D 664
Accelerated Stability	1.5 max		D 2274
Ash, % Weight	0.005 Maximum		D 482
SLBOCLE, g	3100 min ^A		D 6078 ^A
90% Distillation, °C	282 – 338		D 86

^A May be altered to be consistent with CARB or ASTM diesel fuel specifications.

**Caterpillar Oil Aeration Test
Form 12
Build-Up and Hardware Information**

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation / Stand Code:		

Part	Part Number
Intake Valve	
Exhaust Valve	
Cylinder Head	
Head Gasket	
Pistons	
Injectors	
Rod Bearings	
Liners	
Top Ring	
2 nd Ring	
Oil Ring	
Rocker Cover Gasket	
Oil Pan Gasket	
Front Cover Gasket	
Valve Guides	
Valve Guide Seals	
Oil Filter	
Oil Filter Date Code	
Low Pressure Turbo	
High Pressure Turbo	
Micromotion Serial Number	
Micromotion Calibration Date	

**Caterpillar Oil Aeration Test
Form 13
American Chemistry Council Code of Practice
Test Laboratory Conformance Statement**

Test Laboratory				
Test Sponsor				
Formulation/Stand Code				
Test Number				
Start Date		Start Time		Time Zone

Declarations

- No. 1 All requirements of the ACC Code of Practice for which the test laboratory is responsible were met in the conduct of this test. Yes _____ No _____*
- No. 2 The laboratory ran this test for the full duration following all procedural requirements; and all operational validity requirements of the latest version of the applicable test procedure (ASTM or other), including all updates issued by the organization responsible for the test, were met. Yes _____ No _____*
- If the response to this Declaration is “No”, does the test engineer consider the deviations from operational validity requirements that occurred to be beyond the control of the laboratory? Yes _____* No _____
- No. 3 A deviation occurred for one of the test parameters identified by the organization responsible for the test as being a special case. Yes _____* No _____ *(This currently applies only to specific deviations identified in the ASTM Information Letter System)*

Check The Appropriate Conclusion

	Operational review of this test indicates that the results should be included in the Multiple Test Acceptance Criteria calculations.
	*Operational review of this test indicates that the results should not be included in the Multiple Test Acceptance Criteria calculations.

Note: *Supporting comments are required for all responses identified with an asterisk.*

Comments

Signature

Date

Typed Name

Title