

**ASTM Test Method D 6082
High Temperature Foaming
Characteristics of Lubricating Oils**

Version D6082 VERSION 20020311

Conducted For

CC
CC

C	V = Valid
	I = Invalid

CC	NR = Non-Reference Test Oil
	RO = Reference Oil Result

Test Number	
Instrument ID: CCCCCCCCCCCCCCCCCC	Test Run: CCCCCCCCCC

Date Completed: YYYYMMDD	Time Completed: HH:MM
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	
Alternate Codes:	CCCCCCCCCCCCCCCC CCCCCCCCCCCCCCCC CCCCCCCCCCCCCCCC CCCCCCCCCCCCCCCC

In my opinion this test CCCCCCCC been conducted in a valid manner in accordance with the Test Method D6082 and the appropriate amendments through the information letter system. The remarks included in this report describe the anomalies associated with this test.

Submitted By: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
Testing Laboratory

 Signature Image
Signature

)CCC

Typed Name

)CCC

Title

**ASTM Test Method D 6082
High Temperature Foaming
Characteristics Of Lubricating Oils
Form 2**

Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
Lab Sample Code: CCCCCCCCCCCCCCCCCC

Testing Lab: CC	TMC Reference Oil ID: CCCCCC
Date Completed: YYYYMMDD	Time Completed: HH:MM

Instrument ID: CCCCCCCCCCCCCCCCCC	
Test Run: CCCCCCCCCC	
Date of Last TMC Calibration: YYYYMMDD	TMC Calibration Expiration Date: YYYYMMDD

Operational Parameters			
Make of Foam Bath	CCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Model of Foam Bath	CCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Type of Bath (Air, Oil)	CCC	Was the Blending Option used? (Y/N)	C
Bath Temperature, °C	S123.1	Blender Calibration, rpm	S12345
Barometric Pressure ^A, mm Hg	S123.1	Diffuser Pore Size, µm	S12
Air Flow, ml/min	S123	Diffuser Permeability, ml/min	S1234
Device Used to Measure Air Flow	CCCCCCCCCCCCCCCCCCCCCCCCCCCC		

Test Results	
Foam Tendency: Volume of Static Foam Immediately Before Air Disconnect, ml	S123
Foam Stability: Volume of Static Foam One Minute After Air Disconnect, ml	S123

^ANot required to report (for information only)

Result Summary

