

**ASTM TEST METHOD D6082
HIGH TEMPERATURE FOAMING
CHARACTERISTICS OF LUBRICATING OILS**

VERSION *D6082 VERSION 20020311 BETA*

CONDUCTED FOR

CC
CC

<i>C</i>	V = VALID
	I = INVALID

<i>CC</i>	NR = Non Reference Oil Test
	RO = Reference Oil Test

Test Number	
Instrument ID: <i>CCCCCCCCCCCCCCCCCCCC</i>	Test Run Number: <i>CCCCCCCCCC</i>

Date Completed: <i>YYYYMMDD</i>	EOT Time: <i>HH:MM</i>
Oil Code: <i>CC</i>	
Alternate Codes:	<i>CCCCCCCCCCCCCCCC</i> <i>CCCCCCCCCCCCCCCC</i> <i>CCCCCCCCCCCCCCCC</i>

In my opinion this test <i>CCCCCCCC</i> been conducted in a manner in accordance with Test Method D6082 and the appropriate amendments through the information letter system. The remarks included in this report describe the anomalies associated with this test.

SUBMITTED BY: CC
Testing Laboratory

Signature Image

Signature

CC
Typed Name

CC
Title

**ASTM TEST METHOD D6082
HIGH TEMPERATURE FOAMING
CHARACTERISTICS OF LUBRICATING OILS
FORM 2**

Oil Code:	cc
Lab Sample Code:	cccccccccccccccccccc

Testing Lab: CC	TMC Reference Oil ID: ccccc
Date Completed: YYYYMMDD	Time Completed: HH:MM

Instrument ID: ccccccccccccccccccccc	
Test Run No.: ccccccccc	
Date of Last TMC Calibration: YYYYMMDD	TMC Calibration Expiration Date: YYYYMMDD

OPERATIONAL PARAMETERS			
Make of Foam Bath:	cccccccccccccccccccccccccccccccccccc		
Model of Foam Bath:	cccccccccccccccccccccccccccccccccccc		
Type of Bath (Air, Oil):	CCC	Was the Blending Option used (Y/N)?:	C
Bath Temperature, °C:	S123.1	Blender Calibration, rpm:	S12345
Barometric Pressure ^A , mm Hg:	S123.1	Diffuser Pore Size, µm:	S12
Air Flow, ml/min:	S123	Diffuser Permeability, ml/min:	S1234
Device Used to Measure Air Flow:	cc		

TEST RESULTS	
Foam Tendency: Volume of Static Foam Immediately Before Air Disconnect, ml:	S123
Foam Stability: Volume of Static Foam One Minute After Air Disconnect, ml:	S123

^A Not required to report (for information only).

RESULT SUMMARY

