

**D xxxx – Engine Oil Elastomer Compatibility Form 1 – Validity Declaration**

Version:  
Conducted for:

	<b>V = Valid</b>
	<b>I = Invalid</b>

Elastomer Type	Bath Number	Elastomer Batch	Oilcode	CMIR	SOT Date	SOT Time	EOT Date	EOT Time
Nitrile								
Polyacrylate								
Fluoroelastomer								
Silicon								
Vamac								

Alternate Codes:			
------------------	--	--	--

In my opinion this test _____ been conducted in accordance with Test Method D xxxx and the appropriate amendments through the information letter system. The remarks on Form 7 describe any anomalies associated with this test.
--

Submitted By:

\_\_\_\_\_ Testing Laboratory

\_\_\_\_\_ Signature

\_\_\_\_\_ Typed Name

\_\_\_\_\_ Title

**D xxxx – Engine Oil Elastomer Compatibility  
Form 2 – Candidate Data**

Sample Code:	Lab:	EOT Date: Test Length:
--------------	------	---------------------------

Elastomer Identification	TMC Identification	Parameter	Specification Limit	Acceptance Limits		Reference Result	Candidate Result
				Updated on:			
Type:	Industry Oil:	Volume Change	+5% to -3%		To		
Nitrile		Hardness	+7 pts to -5 pts		To		
Batch:	CMIR:	Tensile Strength	+10% to -TMC 1006		To		
		Elongation	+10% to -TMC 1006		To		

Elastomer Identification	TMC Identification	Parameter	Specification Limit	Acceptance Limits		Reference Result	Candidate Result
				Updated on:			
Type:	Industry Oil:	Volume Change	+5% to -3%		to		
Polyacrylate		Hardness	+8 pts to -5 pts		to		
Batch:	CMIR:	Tensile Strength	+18% to -15%		to		
		Elongation	+10% to -35%		to		

Elastomer Identification	TMC Identification	Parameter	Specification Limit	Acceptance Limits		Reference Result	Candidate Result
				Updated on:			
Type:	Industry Oil:	Volume Change	+5% to -2%		to		
Fluoroelastomer		Hardness	+7 pts to -5 pts		to		
Batch:	CMIR:	Tensile Strength	+10% to -TMC 1006		to		
		Elongation	+10% to -TMC 1006		to		

Elastomer Identification	TMC Identification	Parameter	Specification Limit	Acceptance Limits		Reference Result	Candidate Result
				Updated on:			
Type:	Industry Oil:	Volume Change	+TMC 1006 to -3%		to		
Silicon		Hardness	+5 pts to -TMC 1006		to		
Batch:	CMIR:	Tensile Strength	+10% to -45%		to		
		Elongation	+20% to -30%		to		

Elastomer Identification	TMC Identification	Parameter	Specification Limit	Acceptance Limits		Reference Result	Candidate Result
				Updated on:			
Type:	Industry Oil:	Volume Change	Report		to		
Vamac		Hardness	Report		to		
Batch:	CMIR:	Tensile Strength	Report		to		
		Elongation	Report		to		



**D xxxx – Engine Oil Elastomer Compatibility  
Form 4 – Results Summary – Non-Reference Oil - Vamac**

Sample Code:	Lab:
Lab Oil Code:	

Elastomer Type:		Elastomer Batch Code:			
SOT Time:		EOT Time:		Bath Number:	
SOT Date:		EOT Date:			
Test Temperature, °C	Test Duration, Hours	Volume Change, %	Hardness Change, Points	Tensile Strength Change, %	Elongation Change, %
Average					
Standard Deviation					



**D xxxx – Engine Oil Elastomer Compatibility  
Form 6 – Results Summary – Reference Oil - Vamac**

Lab Oil Code:	Lab:
---------------	------

CMIR:		TMC Industry Oil Code:			
Elastomer Type:		Elastomer Batch Code:			
SOT Time:		EOT Time:		Bath Number:	
SOT Date:		EOT Date:			
Test Temperature, °C	Test Duration, Hours	Volume Change, %	Hardness Change, Points	Tensile Strength Change, %	Elongation Change, %
Average					
Standard Deviation					

