

**REPORT ON
SEQUENCE IIIF EVALUATION**

VERSION 20010529

CONDUCTED FOR

*TSTSPON1
TSTSPON2*

<i>LABVALID</i>	V = VALID
	I = INVALID
	N = RESULTS CANNOT BE INTERPRETED AS REPRESENTATIVE OF OIL PERFORMANCE (NON-REFERENCE OIL) AND SHALL NOT BE USED FOR MULTIPLE TEST ACCEPTANCE

<i>TSTOIL</i>	NR = Non-Reference Oil Test
	RO = Reference Oil Test

Test Number					
Test Stand	<i>STAND</i>	Stand Test Number	<i>STRUN</i>	Lab Test Number	<i>LABRUN</i>
Oil Code	<i>OILCODE</i>				
Formulation/Stand Code	<i>FORM</i>				
Alternate Codes	<i>ALTCODE1</i>	<i>ALTCODE2</i>	<i>ALTCODE3</i>		
EOT Date	<i>DTCOMP</i>	EOT Time	<i>EOTTIME</i>		

In my opinion this test *OPVALID* been conducted in a valid manner in accordance with the latest draft of Sequence IIIF procedure and the appropriate amendments through the information letter system. The remarks included in the report describe the anomalies associated with this test.

SUBMITTED BY: *SUBLAB*

Testing Laboratory

SUBSIGIM

Signature

SUBNAME

Typed Name

SUBTITLE

Title

Form 2

Sequence III F

Table of Contents

1.	Title / Validity Declaration Page	Form 1
2.	Table of Contents	Form 2
3.	Summary of Test Method	Form 3
4.	Test Result Summary	Form 4
5.	Operational Summary	Form 5
6.	Used Oil Analysis	Form 6
7.	Valve Lifter and Camshaft Wear Results	Form 7
8.	Summary of Oil Ring Land Deposit Rating	Form 8
9.	Summary of Piston Deposits	Form 9
10.	Blowby Values & Plot	Form 10
11.	Viscosity Increase Plot	Form 11
12.	Hardware Information	Form 12
13.	Downtime & Outlier Report Form	Form 13

Sequence IIIF

FORM 3

Summary of Test Method

The Sequence IIIF Test is a fired-engine, dynamometer lubricant test for evaluating automotive engine oils for certain high-temperature performance characteristics, including oil thickening, varnish deposition, oil consumption, and engine wear. Such oils include both single viscosity grade and multiviscosity grade oils that are used in spark-ignition, gasoline-fueled engines, as well as diesel engines.

The Sequence IIIF Test utilizes a 1996 model Buick 3800 Series II, water-cooled, 4 cycle, V-6 engine as the test apparatus. The Sequence IIIF test engine is an overhead valve design (OHV) and uses a single camshaft operating both intake and exhaust valves via pushrods and hydraulic valve lifters in a sliding-follower arrangement. The engine uses one intake and one exhaust valve per cylinder. Induction is handled by a modified GM port fuel injection system setting the Air-to-Fuel ratio at 15:1. The test engine is overhauled prior to each test, during which critical engine dimensions are measured and rated or measured parts (pistons, camshaft, valve lifters, etc.) are replaced.

The Sequence IIIF Test consists of a 10-minute operational check, followed by 80 hours of engine operation at moderately high speed, load, and temperature conditions. The 80-hour segment is broken down into eight 10-hour test segments. Following each 10-hour segment, and the 10-minute operational check, oil samples are drawn from the engine. The kinematic viscosities of the 10-hour segment samples are compared to the viscosity of the 10-minute sample to determine the viscosity increase of the test oil.

The Sequence IIIF Test is operated at the following test states during the 80-hour portion of the test:

Parameter	Set Point
Engine Speed	3600 r/min
Engine Load	200 N-m
Oil Filter Block Temperature	155 °C
Coolant Outlet Temperature	122 °C
Fuel Pressure	365 kPa
Intake Air Temperature	27 °C
Intake Air Pressure	0.05 kPa
Intake Air Dew Point	16.1 °C
Exhaust Back Pressure	6 kPa
Engine Coolant Flow	160 L/min
Breather Tube Coolant Flow	10 L/min
Air-to-Fuel Ratio	15.0:1
Breather Tube Coolant Outlet Temperature	40 °C

**SEQUENCE IIIF
FORM 4
TEST RESULT SUMMARY**

LAB	<i>LAB</i>	OIL CODE	<i>OILCODE</i>
TEST STAND NO.	<i>STAND</i>	TEST NO.	<i>STAND - STRUN - LABRUN</i>
LABORATORY OIL CODE	<i>LABOCODE</i>		
FORMULATION STAND CODE	<i>FORM</i>		

DATE STARTED	<i>DTSTRT</i>	ENGINE NO.	<i>ENGINENO</i>
TIME STARTED	<i>STRTIME</i>	FUEL BATCH	<i>FUELBTID</i>
DATE COMPLETED	<i>DTCOMP</i>	SAE VISCOSITY	<i>SAEVISC</i>
TIME COMPLETED	<i>EOTTIME</i>	TMC OIL CODE	<i>AIND</i>
TEST LENGTH	<i>TESTLEN</i>		

Pass/Fail Results						
	Viscosity Increase (%)	Average Cam + Lifter Wear (µm)	Average Weighted Piston Deposits (merits)	Average Piston Skirt Varnish (merits)	Number of Hot-Stuck Rings	Oil Consumption (L) ^B
Original Units	<i>PVIS</i>	<i>ACLW</i>	<i>WPD</i>	<i>APV</i>	<i>HSTUKT</i>	<i>OILCON</i>
Transformed Results	<i>TPVIS</i>					
Industry Correction Factor	<i>PVIS_CF</i>	<i>ACLW_CF</i>	<i>WPD_CF</i>	<i>APV_CF</i>		
Corrected Transformed Result	<i>PVIS_COR</i>					
Severity Adjustment	<i>PVIS_SA</i>		<i>WPD_SA</i>	<i>APV_SA</i>		
Final Transformed Result	<i>TPVISFNL</i>					
Final Original Unit Result	<i>PVISFNL</i>	<i>ACLWFNL</i>	<i>WPDFNL</i>	<i>APVFNL</i>		

Additional Results			
Oil Consumption Hours, h ^B	<i>OCNHRS</i>	Average Oil Ring Plugging, %	<i>ORPAVG</i>
Maximum Cam + Lifter Wear, µm	<i>MCLW</i>	Number of Cold-Stuck Rings	<i>CSTUKT</i>

Most Recent Stand Reference Oil Test History^C			
Test Number	<i>RSTAND - RSTRUN - RLABRUN</i>		
Oilcode	<i>ROILCODE</i>		
Date Completed	<i>RDTCOMP</i>	TMC Oil Code	<i>RIND</i>
Final Viscosity Increase, %	<i>RPVISFNL</i>	Fuel Batch	<i>RFUELBD</i>
Final Average Piston Skirt Varnish, merits	<i>RAPVFNL</i>		
Final Average Cam + Lifter Wear, µm	<i>RACLWFNL</i>		
Final Maximum Cam + Lifter Wear, µm	<i>RMCLWFNL</i>		
Final Average Weighted Piston Deposit, merits	<i>RWPDFNL</i>		

^A Reference Oil Tests Only

^B Test Hours at which Oil Consumption was calculated

^C Non-Reference Oil Tests Only

**SEQUENCE IIIF
FORM 5
OPERATIONAL SUMMARY**

LAB	LAB	OIL CODE	OILCODE
TEST STAND NO.	STAND	TEST NO.	STAND - STRUN - LABRUN
LABORATORY OIL CODE	LABOCODE		
FORMULATION STAND CODE	FORM		

	Parameter	Units	QI Threshold	EOT QI	Target	Average	Standard Deviation	Number Of	
								Samples	BQD
Controlled Parameters	Speed	r/min	0.000	QRPM	3600	ARPM	SRPM	NRPM	BRPM
	Load	Nm	0.000	QLOAD	200	ALOAD	SLOAD	NLOAD	BLOAD
	Oil Filter Block	°C	0.000	QOTEMP	155.0	AOTEMP	SOTEMP	NOTEMP	BOTEMP
	Engine Coolant Out	°C	0.000	QCOLOUT	122.0	ACOLOUT	SCOLOUT	NCOLOUT	BCOLOUT
	Condenser Coolant Out	°C	0.000	QCCOLOUT	40.0	ACCOLOUT	SCCOLOUT	NCCOLOUT	BCCOLOUT
	Left Air-to-Fuel Ratio		0.000	QLAFR	15.0	ALAFR	SLAFR	NLAFR	BLAFR
	Right Air-to-Fuel Ratio		0.000	QRAFR	15.0	ARAFR	SRAFR	NRAFR	BRAFR
	Left Exhaust Back Pressure	kPa	0.000	QLEXBP	6.0	ALEXBP	SLEXBP	NLEXBP	BLEXBP
	Right Exhaust Back Pressure	kPa	0.000	QREXBP	6.0	AREXBP	SREXBP	NREXBP	BREXBP
	Intake Air	kPa	0.000	QINAIR	0.05	AINAIR	SINAIR	NINAIR	BINAIR
	Engine Coolant Flow	L/min	0.000	QCOLFLO	160.0	ACOLFLO	SCOLFLO	NCOLFLO	BCOLFLO

	Parameter	Units	Average	Standard Deviation	Number Of	
					Samples	BQD
Non-controlled Parameters	Oil Sump	°C	AOSUMP	SOSUMP	NOSUMP	BOSUMP
	Pump Outlet Pressure	kPa	APOUTP	SPOUTP	NPOUTP	BPOUTP
	Gallery Pressure	kPa	AOILPRS	SOILPRS	NOILPRS	BOILPRS
	Engine Coolant In	°C	AECOLIN	SECOLIN	NECOLIN	BECOLIN
	Fuel Inlet	°C	AFUELIN	SFUELIN	NFUELIN	BFUELIN
	Intake Air	°C	AINAT	SINAT	NINAT	BINAT
	Intake Air Dew Point	°C	AINDEW	SINDEW	NINDEW	BINDEW
	Intake Vacuum	kPa	AINVAC	SINVAC	NINVAC	BINVAC
	Crankcase	kPa	ACCASEP	SCCASEP	NCCASEP	BCCASEP
	Fuel Pressure	kPa	APFUEL	SPFUEL	NPFUEL	BPFUEL

OIL CONSUMPTION DATA									
HOURS	Initial Run-in	CONH01	CONH02	CONH03	CONH04	CONH05	CONH06	CONH07	CONH08
LEVEL (ml) low	OILLINI	OILLH01	OILLH02	OILLH03	OILLH04	OILLH05	OILLH06	OILLH07	OILLH08

NOx Measurement			
Hours	NOXHH07	NOXHH039	NOXHH079
NOx, ppm	NOX_H007	NOX_H039	NOX_H079

**SEQUENCE IIIF
FORM 6
USED OIL ANALYSIS RESULTS**

LAB	<i>LAB</i>	OIL CODE	<i>OILCODE</i>
TEST STAND NO.	<i>STAND</i>	TEST NO.	<i>STAND - STRUN - LABRUN</i>
LABORATORY OIL CODE	<i>LABOCODE</i>		
FORMULATION STAND CODE	<i>FORM</i>		

VISCOSITY INCREASE DATA (cSt AT 40°C)			
HOURS	VISCOSITY ^A	CHANGE	PERCENT
NEW OIL	<i>VNEW</i>		
INITIAL ^B	<i>VINI</i>		
<i>VISTH010</i>	<i>VIS_H010</i>	<i>DVISH010</i>	<i>PVISH010</i>
<i>VISTH020</i>	<i>VIS_H020</i>	<i>DVISH020</i>	<i>PVISH020</i>
<i>VISTH030</i>	<i>VIS_H030</i>	<i>DVISH030</i>	<i>PVISH030</i>
<i>VISTH040</i>	<i>VIS_H040</i>	<i>DVISH040</i>	<i>PVISH040</i>
<i>VISTH050</i>	<i>VIS_H050</i>	<i>DVISH050</i>	<i>PVISH050</i>
<i>VISTH060</i>	<i>VIS_H060</i>	<i>DVISH060</i>	<i>PVISH060</i>
<i>VISTH070</i>	<i>VIS_H070</i>	<i>DVISH070</i>	<i>PVISH070</i>
<i>VISTH080</i>	<i>VIS_H080</i>	<i>DVISH080</i>	<i>PVISH080</i>
<i>TESTLEN</i>	<i>WISEOT</i>	<i>DWISEOT</i>	<i>PVIS</i>

^A 8000 cSt is maximum allowable viscosity

^B At end of leveling run

Results of ICP Analysis of Used Oil										
Test Hours	Initial	<i>TST_H010</i>	<i>TST_H020</i>	<i>TST_H030</i>	<i>TST_H040</i>	<i>TST_H050</i>	<i>TST_H060</i>	<i>TST_H070</i>	<i>TST_H080</i>	<i>TESTLEN</i>
Iron	<i>FEWMINI</i>	<i>FEWMH010</i>	<i>FEWMH020</i>	<i>FEWMH030</i>	<i>FEWMH040</i>	<i>FEWMH050</i>	<i>FEWMH060</i>	<i>FEWMH070</i>	<i>FEWMH080</i>	<i>FEWMEOT</i>
Copper	<i>CUWMINI</i>	<i>CUWMH010</i>	<i>CUWMH020</i>	<i>CUWMH030</i>	<i>CUWMH040</i>	<i>CUWMH050</i>	<i>CUWMH060</i>	<i>CUWMH070</i>	<i>CUWMH080</i>	<i>CUWMEOT</i>
Lead	<i>PBWMINI</i>	<i>PBWMH010</i>	<i>PBWMH020</i>	<i>PBWMH030</i>	<i>PBWMH040</i>	<i>PBWMH050</i>	<i>PBWMH060</i>	<i>PBWMH070</i>	<i>PBWMH080</i>	<i>PBWMEOT</i>

Cold Crank Simulator Results, D 5293	
Final Temperature, °C	<i>CCSTEMP</i>
Final Cold-Crank Simulator Viscosity, cP	<i>CCS</i>

Mini-Rotary Viscometer Results, D 4684	
MRV Temperature, °C	<i>MRVTEMP</i>
MRV Result, cP	<i>MRV</i>
Yield Stress, cP	<i>YSTRESS</i>

**SEQUENCE IIIF
FORM 7
VALVE LIFTER AND CAMSHAFT WEAR RESULTS**

LAB	<i>LAB</i>	OIL CODE	<i>OILCODE</i>
TEST STAND NO.	<i>STAND</i>	TEST NO.	<i>STAND - STRUN - LABRUN</i>
LABORATORY OIL CODE	<i>LABOCODE</i>		
FORMULATION STAND CODE	<i>FORM</i>		

NUMBER	CAMSHAFT LOBE, μm	VALVE LIFTER, μm	CAM & LIFTER WEAR, μm
1	<i>CAMW01</i>	<i>LFTW01</i>	<i>CLW01</i>
2	<i>CAMW02</i>	<i>LFTW02</i>	<i>CLW02</i>
3	<i>CAMW03</i>	<i>LFTW03</i>	<i>CLW03</i>
4	<i>CAMW04</i>	<i>LFTW04</i>	<i>CLW04</i>
5	<i>CAMW05</i>	<i>LFTW05</i>	<i>CLW05</i>
6	<i>CAMW06</i>	<i>LFTW06</i>	<i>CLW06</i>
7	<i>CAMW07</i>	<i>LFTW07</i>	<i>CLW07</i>
8	<i>CAMW08</i>	<i>LFTW08</i>	<i>CLW08</i>
9	<i>CAMW09</i>	<i>LFTW09</i>	<i>CLW09</i>
10	<i>CAMW10</i>	<i>LFTW10</i>	<i>CLW10</i>
11	<i>CAMW11</i>	<i>LFTW11</i>	<i>CLW11</i>
12	<i>CAMW12</i>	<i>LFTW12</i>	<i>CLW12</i>
MAXIMUM	<i>MAXCW</i>	<i>MAXLFTW</i>	<i>MCLW</i>
MINIMUM	<i>MINCW</i>	<i>MINLFTW</i>	<i>MINCLW</i>
AVERAGE	<i>AVGCW</i>	<i>AVGLFTW</i>	<i>ACLW</i>

SEQUENCE IIIF
FORM 8
SUMMARY OF OIL RING LAND DEPOSIT RATING

LAB	<i>LAB</i>	OIL CODE	<i>OILCODE</i>
TEST STAND NO.	<i>STAND</i>	TEST NO.	<i>STAND - STRUN - LABRUN</i>
LABORATORY OIL CODE	<i>LABOCODE</i>		
FORMULATION STAND CODE	<i>FORM</i>		
RATER	<i>RLDRATER</i>	RATING DATE	<i>RLDRTDT</i>

PISTON	OIL RING LAND DEPOSIT, MERITS	% CHIPPED
1	<i>ORLD1</i>	<i>ORCHIP1</i>
2	<i>ORLD2</i>	<i>ORCHIP2</i>
3	<i>ORLD3</i>	<i>ORCHIP3</i>
4	<i>ORLD4</i>	<i>ORCHIP4</i>
5	<i>ORLD5</i>	<i>ORCHIP5</i>
6	<i>ORLD6</i>	<i>ORCHIP6</i>
Average	<i>ORLD</i>	<i>AVGORCHP</i>

PISTON	% OIL RING PLUGGING	RING STICKING ^A	
		HOT-STUCK RINGS	COLD-STUCK RINGS
1	<i>ORP1</i>	<i>HSTUK1</i>	<i>CSTUK1</i>
2	<i>ORP2</i>	<i>HSTUK2</i>	<i>CSTUK2</i>
3	<i>ORP3</i>	<i>HSTUK3</i>	<i>CSTUK3</i>
4	<i>ORP4</i>	<i>HSTUK4</i>	<i>CSTUK4</i>
5	<i>ORP5</i>	<i>HSTUK5</i>	<i>CSTUK5</i>
6	<i>ORP6</i>	<i>HSTUK6</i>	<i>CSTUK6</i>
Total		<i>HSTUKT</i>	<i>CSTUKT</i>
Average	<i>ORPAVG</i>		

^A Possible values T = top compression ring
B = bottom compression ring
O = oil ring
N = none

SEQUENCE III F
FORM 9
SUMMARY OF PISTON DEPOSITS

LAB	LAB	OIL CODE	OILCODE
TEST STAND NO.	STAND	TEST NO.	STAND - STRUN - LABRUN
LABORATORY OIL CODE	LABOCODE		
FORMULATION STAND CODE	FORM		
RATER	APVRATER	RATING DATE	APVRTDT

NOTE: CRC Manual 14 used for ALL Ratings

NOTE: These are unweighted ratings.

	Grooves, merits			Lands, merits		Undercrown, merits
	1	2	3	2	3	
Piston 1	G1P1	G2P1	G3P1	L2P1	ORLD1	UCP1
Piston 2	G1P2	G2P2	G3P2	L2P2	ORLD2	UCP2
Piston 3	G1P3	G2P3	G3P3	L2P3	ORLD3	UCP3
Piston 4	G1P4	G2P4	G3P4	L2P4	ORLD4	UCP4
Piston 5	G1P5	G2P5	G3P5	L2P5	ORLD5	UCP5
Piston 6	G1P6	G2P6	G3P6	L2P6	ORLD6	UCP6
WF	0.05	0.10	0.20	0.15	0.30	0.10

NOTE: These are unweighted ratings.

	Piston Skirt Varnish, merits		
	Thrust	Anti-Thrust	Average
Piston 1	PSVT1	PSVA1	PSVAV1
Piston 2	PSVT2	PSVA2	PSVAV2
Piston 3	PSVT3	PSVA3	PSVAV3
Piston 4	PSVT4	PSVA4	PSVAV4
Piston 5	PSVT5	PSVA5	PSVAV5
Piston 6	PSVT6	PSVA6	PSVAV6
Average	PSVTAV	PSVAAV	APV
WF			0.10

PSVAV_x = (PSVT_x + PSVA_x)/2 where x = Number of Piston
 PSVTAV = average of six Thrust Piston Skirt ratings.
 PSVAAV = average of six Anti-Thrust Piston Skirt ratings.
 APV = average of all 12 Piston Skirt ratings.

	Total Weighted Deposits, merits
Piston 1	WPD1
Piston 2	WPD2
Piston 3	WPD3
Piston 4	WPD4
Piston 5	WPD5
Piston 6	WPD6

$WPD_x = (WF * G1P_x) + (WF * G2P_x) + (WF * G3P_x) + (WF * L2P_x) + (WF * ORLD_x) + (WF * UCP_x) + (WF * PSVAV_x)$
 where: x = Number of Piston
 WF = Appropriate Weighting Factor (WF) for part, from table.

Average Weighted Piston Deposits, merits	WPD	$WPD = (WPD1 + WPD2 + WPD3 + WPD4 + WPD5 + WPD6) / 6$
--	-----	---

**SEQUENCE IIIF
FORM 10
BLOWBY VALUES & PLOT**

LAB	<i>LAB</i>	OIL CODE	<i>OILCODE</i>
TEST STAND NO.	<i>STAND</i>	TEST NO.	<i>STAND - STRUN - LABRUN</i>
LABORATORY OIL CODE	<i>LABOCODE</i>		
FORMULATION STAND CODE	<i>FORM</i>		

Blowby Plot

BLOWBYIM




Test Hours	<i>BBYTH001</i>	<i>BBYTH006</i>	<i>BBYTH011</i>	<i>BBYTH016</i>	<i>BBYTH021</i>	<i>BBYTH026</i>	<i>BBYTH031</i>	<i>BBYTH036</i>	<i>BBYTH041</i>	<i>BBYTH046</i>
Blowby, L/min.	<i>BLWBH001</i>	<i>BLWBH006</i>	<i>BLWBH011</i>	<i>BLWBH016</i>	<i>BLWBH021</i>	<i>BLWBH026</i>	<i>BLWBH031</i>	<i>BLWBH036</i>	<i>BLWBH041</i>	<i>BLWBH046</i>
Test Hours	<i>BBYTH051</i>	<i>BBYTH056</i>	<i>BBYTH061</i>	<i>BBYTH066</i>	<i>BBYTH071</i>	<i>BBYTH076</i>	<i>BBYTH079</i>			Average
Blowby, L/min.	<i>BLWBH051</i>	<i>BLWBH056</i>	<i>BLWBH061</i>	<i>BLWBH066</i>	<i>BLWBH071</i>	<i>BLWBH076</i>	<i>BLWBH079</i>			<i>ABLOBY</i>

SEQUENCE III F
FORM 11
VISCOSITY INCREASE PLOT

LAB	<i>LAB</i>	OIL CODE	<i>OILCODE</i>
TEST STAND NO.	<i>STAND</i>	TEST NO.	<i>STAND - STRUN - LABRUN</i>
LABORATORY OIL CODE	<i>LABOCODE</i>		
FORMULATION STAND CODE	<i>FORM</i>		

VISINIM



**SEQUENCE IIIF
FORM 12
HARDWARE INFORMATION**

LAB	<i>LAB</i>	OIL CODE	<i>OILCODE</i>
TEST STAND NO.	<i>STAND</i>	TEST NO.	<i>STAND - STRUN - LABRUN</i>
LABORATORY OIL CODE	<i>LABOCODE</i>		
FORMULATION STAND CODE	<i>FORM</i>		

Build Completion Date	<i>BUILDDT</i>	Piston Batch (Code)	<i>PISTBAT</i>
Block Serial Number	<i>BLOCKSN</i>	Piston Size (Grade)	<i>PISTSIZE</i>
Crankshaft Serial Number	<i>CRANKSN</i>	Piston Ring Batch Code	<i>RINGCODE</i>
Camshaft Serial Number	<i>CAMSN</i>	Oil Filter Batch Code	<i>OILFIBAT</i>
Cylinder Head Serial Number, Left	<i>LHEADSN</i>	Intake Valve Seals Batch Code	<i>INVS LBAT</i>
Cylinder Head Serial Number, Right	<i>RHEADSN</i>	Valve Springs Batch Code	<i>VALSPBAT</i>
Bearing Kit Serial Number	<i>BRNGSN</i>	Lifter Serial Number	1 <i>LFTR1SN</i>
Top Ring Gap, mils	<i>TRINGGAP</i>		2 <i>LFTR2SN</i>
Bottom Ring Gap, mils	<i>BRINGGAP</i>		3 <i>LFTR3SN</i>
			4 <i>LFTR4SN</i>
			5 <i>LFTR5SN</i>
			6 <i>LFTR6SN</i>
			7 <i>LFTR7SN</i>
			8 <i>LFTR8SN</i>
			9 <i>LFTR9SN</i>
			10 <i>LFTR10SN</i>
			11 <i>LFTR11SN</i>
			12 <i>LFTR12SN</i>

**SEQUENCE IIIF
FORM 13
DOWNTIME & OUTLIER REPORT FORM**

LAB	<i>LAB</i>	OIL CODE	<i>OILCODE</i>
TEST STAND NO.	<i>STAND</i>	TEST NO.	<i>STAND - STRUN - LABRUN</i>
LABORATORY OIL CODE	<i>LABOCODE</i>		
FORMULATION STAND CODE	<i>FORM</i>		

Downtime Occurrences		<i>DWNOCR</i>	
Test Hours	Date	Total Downtime	Reasons
<i>DOWNR001</i>	<i>DDATR001</i>	<i>DTIMR001</i>	<i>DREAR001</i>
Total Downtime		<i>TOTLDOWN</i> Maximum allowable downtime: 24 hours	

Other Comments & Outliers	<i>TOTCOM</i>
<i>OCOMR001</i>	