

**REPORT ON  
SEQUENCE IIIG EVALUATION**

VERSION *IIIG VERSION 20030331*

CONDUCTED FOR

CC  
CC

<i>C</i>	V = VALID
	I = INVALID
	N = RESULTS CANNOT BE INTERPRETED AS REPRESENTATIVE OF OIL PERFORMANCE (NON-REFERENCE OIL) AND SHALL NOT BE USED FOR MULTIPLE TEST ACCEPTANCE

<i>CC</i>	NR = Non-Reference Oil Test
	RO = Reference Oil Test

Test Number					
Test Stand	<i>CCCCC</i>	Stand Test Number	<i>CCCC</i>	Lab Test Number	<i>CCCCC</i>
Oil Code	<i>CC</i>				
Formulation/Stand Code	<i>CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC</i>				
Alternate Codes	<i>CCCCCCCCCCCCCCCC</i>	<i>CCCCCCCCCCCCCCCC</i>	<i>CCCCCCCCCCCCCCCC</i>	<i>CCCCCCCCCCCCCCCC</i>	<i>CCCCCCCCCCCCCCCC</i>
EOT Date	<i>YYYYMMDD</i>	EOT Time	<i>HH:MM</i>		

In my opinion this test *CCCCC* been conducted in a valid manner in accordance with the latest draft of Sequence IIIG procedure and the appropriate amendments through the information letter system. The remarks included in the report describe the anomalies associated with this test.

SUBMITTED BY: *CC*

Testing Laboratory

*Signature Image*

---

Signature

*CC*

Typed Name

*CC*

Title

**SEQUENCE IIIG  
FORM 4  
TEST RESULT SUMMARY**

LAB	CC	OIL CODE	CC
TEST STAND NO.	CCCCC	TEST NO.	CCCCC - CCCC - CCCCC
LABORATORY OIL CODE	CCCCCCCCCCCCCCCCCCCC		
FORMULATION STAND CODE	CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

DATE STARTED	YYYYMMDD	ENGINE NO.	CCCCCCCCCCCCCCCC
TIME STARTED	HH:MM	FUEL BATCH	CCCCCCCCCCCCCCCC
DATE COMPLETED	YYYYMMDD	SAE VISCOSITY	CCCCCCC
TIME COMPLETED	HH:MM	TMC OIL CODE	CCCCCCC
TEST LENGTH	S1234		

Pass/Fail Results						
	Viscosity Increase (%)	Average Cam + Lifter Wear (µm)	Average Weighted Piston Deposits (merits)	Average Piston Skirt Varnish (merits)	Number of Hot-Stuck Rings	Oil Consumption (L) <sup>B</sup>
Original Units	S1234.12	S1234.1	S12.12	S12.12	S12	S12.12
Transformed Results	S12.123456	S1234.1				
Industry Correction Factor	S12.123456	S1.1234	S1.1234	S1.1234		
Corrected Transformed Result	S12.123456	S1234.1				
Severity Adjustment	S12.123456	S1234.1	S1.1234	S1.1234		
Final Transformed Result	S12.123456	S1234.1				
Final Original Unit Result	S1234.1	S1234.1	S12.12	S12.12		

Additional Results			
Oil Consumption Hours, h <sup>B</sup>	S12	Average Oil Ring Plugging, %	S1234
Maximum Cam + Lifter Wear, µm	S12345	Number of Cold-Stuck Rings	S12

Most Recent Stand Reference Oil Test History <sup>C</sup>			
Test Number	CCCCC - CCCC - CCCCC		
Oilcode	CC		
Date Completed	YYYYMMDD	TMC Oil Code	CCCCCC
Final Viscosity Increase, %	S1234.1	Fuel Batch	CCCCCCCCCCCCCCCC
Final Average Piston Skirt Varnish, merits	S12.12		
Final Average Cam + Lifter Wear, µm	S1234.1		
Final Maximum Cam + Lifter Wear, µm	S12345		
Final Average Weighted Piston Deposit, merits	S12.12		

<sup>A</sup> Reference Oil Tests Only

<sup>B</sup> Test Hours at which Oil Consumption was calculated

<sup>C</sup> Non-Reference Oil Tests Only

**SEQUENCE IIIG  
FORM 5  
OPERATIONAL SUMMARY**

LAB	CC	OIL CODE	CC
TEST STAND NO.	CCCCC	TEST NO.	CCCCC - CCCC - CCCCC
LABORATORY OIL CODE	CCCCCCCCCCCCCCCCCCCC		
FORMULATION STAND CODE	CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

	Parameter	Units	QI Threshold	EOT QI	Target	Average	Standard Deviation	Number Of	
								Samples	BQD
Controlled Parameters	Speed	r/min	0.000	S12.123	3600	S12345	S12.123	S12345	S12345
	Load	Nm	0.000	S12.123	250	S12345	S12.123	S12345	S12345
	Oil Filter Block	°C	0.000	S12.123	150.0	S12345	S12.123	S12345	S12345
	Engine Coolant Out	°C	0.000	S12.123	115.0	S123.1	S12.123	S12345	S12345
	Condenser Coolant Out	°C	0.000	S12.123	40.0	S123.1	S12.123	S12345	S12345
	Left Air-to-Fuel Ratio		0.000	S12.123	15.0	S12.1	S12.123	S12345	S12345
	Right Air-to-Fuel Ratio		0.000	S12.123	15.0	S12.1	S12.123	S12345	S12345
	Left Exhaust Back Pressure	kPa	0.000	S12.123	6.0	S1.12	S12.123	S12345	S12345
	Right Exhaust Back Pressure	kPa	0.000	S12.123	6.0	S1.12	S12.123	S12345	S12345
	Intake Air	kPa	0.000	S12.123	0.05	S1.12	S12.123	S12345	S12345
	Engine Coolant Flow	L/min	0.000	S12.123	160.0	S123.1	S12.123	S12345	S12345

	Parameter	Units	Average	Standard Deviation	Number Of	
					Samples	BQD
Non-controlled Parameters	Oil Sump	°C	S123.1	S12.123	S12345	S12345
	Pump Outlet Pressure	kPa	S123.1	S12.123	S12345	S12345
	Gallery Pressure	kPa	S1234	S12.123	S12345	S12345
	Engine Coolant In	°C	S1234	S12.123	S12345	S12345
	Fuel Inlet	°C	S12345	S12.123	S12345	S12345
	Intake Air	°C	S12345	S12.123	S12345	S12345
	Intake Air Dew Point	°C	S123.1	S12.123	S12345	S12345
	Intake Vacuum	kPa	S12345	S12.123	S12345	S12345
	Crankcase	kPa	S1.123	S12.123	S12345	S12345
	Fuel Pressure	kPa	S1234	S12.123	S12345	S12345

OIL CONSUMPTION DATA						
HOURS	Initial Run-in	S12	S12	S12	S12	S12
LEVEL (ml) low	S123	S123	S123	S123	S123	S123

NOx Measurement			
Hours	S12	S12	S12
NOx, ppm	S12345	S12345	S12345

**SEQUENCE IIIG  
FORM 6  
USED OIL ANALYSIS RESULTS**

LAB	CC	OIL CODE	CC
TEST STAND NO.	CCCCC	TEST NO.	CCCCC - CCCC - CCCCC
LABORATORY OIL CODE	CCCCCCCCCCCCCCCCCCCC		
FORMULATION STAND CODE	CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

VISCOSITY INCREASE DATA (cSt AT 40°C)			
HOURS	VISCOSITY <sup>A</sup>	CHANGE	PERCENT
NEW OIL	S1234.12		
INITIAL <sup>B</sup>	S1234.12		
S12	S1234.12	S1234.12	S1234.12
S12	S1234.12	S1234.12	S1234.12
S12	S1234.12	S1234.12	S1234.12
S12	S1234.12	S1234.12	S1234.12
S12	S1234.12	S1234.12	S1234.12
S12	S1234.12	S1234.12	S1234.12
S1234	S1234.12	S1234.12	S1234.12

Results of ICP Analysis of Used Oil			
Hours	Iron	Copper	Lead
Initial	S12345	S12345	S12345
S12	S12345	S12345	S12345
S12	S12345	S12345	S12345
S12	S12345	S12345	S12345
S12	S12345	S12345	S12345
S12	S12345	S12345	S12345
S1234	S12345	S12345	S12345

<sup>A</sup> 8000 cSt is maximum allowable viscosity

<sup>B</sup> At end of leveling run

Cold Crank Simulator Results, D 5293	
Specified Temperature, °C	S12
Cold-Crank Simulator Viscosity at Specified Temperature, cP	S12345
Second Temperature, °C	S12
Cold-Crank Simulator Viscosity at Second Temperature, cP	S12345

Mini-Rotary Viscometer Results, D 4684	
MRV Temperature, °C	S12
MRV Result, cP	S12345
Yield Stress, cP	S123

**SEQUENCE III G  
FORM 7  
VALVE LIFTER AND CAMSHAFT WEAR RESULTS**

LAB	CC	OIL CODE	CC
TEST STAND NO.	CCCCC	TEST NO.	CCCCC - CCCC - CCCCC
LABORATORY OIL CODE	CCCCCCCCCCCCCCCCCCCC		
FORMULATION STAND CODE	CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

NUMBER	CAMSHAFT LOBE, $\mu\text{m}$	VALVE LIFTER, $\mu\text{m}$	CAM & LIFTER WEAR, $\mu\text{m}$
1	S1234	S1234	S1234
2	S1234	S1234	S1234
3	S1234	S1234	S1234
4	S1234	S1234	S1234
5	S1234	S1234	S1234
6	S1234	S1234	S1234
7	S1234	S1234	S1234
8	S1234	S1234	S1234
9	S1234	S1234	S1234
10	S1234	S1234	S1234
11	S1234	S1234	S1234
12	S1234	S1234	S1234
MAXIMUM	S1234	S1234	S12345
MINIMUM	S1234	S1234	S12345
AVERAGE	S1234	S1234	S1234.1

**SEQUENCE IIIG  
FORM 8  
SUMMARY OF OIL RING LAND DEPOSIT RATING**

LAB	CC	OIL CODE	CC
TEST STAND NO.	CCCCC	TEST NO.	CCCCC - CCCC - CCCCC
LABORATORY OIL CODE	CCCCCCCCCCCCCCCCCCCC		
FORMULATION STAND CODE	CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		
RATER	CCC	RATING DATE	YYYYMMDD

PISTON	OIL RING LAND DEPOSIT, MERITS	% CHIPPED
1	<i>S12.12</i>	<i>S1234</i>
2	<i>S12.12</i>	<i>S1234</i>
3	<i>S12.12</i>	<i>S1234</i>
4	<i>S12.12</i>	<i>S1234</i>
5	<i>S12.12</i>	<i>S1234</i>
6	<i>S12.12</i>	<i>S1234</i>
Average	<i>S12.12</i>	<i>S1.12</i>

PISTON	% OIL RING PLUGGING	RING STICKING <sup>A</sup>	
		HOT-STUCK RINGS	COLD-STUCK RINGS
1	<i>S1234</i>	<i>CCC</i>	<i>CCC</i>
2	<i>S1234</i>	<i>CCC</i>	<i>CCC</i>
3	<i>S1234</i>	<i>CCC</i>	<i>CCC</i>
4	<i>S1234</i>	<i>CCC</i>	<i>CCC</i>
5	<i>S1234</i>	<i>CCC</i>	<i>CCC</i>
6	<i>S1234</i>	<i>CCC</i>	<i>CCC</i>
Total		<i>S12</i>	<i>S12</i>
Average	<i>S1234</i>		

<sup>A</sup> Possible values T = top compression ring  
 B = bottom compression ring  
 O = oil ring  
 N = none

**SEQUENCE IIIG  
FORM 9  
SUMMARY OF PISTON DEPOSITS**

LAB	CC	OIL CODE	CC
TEST STAND NO.	CCCCC	TEST NO.	CCCCC - CCCC - CCCCC
LABORATORY OIL CODE	CCCCCCCCCCCCCCCCCCCC		
FORMULATION STAND CODE	CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		
RATER	CCC	RATING DATE	YYYYMMDD

**NOTE: CRC Manual 14 used for ALL Ratings**

NOTE: These are unweighted ratings.

	Grooves, merits			Lands, merits		Undercrown, merits
	1	2	3	2	3	
Piston 1	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>
Piston 2	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>
Piston 3	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>
Piston 4	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>
Piston 5	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>
Piston 6	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>
WF	0.05	0.10	0.20	0.15	0.30	0.10

NOTE: These are unweighted ratings.

	Piston Skirt Varnish, merits		
	Thrust	Anti-Thrust	Average
Piston 1	<i>S12.12</i>	<i>S12.12</i>	<i>S1.12</i>
Piston 2	<i>S12.12</i>	<i>S12.12</i>	<i>S1.12</i>
Piston 3	<i>S12.12</i>	<i>S12.12</i>	<i>S1.12</i>
Piston 4	<i>S12.12</i>	<i>S12.12</i>	<i>S1.12</i>
Piston 5	<i>S12.12</i>	<i>S12.12</i>	<i>S1.12</i>
Piston 6	<i>S12.12</i>	<i>S12.12</i>	<i>S1.12</i>
Average	<i>S12.12</i>	<i>S12.12</i>	<i>S12.12</i>
WF			0.10

PSVAV<sub>x</sub> = (PSVT<sub>x</sub> + PSVA<sub>x</sub>)/2 where x = Number of Piston  
 PSVTAV = average of six Thrust Piston Skirt ratings.  
 PSVAAV = average of six Anti-Thrust Piston Skirt ratings.  
 APV = average of all 12 Piston Skirt ratings.

	Total Weighted Deposits, merits
Piston 1	<i>S12.12</i>
Piston 2	<i>S12.12</i>
Piston 3	<i>S12.12</i>
Piston 4	<i>S12.12</i>
Piston 5	<i>S12.12</i>
Piston 6	<i>S12.12</i>


WPD<sub>x</sub>=(WF\*G1P<sub>x</sub>)+(WF\*G2P<sub>x</sub>)+(WF\*G3P<sub>x</sub>)+(WF\*L2P<sub>x</sub>)+(WF\*ORLD<sub>x</sub>)+(WF\*UCP<sub>x</sub>)+(WF\*PSVAV<sub>x</sub>)  
 where: x=Number of Piston  
 WF=Appropriate Weighting Factor (WF) for part, from table.

Average Weighted Piston Deposits, merits	<i>S12.12</i>	WPD=(WPD1+WPD2+WPD3+WPD4+WPD5+WPD6)/6
--	---------------	---------------------------------------

**SEQUENCE III G  
FORM 10  
BLOWBY VALUES & PLOT**

LAB	CC	OIL CODE	CC
TEST STAND NO.	CCCCC	TEST NO.	CCCCC - CCCC - CCCCC
LABORATORY OIL CODE	CCCCCCCCCCCCCCCCCCCC		
FORMULATION STAND CODE	CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Blowby Plot



Test Hours	S12	S12	S12	S12	S12	S12	S12	S12	S12	S12
Blowby, L/min.	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1
Test Hours	S12	S12	S12	S12	S12	S12	S12	S12	S12	S12
Blowby, L/min.	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1
Test Hours	S12	Average								
Blowby, L/min.	S12.1	S12.1								





**SEQUENCE IIIG  
FORM 12  
HARDWARE INFORMATION**

LAB	CC	OIL CODE	CC
TEST STAND NO.	CCCCC	TEST NO.	CCCCC - CCCC - CCCCC
LABORATORY OIL CODE	CCCCCCCCCCCCCCCCCCCC		
FORMULATION STAND CODE	CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Build Completion Date	YYYYMMDD	Piston Batch (Code)	CCCCC
Block Serial Number	CCCCCC	Piston Size (Grade)	CC
Crankshaft Serial Number	CCCCC	Piston Ring Batch Code	CCCCC
Camshaft Serial Number	CCCCCC	Oil Filter Batch Code	CCCCCC
Cylinder Head Serial Number, Left	CCCCCCCC	Intake Valve Seals Batch Code	CCCCC
Cylinder Head Serial Number, Right	CCCCCCCC	Valve Springs Batch Code	CCCCC
Bearing Kit Serial Number	CCCCCC	Lifter Serial Number	1 CCCCCCCC
Top Ring Gap, mils	S12		2 CCCCCCCC
Bottom Ring Gap, mils	S12		3 CCCCCCCC
			4 CCCCCCCC
			5 CCCCCCCC
			6 CCCCCCCC
			7 CCCCCCCC
			8 CCCCCCCC
			9 CCCCCCCC
			10 CCCCCCCC
			11 CCCCCCCC
			12 CCCCCCCC

