

**Report On**  
**Sequence IIIHB Evaluation**  
 Version

Conducted For

	V = Valid
	I = Invalid
	N = Results cannot be interpreted as representative of oil performance (Non-reference oil) and shall not be used for multiple test acceptance

	NR = Non-reference oil test
	RO = Reference oil test

Test Number					
Test Stand		Stand Test		Lab Test	
Oil Code					
Formulation/Stand					
Alternate Codes					
EOT Date			EOT Time		

<p>In my opinion this test _____ been conducted in a valid manner in accordance with the Test Method, D XXXX, and appropriate amendments. The remarks included in the report describe the anomalies associated with this test.</p>
--

Submitted By:

\_\_\_\_\_

Testing Laboratory

\_\_\_\_\_

Signature

\_\_\_\_\_

Typed Name

\_\_\_\_\_

Title

**Sequence IIIHB**  
**Form 2**  
**Table of Contents**

1.	Title / Validity Declaration Page	Form 1
2.	Table of Contents	Form 2
3.	Summary of Test Method	Form 3
4.	Test Result Summary	Form 4
5.	Operational Summary	Form 5
6.	Oil Consumption Data Plot	Form 6
7.	Used Oil Analysis	Form 7
8.	Blowby Values & Plot	Form 8
9.	Hardware Information	Form 9
10.	Downtime Report Form	Form 10
11.	Test Comments	Form 11
12.	American Chemistry Council Code Of Practice Test Laboratory Conformance Statement	Form 12

**Sequence IIIHB  
Form 3  
Summary of Test Method**

The Sequence IIIHB Test is a fired-engine, dynamometer lubricant test for evaluating automotive engine oils for certain high-temperature performance characteristics. Such oils include both single viscosity grade and multi-viscosity grade oils that are used in spark-ignition, gasoline-fueled engines, as well as diesel engines. The Sequence IIIHB Test utilizes a 2012 Chrysler Penstar 3.6 Liter, water-cooled, 4 cycle, V-6 engine as the test apparatus. The Sequence IIIHB test engine is an overhead valve design (OHV) and uses dual overhead camshafts operating both intake and exhaust valves. The engine uses two intake and two exhaust valve per cylinder. The test engine is overhauled prior to each test, during which critical engine dimensions are measured and rated or measured parts (pistons, rings, etc.) are replaced.

The Sequence IIIHB Test consists 90 hours of engine operation at moderately high speed, load, and temperature conditions. The 90-hour segment is broken down into four 20-hour test segments and one 10-hour segment. Following each 20-hour segment, the 10 hour segment, and the 10-minute operational check, oil samples are drawn from the engine. The ICP analysis of the 20-hour segment samples and 10 hour segment samples are compared to the ICP analysis of the initial sample to determine the phosphorus retention of the test oil.

The Sequence IIIHB Test is operated at the following test states during the 90-hour portion of the test:

Quantity	Set Point
Engine Speed	3900 r/min
Engine Load	250 N·m
Oil Temperature, Block	151° C
Coolant Outlet Temperature	115° C
Fuel Temperature	30° C
Intake Air Temperature	35° C
Intake Air Pressure	0.05 kPa
Intake Air Dew Point	16.1° C
Exhaust Back Pressure	4.5 kPa
Engine Coolant Flow	170 L/min
Coolant Pressure	200 kPa

**Sequence IIIHB**

**Form 4**

**Test Result Summary**

Lab		Oil Code	
Stand		Test No.	
Laboratory Oil Code			
Formulation Stand Code			

Date Started		Engine No.	
Time Started		Fuel Batch	
Date Completed		SAE Viscosity	
Time Completed		Reference Oil <sup>A</sup>	
Test Length			

	<b>Phosphorus Retention %</b>
Original Units	
Transformed Results <sup>B</sup>	
Industry Correction Factor	
Corrected Transformed Result	
Severity Adjustment	
Final Transformed Result	
Final Original Unit Result	

**Additional Results**

Oil Consumption Hours, h <sup>B</sup>		Oil Consumption, L	
---------------------------------------	--	--------------------	--

<sup>A</sup> Reference Oil Tests Only

<sup>B</sup> Test Hours at which Oil Consumption was calculated

**Sequence IIIHB  
Form 5  
Operational Summary**

Lab		Oil Code	
Stand		Test No.	
Laboratory Oil Code			
Formulation Stand Code			

	Quantity	Units	QI Threshold	EOT QI	Target	Average	Standard Deviation	Number of	
								Samples	BQD
<b>Controlled Parameters</b>	Speed	r/min	0.000		3900				
	Load	N·m	0.000		250				
	Oil, Block	°C	0.000		151				
	Coolant Out	°C	0.000		115				
	Coolant System	kPa			200				
	Intake Air	°C	0.000		35				
	Intake Air	kPa	0.000		0.05				
	Dew Point	°C	0.000		16.1				
	EBP Rt.	kPa	0.000		4.5				
	EBP Lt.	kPa	0.000		4.5				
	AFR, Rt.				14.4				
	AFR, Lt.				14.4				
	Fuel @ Rail	°C	0.000		30				
	Fuel @ Rail	kPa			420				
	Coolant Flow	L/min	0.000		170				

	Quantity	Units	Average	Standard Deviation	Number of	
					Samples	BQD
<b>Non-controlled Parameters</b>	Oil Sump	°C				
	Oil Pump	°C				
	Oil Cooler	°C				
	Coolant In	°C				
	Oil Gallery	kPa				
	Oil Pump	kPa				
	Manifold Absolute Pressure	kPaA				
	Right Exhaust Temperature	°C				
	Left Exhaust Temperature	°C				
	Fuel Flow Rate	kg/h				
	Crankcase	kPa				
	Right NOx	mg/kg				
	Left NOx	mg/kg				

**Sequence IIIHB  
Form 6  
Oil Consumption Data Plot**

Lab		Oil Code	
Stand		Test No.	
Laboratory Oil Code			
Formulation Stand Code			

**Oil Consumption Data**

Hours					<b>EOT</b>
Level low (mL)					
Total Oil Consumed (L)					

**Oil Consumption Plot**



## Sequence IIIHB

### Form 7

#### Used Oil Analysis Results

Lab		Oil Code	
Stand		Test No.	
Laboratory Oil Code			
Formulation Stand Code			

Oxidation & Nitration Results						
Parameter	Method	Test Hours				EOT
DIR Oxidation	E168 IIIG Area					
DIR Nitration	E168 IIIG Area					
Total Acid Number						
Parameter	Method					EOT
TAN	D664					
TBN	D4739					
Metals Element Analysis – ICP Method D5185 mg/kg						
Element	New Oil	Initial <sup>A</sup>				EOT
Aluminum (Al)						
Boron (B)						
Calcium (Ca)						
Copper (Cu)						
Iron (Fe)						
Potassium (K)						
Magnesium (Mg)						
Manganese (Mn)						
Molybdenum (Mo)						
Sodium (Na)						
Phosphorus (P)						
Lead (Pb)						
Silicon (Si)						
Tin (Sn)						
Zinc (Zn)						

<sup>A</sup> Initial = At end of leveling run

**Sequence IIIHB  
Form 8  
Blowby Values & Plot**

Lab		Oil Code	
Stand		Test No.	
Laboratory Oil Code			
Formulation Stand Code			

Blowby Plot



Test Hours	Blowby, L/min	Test Hours	Blowby, L/min	Test Hours	Blowby, L/min
				<b>Average</b>	



**Sequence IIIHB  
Form 9  
Hardware Information**

Lab		Oil Code	
Stand		Test No.	
Laboratory Oil Code			
Formulation Stand Code			

<b>Hardware Information</b>	
Engine Build Date	
Block Serial Number	
Ring Batch Code	
Oil Control (OC) Ring Batch Code	
Expander Ring (EXP) Batch Code	
Cylinder Head Serial Number, Left	
Cylinder Head Serial Number, Right	
Lab Block Number	
Piston Batch Code	

<b>Cylinder Bore Measurements</b>								
Cylinder	Transverse				Longitudinal			
	Top	Middle	Bottom	Taper	Top	Middle	Bottom	Taper
2								
4								
6								
1								
3								
5								

<b>Cylinder Bore Measurements</b>					
Cylinder	Rk	Rpk	Rvk	Rz	Mr2
2					
4					
6					
1					
3					
5					





**Sequence IIIHB**  
**Form 12**  
**American Chemistry Council Code of Practice**  
**Test Laboratory Conformance Statement**

Test Laboratory					
Test Sponsor					
Formulation / Stand Code					
Test Number					
Start Date		Start Time		Time Zone	

Declarations

No. 1 All requirements of the ACC Code of Practice for which the test laboratory is responsible were met in the conduct of this test. Yes \_\_\_\_\_ No \_\_\_\_\_\*

No. 2 The laboratory ran this test for the full duration following all procedural requirements; and all operational validity requirements of the latest version of the applicable test procedure (ASTM or other), including all updates issued by the organization responsible for the test, were met. Yes \_\_\_\_\_ No \_\_\_\_\_\*

If the response to this Declaration is “No”, does the test engineer consider the deviations from operational validity requirements that occurred to be beyond the control of the laboratory? Yes \_\_\_\_\_\* No \_\_\_\_\_

No 3. A deviation occurred for one of the test parameters identified by the organization responsible for the test as being a special case. Yes \_\_\_\_\_\* No \_\_\_\_\_ (This currently applies only to specific deviations identified in the ASTM Information Letter System)

	Operational review of this test indicates that the results should be included in the Multiple Test Acceptance Criteria calculations.
	*Operational review of this test indicates that the results should not be included in the Multiple Test Acceptance Criteria calculations.

Note: Supporting comments are required for all responses identified with an asterisk.

Comments

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Date

\_\_\_\_\_  
Typed Name

\_\_\_\_\_  
Title