A5. Report Forms M11 EGR LUBRICANT PERFORMANCE TEST

VERSION 20020301 **METHOD**

CONDUCTED FOR:

		V = VALID; THE REFERENCE OIL/NON-REFERENCE OIL WAS EVALUATED IN ACCORDANCE WITH THE TEST PROCEDURE.							
		I = INVALID; THE REFERENCE OIL/NON-REFERENCE OIL WAS NOT EVALUATED IN ACCORDANCE WITH THE TEST PROCEDURE.							
					RESULTS CANNOT BE PLE TEST ACCEPTANC	Е.			
		NR = Non-Refer	ence Oil Test						
		RO = Reference	Oil Test						
STAND:			ENGINE NO.:		ENGINE RUN NO.:				
END OF	TEST DATE:			END OF TEST TIME:					
OIL COL	DE:								
FORMUI	LATION/STANI	O CODE:	,						
ALTCO	DDE1:		ALTCODE2:		ALTCODE3:				
n my opi	nion this test	ł	been conducted in a va	alid manner in accordanc	e with the Test Procedure				
	ppropriate ameno alies associated v		information letter sys	stem. The remarks include	ded in this report describe				
		SI	JBMITTED BY:						
		50	SDMITTED DT.			Testing Laboratory			
						Signature			
						Typed Name			
						Typed Name			

M11 EGR LUBRICANT PERFORMANCE TEST FORM 2 TABLE OF CONTENTS

1.	Final Report Cover Sheet	Form 1
2.	Table of Contents	Form 2
3.	Summary of Test Method	Form 3
4.	Test Results Summary	Form 4
5.	Operational Summary	Form 5
6.	Crosshead Mass Loss Summary	Form 6
7.	Oil Filter Delta Pressure Plot	Form 7
8.	Sludge Rating Summary	Form 8
9.	Rod Bearing Mass Loss	Form 9
10.	Piston Rating Summary	Form 10
11.	Piston 1 Deposit Rating	Form 11
12.	Piston 2 Deposit Rating	Form 12
13.	Piston 3 Deposit Rating	Form 13
14.	Piston 4 Deposit Rating	Form 14
15.	Piston 5 Deposit Rating	Form 15
16.	Piston 6 Deposit Rating	Form 16
17.	Ring Mass Loss Summary	Form 17
18.	Oil Analysis Summary	Form 18
19.	Test Fuel Analysis	Form 19
20.	Injector Adjusting Screw Mass Loss	Form 20
21.	Unscheduled Downtime & Maintenance Summary	Form 21
22.	Characteristics of the Data Acquisition System	Form 22

M11 EGR LUBRICANT PERFORMANCE TEST FORM 3 SUMMARY OF TEST METHOD

The M11 EGR Lubricant Performance Test is an engine-dynamometer test which evaluates the ability of a lubricant to minimize crosshead wear, filter plugging, sludge build-up, and topring weight loss. This test is a two stage, steady state test (constant speed and load). Stage A is 50 h and is run with retarded fuel injection timing to produce elevated soot levels in the oil. Stage B is 50 h and is run under heavy load conditions to induce wear. The stages are run in sequence (Stage A followed by Stage B) three times for a total test length of 300 h.

The test engine is a Cummins M11 diesel engine with EGR. It is an in-line six cylinder, four stroke, turbocharged engine with electronically controlled fuel injection. A two-h break-in is conducted prior to each test since a new engine build is used for each test.

M11 EGR TEST CONDITIONS

Parameter	Stage A	Stage B
Time, h	50	50
Injection Timing, °BTDC	16 min	32
Speed, r/min	1800	1600
Fuel Flow, kg/h	58.0	64.4
Intake CO ₂ %	0.97 - 1.09	0.78 - 0.85
Inlet Manifold Temp., °C	80	65.5
Coolant Out Temp., °C	65.5	65.5
Fuel In Temp., °C	40	40
Oil Gallery Temp., °C	115	115
Intake Air Temp., °C	Record	Record
Intake Air Pressure, kPa absolute	Record	Record
Intake Manifold Pressure, kPa absolute	300 Minimum	320 Minimum
Exhaust Back Pressure, kPa absolute	107	107
Crankcase Pressure, kPa	Record	Record
Coolant System Pressure, kPa	99 - 107	99 - 107
Power, kW	Record	Record
Torque, Nm	Record	Record
Pre-turbine Exhaust Temp., °C	Record	Record
Tailpipe Exhaust Temp., °C	Record	Record
Oil Sump Temp., °C	Record	Record
Inlet Air Dew Point, °C	Record	Record
Inlet Air Humidity, kg/kg	Record	Record
Oil Gallery Pressure, kPa	Record	Record
Oil Filter Delta P, kPa	Record	Record

M11 EGR LUBRICANT PERFORMANCE TEST Test Results Summary Form 4

Laboratory:	EOT Date:	EOT Date:		EOT Time:			
Stand:	Engine:	Engine: E			Engine Run No.:		
Formulation/Stand Code:							
Oil Code:	Oil Code: Engine Kit S/N:						
DATE TEST STARTED							
START TIME							
TEST LENGTH							
TMC OIL CODE A							
LABORATORY OIL CODE							
SAE VISCOSITY							
TGA SOOT % AT 50 h (2.8 minimum)							
TGA SOOT % AT 250 h (8.0 - 9.5)							
AVERAGE TGA SOOT % 0 - 300 h							
TOTAL OIL CONSUMPTION, kg							
	Adjusted Average Crosshead Mass Loss (mg)	Filter Plugging Delta P (kPa)		rage Sludge Rating (merits)	Avg. Top Ring Weight Loss (mg)		
Original Result							
Transformed Result B							
Correction Factor B							
Corrected Transformed Result B							
Severity Adjustment B							
Final Transformed Result B							
Final Result							
	LAST STAND REFE	ERENCE RESULTS					
TEST NUMBER: -	-						
OILCODE							
TEST LENGTH							
TMC OIL CODE							
EOT DATE							
EOT TIME							
STAND CALIBRATION EXPIRATION D	OATE						
TGA SOOT % AT 50 h (2.8 minimum)							
TGA SOOT % AT 250 h (8.5 - 9.5)							
AVERAGE TGA SOOT % 0 - 300 h							
TOTAL OIL CONSUMPTION, kg							
	Adjusted Average Crosshead Mass Loss (mg)	Filter Plugging Delta P (kPa)	Ave	erage Sludge Rating (merits)	Avg. Top Ring Weight Loss (mg)		
Original Result							
Transformed Result B							
Correction Factor B							
Corrected Transformed Result B							
Final Transformed Result B							
Einal Dagult					<u> </u>		

A Reference Tests Only
B Filter Plugging Delta P Value in Transformed Units

M11 EGR LUBRICANT PERFORMANCE TEST FORM 5 **OPERATIONAL SUMMARY**

Laboratory	EOT Date	EOT Time	
Test Number Stand:	Engine:	Engine Run No.:	
Formulation/Stand Code:	·		
Oil Code:			

Parameter	Units	QI Threshold	EOT _A	Ta	rget	1	Average	Samples B	\mathbf{BQD}^{C}	Over/Under Range ^D
Speed Fuel Flow Coolant Out	r/min	0.000		1800	1600					
Fuel Flow	kg/h	0.000		58.0	64.4					
Coolant Out	°C	0.000		65	5.5					
Fuel In	°C	0.000		4	-0					
Oil Gallery	°C	0.000		1	15					
Intake Manifold	°C	0.000		80.0	65.5					
Exhaust	kPa	0.000		1	07					
Parameter	Units	Typical	Values E			Average				
Torque	N-m	TBD	TBD							
Power	kW	TBD	TBD							
Intake CO ₂	%	0.97 - 1.09	0.78 - 0.85							
Blowby	L/min	TH	BD							
Coolant In	°C	TI	BD .							
Intake Air	°C	TI	BD							
Pre-Turbine (F)	°C	TI	BD .							
Pre-Turbine (R)	°C	TI	BD .							
Tailpipe	°C	TI	BD .							
Fuel	kPa	TI	BD .							
Oil Gallery	kPa	TI	3D							
Coolant	kPa	99 -	107							
Intake Manifold	kPa	TI	BD .							
Crankcase	kPa	TI	3D							
Intake Air	kPa	TI	3D							

A QI values above the threshold are acceptable by the M11 Surveillance Panel. QI values below the threshold may not be considered acceptable based on an engineering review. See the comments section of this report.

B Total number of data points taken

C Number of Bad Quality Data points not used in the calculation of the statistical measures D Number of points clipped by over/under range limits E Typical values determined from reference oil test database

M11 EGR LUBRICANT PERFORMANCE TEST FORM 6 CROSSHEAD MASS LOSS SUMMARY

Laboratory	EOT Date	EOT Time	
	Test Number		
STAND:	ENGINE:	ENGINE RUN NO.:	
FORMULATION/STAND CODE:			
OIL CODE:			

LOCATION	SERIAL NO.	PRETEST MASS (g)	EOT MASS (g)	MASS LOSS (mg)
1E				
1I				
2I				
2E				
3E				
3I				
4I				
4E				
5E				
5I				
6I				
6E				

INTAKE EVITATIOT CHIMMADV	INT	AKE	EXHAUST		
INTAKE/EXHAUST SUMMARY	As Measured	Outlier Screened	As Measured	Outlier Screened	
Average Crosshead Mass Loss (mg)					
Minimum Crosshead Mass Loss (mg)					
Maximum Crosshead Mass Loss (mg)					
Standard Deviation (mg)					
Outlier Crossheads Locations					

A Location Designation. Example: 3E

Overall Summary	As Measured	Outlier Screened	Adjusted to X.X% Soot
Average Crosshead Mass Loss (mg)			
Minimum Crosshead Mass Loss (mg)			
Maximum Crosshead Mass Loss (mg)			
Standard Deviation (mg)			

M11 EGR LUBRICANT PERFORMANCE TEST FORM 7 OIL FILTER DELTA PRESSURE PLOT

Laboratory	EOT Date	EOT Time
	Test Number	
STAND:	ENGINE:	ENGINE RUN NO.:
FORMULATION/STAND CODE:		
OIL CODE:		

OIL FILTER DELTA PRESSURE vs TEST HOURS OIL FILTER DELTA P (kPa)

TEST HOURS

M11 EGR LUBRICANT PERFORMANCE TEST FORM 8 SLUDGE RATING SUMMARY

Laboratory:	EOT Date:	EOT Time:		
TEST NUMBER				
STAND:	ENGINE:	ENGINE RUN NO.:		
FORMULATION/STAND CODE:				
OIL CODE:				

SLUDGE RATING SUMMARY

Sludge Depth	Valve Cover % of Area	Valve Cover Volume Factor	Oil Pan % of Area	Oil Pan Volume Factor			
1/4A							
1/2A							
3/4A							
A							
AB							
В							
BC							
С							
D							
Е							
F							
G							
Н							
I							
J							
	Total Volume Factor:		Total Volume Factor:				
	MERIT RATING:		MERIT RATING:				
		Average Sludge Rating:					

M11 EGR LUBRICANT PERFORMANCE TEST FORM 9 ROD BEARING MASS LOSS

Laboratory	EOT Date	EOT Time							
Test Number									
STAND:	ENGINE:	ENGINE RUN NO.:							
FORMULATION/STAND CODE:									
OIL CODE:									

CYLINDER NUMBER	BEARING LOCATION	PRE-TEST MASS (g)	POST-TEST MASS (g)	MASS LOSS (mg)
1	UPPER			
1	LOWER			
	UPPER			
2	LOWER			
3	UPPER			
3	LOWER			
4	UPPER			
4	LOWER			
-	UPPER			
5	LOWER			
	UPPER			
6	LOWER			

	BEARING MASS LOSS
AVERAGE (mg)	
MINIMUM (mg)	
MAXIMUM (mg)	
STANDARD DEVIATION (mg)	

M11 EGR LUBRICANT PERFORMANCE TEST FORM 10 PISTON RATING SUMMARY

Laboratory	EOT Date	EOT Time							
TEST NUMBER									
STAND:	ENGINE:	ENGINE RUN NO.:							
FORMULATION/STAND CODE:									
OILCODE:									

UNWEIGHTED DEMERITS										
PISTON	Lands					Grooves		Under	Oil Cooling	Total
NUMBER	1	2	3	4	1	2	3	Crown	Gallery	Demerits
1										
2										
3										
4										
5										
6										
Average Demerits										
Average Total Unweighted Demerits										

DADAMETED	PISTON NUMBER										
PARAMETER	1	2	3	4	5	6	AVERAGE				
TGC											
TLC											

M11 EGR LUBRICANT PERFORMANCE TEST FORM 11 PISTON 1 DEPOSIT RATINGS

Laboratory	EOT Date	EOT Time						
TEST NUMBER								
STAND:	ENGINE:	ENGINE RUN NO.:						
FORMULATION/STAND CODE:								
OILCODE:								

NC A, %			D. 2 DEM.	N() 1				GROOVES LANDS				OIL COOLING UND					
A , %	DEM.	A, %	DEM.	1		NO	0. 2	DEP FACTOR	NO. 3		NO. 3		NO. 4		GALL	ERY (2)	CROV	WN (1)
				A, %	DEM.	A, %	DEM.	TACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.
								7.5										
								4.5										
								1.5										
								UNWEIGI	HTED I	DEP.		T.L. CA	RBON	Ī	T.L.	FLAKED	CARB	ON %
									1.5	1.5	4.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5

M11 EGR LUBRICANT PERFORMANCE TEST FORM 12 PISTON 2 DEPOSIT RATINGS

Laboratory	EOT Date	EOT Time							
TEST NUMBER									
STAND:	ENGINE:	ENGINE RUN NO.:							
FORMULATION/STAND CODE:									
OILCODE:									

		GRO	OVES			LA	NDS		DEP	GRO	OVES		LA	NDS			OOLING		IDER
DEP.	NO	. 1	NO	. 2	NO	. 1	NO	. 2	FACTOR	NO	. 3	NO. 3		3 NO. 4		GALLERY (2)		CROW	N (1)
FACTOR	A, %	DEM.	PACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM						
CARBON																			
HC-1.0																			
MC-0.5																			
LC25																			
TOTAL																			
VARNISH																			
8 - 9																			
7 - 7.9									7.5										
6 - 6.9																			
5 - 5.9																			
4 - 4.9									4.5										
3 - 3.9																			
2 - 2.9																			
1 - 1.9									1.5										
>0 - 0.9																			
TOTAL																			
Rating																			
TGC %									UNWEIG	ם תידים) FD		T.L. CARBON			T.L. FLAKED CARBON %			
100 %									OINWEIG.	T CTTT	JUF.		т.ш.	CANDUL	N	1.11.	T. TIMIVE	D CAK	DOM &

M11 EGR LUBRICANT PERFORMANCE TEST FORM 13 PISTON 3 DEPOSIT RATINGS

Laboratory	EOT Date	EOT Time						
STAND:	ENGINE:	ENGINE RUN NO.:						
FORMULATION/STAND CODE:								
OILCODE:								

		GROC	OVES			LAN	NDS		DED	GRO	OVES		LAN	NDS		OIL CO	OOLING	UNI	DER
DEP.	NC) . 1	NC	0. 2	NC) . 1	NC). 2	DEP FACTOR	NC) . 3	NC) . 3	NC). 4	GALL	ERY (2)	CROV	VN (1)
FACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	TACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.
CARBON																			
HC-1.0																			
MC-0.5																			
LC25																			
TOTAL																			
VARNISH																			
8 - 9																			
7 - 7.9									7.5										
6 - 6.9																			
5 - 5.9																			
4 - 4.9									4.5										
3 - 3.9																			
2 - 2.9																			
1 - 1.9									1.5										
>0 - 0.9																			
TOTAL																			
Rating																			
TGC %									UNWEIG	UTED F	DED		T.L. CA	DRON		тіч	FLAKED	CADD	ON 06
100 70									UNWEIG	пты	LI.		1.L. CF	MDON		1.1.1	LAKED	CARD	O1 V 70

M11 EGR LUBRICANT PERFORMANCE TEST FORM 14 PISTON 4 DEPOSIT RATINGS

Laboratory	EOT Date	EOT Time
	TEST NUMBER	
STAND:	ENGINE:	ENGINE RUN NO.:
FORMULATION/STAND CODE:		
OILCODE:		

		GRO	OVES			LAN	NDS		DED	GRO	OVES		LAN	NDS		OIL CO	OOLING	UN	DER
DEP.	NC) . 1	NC	0. 2	NC) . 1	NO	0. 2	DEP FACTOR	NC) . 3	NC) . 3	NC). 4	GALL	ERY (2)	CROV	WN (1)
FACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	TACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.
CARBON																			
HC-1.0																			
MC-0.5																			
LC25																			
TOTAL																			
VARNISH																			
8 - 9																			
7 - 7.9									7.5										
6 - 6.9																			
5 - 5.9																			
4 - 4.9									4.5										
3 - 3.9																			
2 - 2.9																			
1 - 1.9									1.5										
>0 - 0.9																			
TOTAL																			
Rating																			
TGC %									UNWEIG	HTED I	DEP.		T.L. CA	ARBON		T.L. I	FLAKED	CARB	ON %_

M11 EGR LUBRICANT PERFORMANCE TEST FORM 15 PISTON 5 DEPOSIT RATINGS

Laboratory	EOT Date	EOT Time
	TEST NUMBER	
STAND:	ENGINE:	ENGINE RUN NO.:
FORMULATION/STAND CODE:		
OILCODE:		

		GRO	OVES			LAN	NDS		DED	GRO	OVES		LAN	NDS		OIL CO	OOLING	UN	DER
DEP.	NC) . 1	NC	0. 2	NC) . 1	NO	0. 2	DEP FACTOR	NC) . 3	NC) . 3	NC). 4	GALL	ERY (2)	CROV	WN (1)
FACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	TACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.
CARBON																			
HC-1.0																			
MC-0.5																			
LC25																			
TOTAL																			
VARNISH																			
8 - 9																			
7 - 7.9									7.5										
6 - 6.9																			
5 - 5.9																			
4 - 4.9									4.5										
3 - 3.9																			
2 - 2.9																			
1 - 1.9									1.5										
>0 - 0.9																			
TOTAL																			
Rating																			
TGC %									UNWEIG	HTED I	DEP.		T.L. CA	RBON		T.L. I	FLAKED	CARB	ON %

M11 EGR LUBRICANT PERFORMANCE TEST FORM 16 PISTON 6 DEPOSIT RATINGS

Laboratory	EOT Date	EOT Time
	TEST NUMBER	
STAND:	ENGINE:	ENGINE RUN NO.:
FORMULATION/STAND CODE:		
OILCODE:		

		GROO	OVES			LAN	NDS		DED	GRO	OVES		GRO	OVES		OIL CO	OOLING	UN	DER
DEP.	NC) . 1	NC	0. 2	NC) . 1	NO	0. 2	DEP FACTOR	NC) . 3	NC	0. 3	NC). 4	GALL	ERY (2)	CROV	WN (1)
FACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	TACTOR	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.	A, %	DEM.
CARBON																			
HC-1.0																			
MC-0.5																			
LC25																			
TOTAL																			
VARNISH																			
8 - 9																			
7 - 7.9									7.5										
6 - 6.9																			
5 - 5.9																			
4 - 4.9									4.5										
3 - 3.9																			
2 - 2.9																			
1 - 1.9									1.5										
>0 - 0.9																			
TOTAL																			
Rating																			
TGC %									UNWEIG	 HTED [DEP.		T.L. CA	ARBON		T.L. I	FLAKED	CARB	ON %

M11 EGR LUBRICANT PERFORMANCE TEST FORM 17 RING MASS LOSS SUMMARY

Laboratory	EOT Date	EOT Time
	TEST NUMBER	
STAND:	ENGINE:	ENGINE RUN NO.:
FORMULATION/STAND CODE:		
OILCODE:		

		TOP RING			SECOND RING			OIL RING	
	MASS	S (g)	MASS LOSS	MASS	S (g)	MASS LOSS	MASS	S (g)	MASS LOSS
CYLINDER	PRETEST	EOT	(mg)	PRETEST	ЕОТ	(mg)	PRETEST	EOT	(mg)
1									
2									
3									
4									
5									
6									
AVERAGE M	IASS LOSS (mg))							
STD. DEV. M	(ASS LOSS (mg))							
MAXIMUM I	MASS LOSS (mg	g)							
MINIMUM N	AASS LOSS (mg	g)							

M11 EGR LUBRICANT PERFORMANCE TEST FORM 18 OIL ANALYSIS SUMMARY

Laboratory:	EOT Date:	EOT Time:
	TEST NUMBER	
STAND:	ENGINE:	ENGINE RUN NO.:
FORMULATION/STAND CODE:		
OIL CODE:		

Test Hours	VISCOSITY @ 100°C, cSt	TGA % SOOT	TBN D4739	TAN D664	COPPER (ppm)	IRON (ppm)	LEAD (ppm)	ALUMINUM (ppm)	CHROMIUM (ppm)
NEW									

M11 EGR LUBRICANT PERFORMANCE TEST FORM 19 TEST FUEL ANALYSIS (LAST BATCH)

Laboratory	EOT Date	EOT Time
	TEST NUMBER	
STAND:	ENGINE:	ENGINE RUN NO.:
FORMULATION/STAND CODE:		
OILCODE:		

FUEL SUPPLIER	FUEL BATCH IDENTIFIER

Measurement	Specifications	Ana	lysis	Test Method	
		NEW	ЕОТ		
Total Sulfur, % Weight	0.04 - 0.05			D 2662	
Gravity, °API	34.5 - 36.5			D 1298	
Hydrocarbon Composition					
Aromatics % Volume	28 - 33			D 1319	
Olefin	Report			D 1319	
Cetane Index	Report			D 4737	
Cetane Number	42 - 48			D 613	
Copper Strip Corrosion	1 Maximum			D 130	
Flash Point, °C	54 Maximum			D 93	
Pour Point, °C	-18 Maximum			D 97	
Carbon Residue on 10% Residuum, %	0.35 Maximum			D 524 (10% Bottoms)	
Water & Sediment, % Volume	0.05 Maximum			D 2709	
Viscosity, cSt @ 40 °C	2.4 - 3.0			D 445	
Total Acid Number	0.05 Maximum			D 664	
Strong Acid Number	0.00 Maximum			D 664	
Accelerated Stability	tbd			D 2274	
Saturates, %	Report			D 1319	
Cloud Point, °C	Report			D 2500	
Distillation, *C					
IBP	Report			D 86	
10%	Report			D 86	
50%	Report			D 86	
90%	282 - 338			D 86	
EP	Report			D 86	

M11 EGR LUBRICANT PERFORMANCE TEST FORM 20 INJECTOR ADJUSTING SCREW MASS LOSS

Laboratory	EOT Date	EOT Time				
TEST NUMBER						
STAND:	ENGINE:	ENGINE RUN NO.:				
FORMULATION/STAND CODE:						
OILCODE:						

SCREW#	PRE-TEST MASS, g	POST-TEST MASS, g	MASS LOSS, mg
1			
2			
3			
4			
5			
6			
		TOTAL	
		AVERAGE	

M11 EGR LUBRICANT PERFORMANCE TEST FORM 21 UNSCHEDULED DOWNTIME & MAINTENANCE SUMMARY

Laboratory		EOT Date	EOT Time			
TEST NUMBER						
STAND:			ENGINE:	ENGINE RUN NO.:		
FORMULA	TION/STAN	D CODE:	•			
OILCODE:						
Number of l	Downtime Oc	currences				
Test Hours	Date	Downtime	Reasons			
				Total Downtime (hours)		
	Other Comme					
Numb	er of Comme	ent Lines				

M11 EGR LUBRICANT PERFORMANCE TEST FORM 22 CHARACTERISTICS OF THE DATA ACQUISITION SYSTEM

Laboratory		EOT Date		EOT Time	
		TEST NUMBER			
STAND: ENC		ENGINE: ENG		NGINE RUN NO.:	
FORMULATION/STAND CODE:					
OIL CODE:					

PARAMETER	SENSING DEVICE	CALIBRATION FREQUENCY	RECORD DEVICE	OBSERVATION FREQUENCY	RECORD FREQUENCY	LOG FREQUENCY	SYSTEM RESPONSE
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
Temperature							
Oil Gallery							
Fuel In							
Intake Air							
Intake Man.							
Pre-Turb.							
Cool. Out							
Pressure							
Inlet Air							
Exhaust							
Oil Gallery							
Other							
Fuel Flow							
Speed							
Load							

LEGEND:

- (1) OPERATING PARAMETER
- (2) THE TYPE OF DEVICE USED TO MEASURE TEMPERATURE, PRESSURE OR FLOW
- (3) FREQUENCY AT WHICH THE MEASUREMENT SYSTEM IS CALIBRATED
- (4) THE TYPE OF DEVICE

DL - AUTOMATIC DATA LOGGER

C/D - COMPUTER, USING DIRECT I/O ENTRY

- (5) DATA ARE OBSERVED BUT ONLY IF RECORDED OFF SPEC.
- (6) DATA ARE RECORDED BUT ARE NOT RETAINED AT EOT
- (7) DATA ARE LOGGED AS PERMANENT RECORD, NOTE SPECIFY IF: SS SNAPSHOT TAKEN AT SPECIFIED FREQUENCY AG/X AVERAGE OF X DATA POINTS AT SPECIFIED FREQUENCY
- (8) TIME IN SECONDS FOR THE OUTPUT TO REACH 63.2% OF FINAL VALUE FOR STEP CHANGE AT INPUT