

D 6987
Mack T-10 EGR Engine Oil Test

Report Packet Version No.
 T10 VERSION 20040505 BETA
Conducted For

CC
 CCC

T-10: C	V = Valid; The Reference Oil/Non-Reference Oil was evaluated in accordance with the test procedure.
	I = Invalid; The Reference Oil/Non-Reference Oil was not evaluated in accordance with the test procedure.
T-10A: C	N = Results cannot be interpreted as representative of oil performance (Non-Reference Oil) and shall not be used in determining an average test result using multiple test criteria.

CC	NR = Non-Reference Oil Test
	RO = Reference Oil Test

Test Number			
Stand: CCCCC	Stand Run: CCCC	Engine: CCCCC	Engine Hours: CCCCC
End Of Test Date: YYYYMMDD		End Of Test Time: HH:MM	
Oil Code: CCC			
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC			
Alternate Codes	CCCCCCCCCCCCCCCC	CCCCCCCCCCCCCCCC	CCCCCCCCCCCCCCCC

In my opinion this test CCCCCC been conducted in a valid manner in accordance with the Test Method D 6987 and the appropriate amendments through the information letter system. The remarks included in this report describe the anomalies associated with this test.

Submitted By: CCC

Testing Laboratory

Signature Image

Signature

CC

Typed Name

CC

Title

D 6987
Mack T-10 EGR Engine Oil Test
Form 2

Table of Contents

1.	Final Report Cover Sheet	Form 1
2.	Table of Contents	Form 2
3.	Summary of Test Method	Form 3
4.	Test Results Summary	Form 4
5.	Operational Summary	Form 5
6.	Rod Bearing Weight Loss	Form 6
7.	Ring Weight Loss	Form 7
8.	Oil Analysis Summary	Form 8
9.	Liner Surface Roughness & Bore Diameter	Form 9
10.	Liner Wear Summary	Form 10
11.	Unscheduled Downtime & Maintenance Summary	Form 11
12.	Test Fuel Analysis (Last Batch)	Form 12
13.	Characteristics of the Data Acquisition System	Form 13
14.	Build-up and Hardware Information	Form 14
15.	Rating Summary: Piston 1	Form 15
16.	Rating Summary: Piston 2	Form 16
17.	Rating Summary: Piston 3	Form 17
18.	Rating Summary: Piston 4	Form 18
19.	Rating Summary: Piston 5	Form 19
20.	Rating Summary: Piston 6	Form 20
21.	Main Bearing Weight Loss	Form 21
22.	ACC Conformance Statement	Form 22

D 6987
Mack T-10 EGR Engine Oil Test
Form 3

The Mack T-10 EGR Engine Oil Test is a fuel engine-dynamometer test which evaluates the ability of a lubricant to minimize piston ring wear, cylinder liner wear, lead corrosion, oil consumption, and oxidation. This test is a two-phase, steady state test (constant speed and load). The first phase is 75 h and is run with retarded fuel injection timing to produce elevated soot levels in the oil. The second phase is 225 h and is run under heavy load conditions to induce piston ring and cylinder liner wear.

The test engine is a Mack E-TECH V-MAC III diesel engine with EGR. It is an in-line six-cylinder, four stroke, turbocharged engine. It has electronically controlled fuel injection with six individual electronic pumps. A one h break-in is conducted prior to each test since a new engine build is used for each test.

Mack T-10 Test Conditions

Parameter	Phase I	Phase II
Time, h	75	225
Injection Timing, °BTDC	Variable	18
Speed, r/min	1800	1200
Fuel Flow, kg/h	59.2	63.5
Exhaust O₂ Level, %	Record	Record
Intake CO₂, %	1.5	0.2
Exhaust CO₂, %	Record	Record
Inlet Manifold Temp., °C	70	66
Coolant Out Temp., °C	66	85
Fuel In Temp., °C	40	40
Oil Gallery Temp., °C	88	113
Intake Air Temp., °C	25	25
Intake Air Restriction, kPa	3.5 – 4.0	3.5 – 4.0
Inlet Manifold Pressure, kPa	160 minimum	210 minimum
Exhaust Back Pressure, kPa	2.7 – 3.5	2.7 – 3.5
Crankcase Pressure, kPa	0.25 – 0.75	0.25 – 0.75
Power, kW	~257	~324
Torque, Nm	Record	Record
Pre-Turbine Exhaust Temp., °C	Record	Record
Tailpipe Exhaust Temp., °C	Record	Record
Oil Sump Temp., °C	Record	Record
EGR Pre-Venturi Temp., °C	Record	Record
Inlet Air Dew Point, °C	Record	Record
Inlet Air Humidity, kg/kg	Record	Record
Main Gallery Oil Pressure, kPa	Record	Record
Oil Filter Delta P, kPa	Not to exceed 138	Not to exceed 138

D 6987
Mack T-10 EGR Engine Oil Test
Form 4
Test Results Summary

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM
Test Number CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Test Results						
Date Test Started: YYYYMMDD	Start Time: HH:MM	Test Length: S1234				
TMC Oil Code: ^A CCCCCC	Laboratory Oil Code: CCCCCCCCCCCCCCCCCC				SAE Viscosity: CCCCCC	
Average TGA Soot % at 75 h				S123.1		
Centrifugal Oil Filter Mass Gain, g				S123.1		
Oil Filter Delta P, kPa (138 maximum)				S123		
EOT TBN				S123.1		
MRV Yield Stress (Pa) ^C				S12345		
	Delta Pb@ EOT (ppm)	Avg Liner Wear (µm)	Avg Top Ring Weight Loss (mg)	Oil Consumption (g/h)	Delta Pb 250-300h (ppm)	MRV^C Viscosity @75h (cP)
Original Result	S123	S12.1	S123	S123.1	S1234	S123456
Transformed Result ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Correction Factor ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Corrected Transformed Result ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Severity Adjustment ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Final Transformed Result ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Final Original Unit Result ^B	S123	S12.1	S123	S123.1	S1234	S123456
Mack Merits ^D	S1234.1	S1234.1	S1234.1	S1234.1	S1234.1	
Total Mack Merits ^D	S1234.1					

Last Stand Reference Results						
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC						
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC						
Test Length: S1234			TMC Oil Code: CCCCCC			
EOT Date: YYYYMMDD			EOT Time: HH:MM			
Stand Calibration Expiration Date: YYYYMMDD						
Average TGA Soot % at 75 h			S123.1			
	Delta Pb@ EOT (ppm)	Avg Liner Wear (µm)	Avg Top Ring Weight Loss (mg)	Oil Consumption (g/h)	Delta Pb 250-300h (ppm)	MRV^C Viscosity @75h (cP)
Original Result	S123	S12.1	S123	S123.1	S1234	S123456
Transformed Result ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Correction Factor ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Corrected Transformed Result ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Final Transformed Result ^B	S1.1234	S1.1234	S12.1234	S12.1234	S1234	S123456
Final Original Unit Result ^B	S123	S12.1	S123	S123.1	S1234	S123456

^A Reference Tests only.
^B Transformed Units for Delta Pb only.
^C For T-10A use only.
^D Non-reference Tests only.

D 6987
Mack T-10 EGR Engine Oil Test
Form 6
Rod Bearing Weight Loss

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Cylinder #	Location	SOT Weight, g	EOT Weight, g	Weight Change, mg
1	Upper	S12.1234	S12.1234	S123.1
2	Upper	S12.1234	S12.1234	S123.1
3	Upper	S12.1234	S12.1234	S123.1
4	Upper	S12.1234	S12.1234	S123.1
5	Upper	S12.1234	S12.1234	S123.1
6	Upper	S12.1234	S12.1234	S123.1

Summary	As Measured	Outlier Screened
Upper Bearing Average Weight Loss, mg	S123.1	S123.1
Upper Bearing Weight Loss Std. Dev., mg	S123.1	S123.1
Upper Bearing Minimum Weight Loss, mg	S123.1	S123.1
Upper Bearing Maximum Weight Loss, mg	S123.1	S123.1
Outlier Upper Rod Bearing ^A	CCCCC	

^A Cylinder number

Cylinder #	Location	SOT Weight, g	EOT Weight, g	Weight Change, mg
1	Lower	S12.1234	S12.1234	S123.1
2	Lower	S12.1234	S12.1234	S123.1
3	Lower	S12.1234	S12.1234	S123.1
4	Lower	S12.1234	S12.1234	S123.1
5	Lower	S12.1234	S12.1234	S123.1
6	Lower	S12.1234	S12.1234	S123.1
Lower Bearing Average Weight Loss, mg				S123.1
Lower Bearing Weight Loss Std. Dev., mg				S123.1
Lower Bearing Minimum Weight Loss, mg				S123.1
Lower Bearing Maximum Weight Loss, mg				S123.1

Conrod Bearing Batch ID	CCCCCCCCCCCC
--------------------------------	--------------

D 6987
Mack T-10 EGR Engine Oil Test
Form 7
Ring Weight Loss

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Cylinder #	Top Ring SOT Weight, g	Top Ring EOT Weight, g	Weight Loss, mg
1	S12.1234	S12.1234	S123.1
2	S12.1234	S12.1234	S123.1
3	S12.1234	S12.1234	S123.1
4	S12.1234	S12.1234	S123.1
5	S12.1234	S12.1234	S123.1
6	S12.1234	S12.1234	S123.1

Summary	As Measured	Outlier Screened
Top Ring Average Weight Loss, mg	S123	S123
Top Ring Weight Loss Std. Dev., mg	S123.1	S123.1
Top Ring Minimum Weight Loss, mg	S123.1	S123.1
Top Ring Maximum Weight Loss, mg	S123.1	S123.1
Outlier Ring^B	CCCCC	

^A Results calculated without rings with plasma flanking.

^B Ring number wear results are not currently outlier screened.

Cylinder #	2nd Ring SOT Weight, g	2 nd Ring EOT Weight, g	Weight Loss, mg
1	S12.1234	S12.1234	S123.1
2	S12.1234	S12.1234	S123.1
3	S12.1234	S12.1234	S123.1
4	S12.1234	S12.1234	S123.1
5	S12.1234	S12.1234	S123.1
6	S12.1234	S12.1234	S123.1
2nd Ring Average Weight Loss, mg			S123.1
2nd Ring Weight Loss Std. Dev., mg			S123.1
2nd Ring Min. Weight Loss, mg			S123.1
2nd Ring Max. Weight Loss, mg			S123.1

Cylinder #	Oil Ring SOT Weight, g	Oil Ring EOT Weight, g	Weight Loss, mg
1	S12.1234	S12.1234	S123.1
2	S12.1234	S12.1234	S123.1
3	S12.1234	S12.1234	S123.1
4	S12.1234	S12.1234	S123.1
5	S12.1234	S12.1234	S123.1
6	S12.1234	S12.1234	S123.1
Oil Ring Average Weight Loss, mg			S123.1
Oil Ring Weight Loss Std. Dev., mg			S123.1
Oil Ring Minimum Weight Loss, mg			S123.1
Oil Ring Maximum Weight Loss, mg			S123.1

D 6987
MACK T-10 EGR Engine Oil Test
Form 8
Oil Analysis Summary

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM
Test Number: CCC		
Formulation/Stand Code: CC-C-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Hours	Soot Wt.% TGA	Viscosity At 100°C cSt	Viscosity Increase cSt	TBN	TAN	Integrated IR Oxidation	Metal Elements (ppm)										
							Fe	Pb	Cu	Cr	Al	Si	Sn	Na			
CCCCC	S123.1	S123.12		S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
75 (2nd)	S123.1																
75 AVG.	S123.1																
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA
CCCCC	S123.1	S123.12	S12.12	S123.1	S123.1	S1234.1	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA	AAAAAA

Summary	As Measured	Outlier Bearing Adjusted
Delta Pb @ EOT, ppm	S123	S123
Delta Pb @ 250-300h, ppm	S1234	
75-h MRV	S123456	

D 6987
Mack T-10 EGR Engine Oil Test
Form 9
Liner Surface Roughness & Bore Diameter

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Liner No.	Location	Ra (µm)	Bore Diameter (mm)		Ra (µm)	Dia. (mm)
1	Top Ring Travel @ 0°C	S1.12	S123.123	Avg.	S1.12	S123.123
	Top Ring Travel @ 90°C	S1.12	S123.123	Std. Dev.	S1.12	
	Top Ring Travel @ 180°C	S1.12		Min.	S1.12	
	Top Ring Travel @ 270°C	S1.12		Max.	S1.12	
2	Top Ring Travel @ 0°C	S1.12	S123.123	Avg.	S1.12	S123.123
	Top Ring Travel @ 90°C	S1.12	S123.123	Std.Dev.	S1.12	
	Top Ring Travel @ 180°C	S1.12		Min.	S1.12	
	Top Ring Travel @ 270°C	S1.12		Max.	S1.12	
3	Top Ring Travel @ 0°C	S1.12	S123.123	Avg.	S1.12	S123.123
	Top Ring Travel @ 90°C	S1.12	S123.123	Std. Dev.	S1.12	
	Top Ring Travel @ 180°C	S1.12		Min.	S1.12	
	Top Ring Travel @ 270°C	S1.12		Max.	S1.12	
4	Top Ring Travel @ 0°C	S1.12	S123.123	Avg.	S1.12	S123.123
	Top Ring Travel @ 90°C	S1.12	S123.123	Std.Dev.	S1.12	
	Top Ring Travel @ 180°C	S1.12		Min.	S1.12	
	Top Ring Travel @ 270°C	S1.12		Max.	S1.12	
5	Top Ring Travel @ 0°C	S1.12	S123.123	Avg.	S1.12	S123.123
	Top Ring Travel @ 90°C	S1.12	S123.123	Std. Dev.	S1.12	
	Top Ring Travel @ 180°C	S1.12		Min.	S1.12	
	Top Ring Travel @ 270°C	S1.12		Max.	S1.12	
6	Top Ring Travel @ 0°C	S1.12	S123.123	Avg.	S1.12	S123.123
	Top Ring Travel @ 90°C	S1.12	S123.123	Std. Dev.	S1.12	
	Top Ring Travel @ 180°C	S1.12		Min.	S1.12	
	Top Ring Travel @ 270°C	S1.12		Max.	S1.12	

	Ra (µm)	Bore Diameter (mm)
Average Surface Roughness & Bore Diameter	S1.12	S123.123
Standard Deviation Surface Roughness & Bore Diameter	S1.12	S123.123
Minimum Surface Roughness & Bore Diameter	S1.12	S123.123
Maximum Surface Roughness & Bore Diameter	S1.12	S123.123

D 6987
Mack T-10 EGR Engine Oil Test
Form 10
Liner Wear Summary

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Position	Wear Step (µm)					
	Cylinder Number					
	1	2	3	4	5	6
1:00	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
2:00	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
3:00 (Thrust)	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
4:00	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
5:00	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
6:00 (Rear)	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
7:00	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
8:00	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
9:00 (Anti-Thrust)	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
10:00	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
11:00	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
12:00 (Front)	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1
Average	S123.1	S123.1	S123.1	S123.1	S123.1	S123.1

Summary	As Measured	Outlier Screened
Average, µm	S123.1	S12.1
Std. Dev., µm	S123.1	S123.1
Minimum, µm	S123.1	S123.1
Maximum, µm	S123.1	S123.1
Outlier Liners^A	CCCCC	

^A Cylinder Number.

D 6987
Mack T-10 EGR Engine Oil Test
Form 12
Test Fuel Analysis (Last Batch)

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM	
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC			
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC			
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC			
Supplier: CCCCCCCCCCCCCCCCCC		Batch Identifiers: CCCCCCCCCCCCCC	

Measurement	Specs.	Analysis		Test Method
		New	EOT	
Total Sulfur, % Weight	0.04 – 0.05	S1.12	S1.12	D 2622
Gravity, °API	34.5 – 36.5	S1.1	S1.1	D 287 or D 4052
Hydrocarbon Composition				
Aromatics % Vol.	28 – 33	S1.1		D 1319
Olefin	Report	S12.1		D 1319
Cetane Index	Report	S1.1		D 976 & D 4737
Cetane No.	42 – 48	S1.1		D 613
Copper Strip Corrosion	1 Maximum	AAAA		D 130
Flash Point, °C	54 Minimum	S123		D 93
Pour Point, °C	-18 Maximum	S123		D 97
Carbon Residue on 10% Residuum, %	0.35 Maximum	S1.12		D 524 (10% Bottoms)
Water & Sediment, % Vol.	0.05 Maximum	AAAAAA		D 2709
Viscosity, cSt @ 40°C	2.4 – 5.0	S1.1		D 445
Total Acid Number	0.05 Maximum	S1.1		D 664
Strong Acid Number	0.00 Maximum	S1.1		D 664
Accelerated Stability	Tbd	S1.1		D 2274
Distillation, °C				
IBP	Report	S1234		D 86
10%	Report	S1234		D 86
50%	Report	S1234		D 86
90%	282 – 338	S1234		D 86
EP	Report	S1234		D 86

D 6987
Mack T-10 EGR Engine Oil Test
Form 13
Characteristics of the Data Acquisition System

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Parameter (1)	Sensing Device (2)	Calibration Frequency (3)	Record Device (4)	Observation Frequency (5)	Record Frequency (6)	Log Frequency (7)	System Response (8)
Temperatures							
Oil @ Filt.	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Fuel In.	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Intake Air	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Intake Man.	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Pre-Turb.	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Cool. Out	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Other							
Fuel Flow	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Engine RPM	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Load	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Inlet Restr.	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Exh. Press.	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC
Oil Gal. Press.	CCCCCCCCCC	CCCCCCCCCC	CCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCCCC	CCCCCCCC

Legend:

- (1) **Operating Parameter**
- (2) **The type of device used to measure temperature, pressure or flow**
- (3) **Frequency at which the measurement system is calibrated**
- (4) **The type of device where data is recorded**
 LG - Handlog Sheet
 DL - Automatic Data Logger
 SC - Strip Chart Recorder
 C/M - Computer, Using Manual Data Entry
 C/D - Computer, Using Direct I/O Entry
- (5) **Data are observed but only if recorded off spec.**
- (6) **Data are recorded but are not retained at EOT**
- (7) **Data are logged as permanent record, note specify if:**
 SS - Snapshot Taken at Specified Frequency
 AG/X - Average of X Data Points at Specified Frequency
- (8) **Time for the output to reach 63.2% of final value for step change at input**

D 6987
Mack T-10 EGR Engine Oil Test
Form 14
Build-up and Hardware Information

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM	
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC			
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC			
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC			

Injection Timing

Timing Hours	Timing (Deg)
CC	CCCCC
CC	CCCCC
CC	CCCCC
CC	CCCCC
CC	CCCCC
CC	CCCCC
CC	CCCCC
CC	CCCCC
CC	CCCCC
S1	Total Timing Changes

Hardware

Part	Part Number	Serial Number
Primary Turbocharger	CCCCCCCCCCCCCCCCCCCC	
Secondary Charger	CCCCCCCCCCCCCCCCCCCC	
Cylinder Head (front)	CCCCCCCCCCCCCCCCCCCC	cccccccccccccccccccc
Cylinder Head (rear)	CCCCCCCCCCCCCCCCCCCC	cccccccccccccccccccc
Pistons	CCCCCCCCCCCCCCCCCCCC	
Injection Nozzles	CCCCCCCCCCCCCCCCCCCC	
Rod Bearings	CCCCCCCCCCCCCCCCCCCC	
Liners	CCCCCCCCCCCCCCCCCCCC	
Ring Set	CCCCCCCCCCCCCCCCCCCC	

Cylinder Kit Location	CPD ID Number
Cylinder 1	CCCCCCCCCCCCCCCCCCCC
Cylinder 2	CCCCCCCCCCCCCCCCCCCC
Cylinder 3	CCCCCCCCCCCCCCCCCCCC
Cylinder 4	CCCCCCCCCCCCCCCCCCCC
Cylinder 5	CCCCCCCCCCCCCCCCCCCC
Cylinder 6	CCCCCCCCCCCCCCCCCCCC

D 6987
Mack T-10 EGR Engine Oil Test
Form 15
Rating Summary: Piston #1

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM	
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC			
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC			
Formulation/Stand Code: CC-C-CCCCCCCCC-C-C-CCCCCC-CC-CC-CCCC			
Date Rated: YYYYMMDD	Rater Initials: CCC	Verified By: CCC	

Total Piston Ratings Summary																				
Dep. Factor	Grooves				Lands				Dep. Factor	Lands				Groove		Oil Cooling		Under Crown		
	No. 1	No. 2	No. 1	No. 2	No. 1	No. 2	No. 1	No. 2		No. 3	No. 4	A, %	Dem.	A, %	Dem.	A, %	Dem.	A, %	Dem.	
HC-1.0	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
MC-0.5	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
LC-25	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
Total	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
8-9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
7-7.9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
6-6.9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
5-5.9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
4-4.9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
3-3.9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
2-2.9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
1-1.9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
>0-0.9	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
Clean	S123	0	S123	0	S123	0	S123	0	S123	0	S123	0	S123	0	S123	0	S123	0	S123	0
Total	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12
Rating	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12
Location Factor	2	3	1	3	1	3	1	3	20	20	60	60	0.5	0.5	1	1	1	1	1	1
Ind Rating	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12
WDP	TGC		TGC		TLC		TLC		Unweighted Deposits		Unweighted Deposits		T. L. Flaked Carbon %		T. L. Flaked Carbon %		T. L. Flaked Carbon %		T. L. Flaked Carbon %	
S1234.1	S12.12		S12.12		S12.12		S12.12		S1234.1		S1234.1		S123456		S123456		S123456		S123456	

D 6987
Mack T-10 EGR Engine Oil Test
Form 17
Rating Summary: Piston #3

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM	
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC			
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC			
Formulation/Stand Code: CC-C-CCCCCCCC-C-C-CCCCCC-CC-CC-CCCC			
Date Rated: YYYYMMDD	Rater Initials: CCC	Verified By: CCC	

Total Piston Ratings Summary																		
Dep. Factor	Grooves			Lands			Dep. Factor	Groove			Lands			Oil Cooling		Under Crown		
	No. 1	No. 2	No. 1	No. 1	No. 2	No. 1		No. 3	No. 3	No. 3	No. 3	No. 4	A, %	Dem.	A, %	Dem.	A, %	Dem.
HC-1.0	S123	S123.12	S123	S123	S123.12	S123	S123	S123.12	S123	S123.12	S123	S123	S123.12	S123	S123.12			
MC-0.5	S123	S123.12																
LC-25	S123	S123.12	S123	S123	S123.12	S123	S123	S123.12	S123	S123.12	S123	S123	S123.12	S123	S123.12	S123	S123.12	S123
Total	S123	S123.12	S123	S123	S123.12	S123												
8-9	S123	S123.12	S123	S123.12	S123	S123.12												
7-7.9	S123	S123.12	S123	S123.12	S123	S123.12	7.5	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123
6-6.9	S123	S123.12	S123	S123.12	S123	S123.12												
5-5.9	S123	S123.12	S123	S123.12	S123	S123.12	4.5	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123
4-4.9	S123	S123.12	S123	S123.12	S123	S123.12												
3-3.9	S123	S123.12	S123	S123.12	S123	S123.12												
2-2.9	S123	S123.12	S123	S123.12	S123	S123.12												
1-1.9	S123	S123.12	S123	S123.12	S123	S123.12	1.5	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123
>0-0.9	S123	S123.12	S123	S123.12	S123	S123.12												
Clean	S123	0	S123	0	S123	0	Clean	S123	0	S123	0	S123	0	S123	0	S123	0	S123
Total	S123	S123.12	S123	S123.12	S123	S123.12		S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123	S123.12	S123
Rating	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12		S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12
Location Factor	2	3	1	3	3	3		20	20	20	60	60	60	0.5	0.5	1	1	1
Ind Rating	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12		S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12	S123.12
WDP	TGC			TLC				Unweighted Deposits			T. L. Flaked Carbon %							
S1234.1	S12.12			S12.12				S1234.1			S1234.56							

D 6987
Mack T-10 EGR Engine Oil Test
Form 21
Main Bearing Weight Loss

Laboratory: CC	EOT Date: YYYYMMDD	EOT Time: HH:MM
Test Number: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Oil Code: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Formulation/Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		

Position #	Location	SOT Weight, g	EOT Weight, g	Weight Change, mg
1	Upper	S12.1234	S12.1234	S123.1
2	Upper	S12.1234	S12.1234	S123.1
3	Upper	S12.1234	S12.1234	S123.1
4	Upper	S12.1234	S12.1234	S123.1
5	Upper	S12.1234	S12.1234	S123.1
6	Upper	S12.1234	S12.1234	S123.1
7	Upper	S12.1234	S12.1234	S123.1
Upper Bearing Average Weight Loss, mg				S123.1
Upper Bearing Weight Loss Std. Dev., mg				S123.1
Upper Bearing Minimum Weight Loss, mg				S123.1
Upper Bearing Maximum Weight Loss, mg				S123.1

Position #	Location	SOT Weight, g	EOT Weight, g	Weight Change, mg
1	Lower	S12.1234	S12.1234	S123.1
2	Lower	S12.1234	S12.1234	S123.1
3	Lower	S12.1234	S12.1234	S123.1
4	Lower	S12.1234	S12.1234	S123.1
5	Lower	S12.1234	S12.1234	S123.1
6	Lower	S12.1234	S12.1234	S123.1
7	Lower	S12.1234	S12.1234	S123.1
Lower Bearing Average Weight Loss, mg				S123.1
Lower Bearing Weight Loss Std. Dev., mg				S123.1
Lower Bearing Minimum Weight Loss, mg				S123.1
Lower Bearing Maximum Weight Loss, mg				S123.1

Main Bearing Batch ID	CCCCCCCCCCCC
------------------------------	--------------

D 6987
Mack T-10 EGR Engine Oil Test
Form 22
American Chemistry Council Code of Practice
Test Laboratory Conformance Statement

Test Laboratory	CC				
Test Sponsor	CC				
Formulation / Stand Code	CC-CCCCCCCCCC-C-C-CCCCCC-CC-CC-CCCC				
Test Number	CC				
Start Date	YYYYMMDD	Start Time	HH:MM	Time Zone	CCC

Declarations

No. 1 All requirements of the ACC Code of Practice for which the test laboratory is responsible were met in the conduct of this test. Yes C No C *

No. 2 The laboratory ran this test for the full duration following all procedural requirements; and all operational validity requirements of the latest version of the applicable test procedure (ASTM or other) including all updates issued by the organization responsible for the test, were met. Yes C No C *

If the response to this Declaration is "No", does the test engineer consider the deviations from operational validity requirements that occurred to be beyond the control of the laboratory? Yes C * No C

No. 3 A deviation occurred for one of the test parameters identified by the organization responsible for the test as being a special case. Yes C * No C (*This currently applies only to specific deviations identified in the ASTM Information Letter System*)

Check The Appropriate Conclusion

C	Operational review of this test indicates that the results should be included in the Multiple Test Acceptance Criteria calculations.
C	*Operational review of this test indicates that the results should not be included in the Multiple Test Acceptance Criteria calculations.

Note: *Supporting comments are required for all responses identified with an asterisk.*

Comments	
	CC
	CC
	CC
	CC

Signature Image _____

Signature

CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC _____

Typed Name

YYYYMMDD _____

Date

CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC _____

Title