

**Mack T-11
D 7156 - EGR Engine Oil Test**

Report Packet Version No.

Conducted For

	V = Valid; The reference oil/non-reference oil was evaluated in accordance with the test procedure.
	I = Invalid; The reference oil/non-reference oil was not evaluated in accordance with the test procedure.
	N = Results cannot be interpreted as representative of oil performance (non-reference oil) and shall not be used in determining an average test result using multiple test criteria.

	NR = Non Reference Oil Test
	RO = Reference Oil Test

Test Number			
Stand:	Stand Run:	Engine:	Engine Hours:
End Of Test Date:		End Of Test Time:	
Oil Code:			
Formulation/Stand Code:			
Altcode1:	Altcode2:	Altcode3:	

In my opinion this test _____ been conducted in a valid manner in accordance with the Test Method D 7156 and the appropriate amendments through the information letter system. The remarks included in this report describe the anomalies associated with this test.

Submitted By:

_____ Testing Laboratory

_____ Signature

_____ Typed Name

_____ Title

Mack T-11
D 7156 - EGR Engine Oil Test
Form 2

Table of Contents

1.	Final Report Cover Sheet	Form 1
2.	Table of Contents	Form 2
3.	Summary of Test Method	Form 3
4.	Test Results Summary	Form 4
5.	Operational Summary	Form 5
6.	Oil Analysis Summary	Form 6
7.	Oil Analysis Summary	Form 7
8.	Oil Analysis Summary	Form 8
9.	Test Fuel Analysis (Last Batch)	Form 9
10.	Characteristics of the Data Acquisition System	Form 10
11.	Build-up and Hardware Information	Form 11
12.	Unscheduled Downtime & Maintenance Summary	Form 12
13.	ACC Conformance Statement	Form 13

Mack T-11
D 7156 - EGR Engine Oil Test
Form 3
Summary of Test Method

The Mack T-11 EGR Engine oil Test is a fuel engine-dynamometer test which evaluates diesel engine oils for performance characteristics including viscosity increase and soot concentrations (loading). This test is a single-phase, steady state test (constant speed and load). The test is 252 hours and is run with retarded fuel injection timing to produce elevated soot levels in the oil.

The test engine is a Mack E-TECH V-MAC III diesel engine with EGR. It is an in-line six-cylinder, four stroke, turbocharged engine. It has electronically controlled fuel injection with six individual electronic pumps.

Mack T-11 Test Conditions

Parameter	Value
Time, h	252
Injection Timing, °BTDC	Variable
Speed, r/min	1800
Fuel Flow, kg/h	53.5
Intake CO ₂ , %	1.5
Exhaust CO ₂ , %	Record
Inlet Manifold Temp., °C	70
Coolant Out Temp., °C	66
Fuel In Temp., °C	40
Oil Gallery Temp., °C	88
Intake Air Temp., °C	25
Intake Air Restriction, kPa	3.5 – 4.0
Inlet Manifold Pressure, kPa	Tbd
Exhaust Back Pressure, kPa	2.7 – 3.5
Crankcase Pressure, kPa	0.25 – 0.75
Power, kW	Record
Torque, Nm	Record
Pre-Turbine Exhaust Temp., °C	Record
Tailpipe Exhaust Temp., °C	Record
Oil Sump Temp., °C	Record
EGR Pre-Venturi Temp., °C	Record
Inlet Air Dew Point, °C	Record
Fuel Pressure, kPa	Record
Main Gallery Oil Pressure, kPa	Record
Oil Filter Delta P, kPa	Not to exceed 138

Mack T-11
D 7156 - EGR Engine Oil Test
Form 4
Test Results Summary

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation/Stand Code:		

Test Results		
Date Test Started:	Start Time:	
SAE Viscosity:	Test Length:	
TMC Oil Code:^A	Laboratory Oil Code:	
TGA Soot % at 96 h		
TGA Soot % at 192 h		
TGA Soot % at 228 h		
TGA Soot % at 252 h		
Centrifugal Oil Filter Mass Gain, g		
Oil Filter Delta P, kPa		
EOT TBN		
Oil Consumption, g/hr		
Viscosity Increase at 6.0% Soot, cSt		
MRV Yield Stress, cP		
	Soot at 12 cSt (%)	MRV (cP)
Original Result		
Transformed Result		
Correction Factor		
Corrected Transformed Result		
Severity Adjustment		
Final Transformed Result		
Final Original Unit Result		

Last Stand Reference Results		
Test Number:		
Oil Code:		
Test Length:	TMC Oil Code:	
EOT Date:	EOT Time:	
Stand Calibration Expiration Date:		
TGA Soot % at 96 h		
TGA Soot % at 192h		
TGA Soot % at 228h		
TGA Soot % at 252 h		
Oil Consumption, g/hr		
Viscosity at 6.0% Soot, cSt		
	Soot at 12 cSt (%)	MRV
Final Original Unit Result		

^A Reference Tests only.

**Mack T-11
D 7156 - EGR Engine Oil Test
Form 5
Operational Summary**

Laboratory:	EOT Date:
Test Number:	EOT Time:
Oil Code:	
Formulation/Stand Code:	

Parameter	Units	QI Threshold	EOT QI ^A	Target	Average	Samples ^B	BQD ^C	Over/Under Range ^D
Controlled Parameters								
Speed	r/min	0.000		1800				
Fuel Flow	kg/h	0.000		53.5				
Inlet Manifold Temp.	°C	0.000		70				
Coolant Out Temp.	°C	0.000		66				
Fuel In Temp.	°C	0.000		40				
Oil Gallery Temp.	°C	0.000		88				
Inlet Air Temp.	°C	0.000		25				
Inlet Air Restriction	kPa			3.5 – 4.0				
Inlet Man. Pressure	kPa			140 minimum				
Exh. Back Pressure	kPa			2.7 – 3.5				
Crankcase Pressure	kPa			0.25 – 0.75				
Intake CO ₂	%			1.5±.05				
Non-controlled Parameters								
Parameter	Units	Typical Values ^E		Average				
Power	kW		TBD					
Torque	Nm		TBD					
Exhaust CO ₂	%		TBD					
Pre-Turbine Temp. (F)	°C		TBD					
Pre-Turbine Temp. (R)	°C		TBD					
Tailpipe Temp.	°C		TBD					
Oil Sump Temp.	°C		TBD					
EGR Pre-Venturi Temp.	°C		TBD					
Blowby	L/min		TBD					
Inlet Air Dew Point	°C		TBD					
Fuel Pressure	kPa		TBD					
Main Gallery Oil Press.	kPa		TBD					

^A QI values above the threshold are acceptable by the Mack Surveillance Panel. QI values below the threshold may not be considered acceptable based on an engineering review. Refer to Annex A3
^B Total number of data points taken. Minimum acceptable value is 2520
^C Number of Bad Quality Data points not used in the calculation of the statistical measures.
^D Number of points clipped by over/under range limits.
^E Typical values determined from reference oil test database

Mack T-11
D 7156 - EGR Engine Oil Test
Form 9
Test Fuel Analysis (Last Batch)

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation/Stand Code:		
Supplier:		Batch Identifiers:

Measurement	Specs.	Analysis		Test Method
		NEW	EOT	
Total Sulfur, % Weight	0.04 – 0.05			D 2622
Gravity, °API	34.5 – 36.5			D 287 or D 4052
Hydrocarbon Composition				
Aromatics % Vol.	28 – 33			D 1319
Olefin	Report			D 1319
Cetane Index	Report			D 976 & D 4737
Cetane No.	42 – 48			D 613
Copper Strip Corrosion	1 Maximum			D 130
Flash Point, °C	54 Minimum			D 93
Pour Point, °C	-18 Maximum			D 97
Carbon Residue on 10% Residuam, %	0.35 Maximum			D 524 (10% Bottoms)
Water & Sediment, % Vol.	0.05 Maximum			D 2709
Viscosity, cSt @ 40°C	2.4 – 5.0			D 445
Total Acid Number	0.05 Maximum			D 664
Strong Acid Number	0.00 Maximum			D 664
Accelerated Stability	tbd			D 2274
Distillation, °C				
IBP	Report			D 86
10%	Report			D 86
50%	Report			D 86
90%	282 – 338			D 86
EP	Report			D 86

**Mack T-11
D 7156 - EGR Engine Oil Test
Form 10**

Characteristics of the Data Acquisition System

Laboratory:	EOT Date:	EOT Time:
Test Number:		
Oil Code:		
Formulation/Stand Code:		

Parameter (1)	Sensing Device (2)	Calibration Frequency (3)	Record Device (4)	Observation Frequency (5)	Record Frequency (6)	Log Frequency (7)	System Response (8)
Temperatures							
Oil @ Filt.							
Fuel In.							
Intake Air							
Intake Man.							
Pre-Turb.							
Cool. Out							
Other							
Fuel Flow							
Engine RPM							
Load							
Inlet Restr.							
Exh. Press.							
Oil Gal. Press.							

LEGEND:

- (1) Operating Parameter
- (2) The type of device used to measure temperature, pressure or flow
- (3) Frequency at which the measurement system is calibrated
- (4) The type of device where data is recorded
 LG - Handlog Sheet
 DL - Automatic Data Logger
 SC - Strip Chart Recorder
 C/M - Computer, Using Manual Data Entry
 C/D - Computer, Using Direct I/O Entry
- (5) Data are observed but only if recorded off spec.
- (6) Data are recorded but are not retained at EOT
- (7) Data are logged as permanent record, note specify if:
 SS - Snapshot Taken at Specified Frequency
 AG/X - Average of X Data Points at Specified Frequency
- (8) Time for the output to reach 63.2% of final value for step change at input

Mack T-11
D 7156 - EGR Engine Oil Test
Form 13
American Chemistry Council Code of Practice
Test Laboratory Conformance Statement

Test Laboratory					
Test Sponsor					
Formulation / Stand Code					
Test Number					
Start Date		Start Time		Time Zone	

Declarations

No. 1 All requirements of the ACC Code of Practice for which the test laboratory is responsible were met in the conduct of this test. Yes _____ No _____*

No. 2 The laboratory ran this test for the full duration following all procedural requirements; and all operational validity requirements of the latest version of the applicable test procedure (ASTM or other), including all updates issued by the organization responsible for the test, were met.
 Yes _____ No _____*

If the response to this Declaration is “No”, does the test engineer consider the deviations from operational validity requirements that occurred to be beyond the control of the laboratory?
 Yes _____* No _____

No. 3 A deviation occurred for one of the test parameters identified by the organization responsible for the test as being a special case. Yes _____* No _____ (*This currently applies only to specific deviations identified in the ASTM Information Letter System*)

Check the Appropriate Conclusion

	Operational review of this test indicates that the results should be included in the Multiple Test Acceptance Criteria calculations.
	*Operational review of this test indicates that the results should not be included in the Multiple Test Acceptance Criteria calculations.

Note: *Supporting comments are required for all responses identified with an asterisk.*

Comments

Signature

Date

Typed Name

Title