

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION
D4863 ASTM TC SEQUENCE II

SUMMARY OF ENGINE TEST RESULTS
YAMAHA CE50S TIGHTENING TEST

Test Number: _____ Fuel: _____ Start Date: _____
 Stand Number: _____ Fuel/Oil Ratio: _____ E.O.T. Date: _____
 Test Length: _____ SI234 Fuel Batch ID: _____

Delta Torque, lbs. in.

Lubricant Code:	Ind	Bench	Lab Code	Tightening No.:
Temperature, °C	S12	S12	S12	Mean
300	S1.12	S1.12	S1.12	S1.12
325	S1.12	S1.12	S1.12	S1.12
350	S1.12	S1.12	S1.12	S1.12

Lubricant Code:	Ind	Bench	Lab Code	Tightening No.:
Temperature, °C	S12	S12	S12	Mean
300	S1.12	S1.12	S1.12	S1.12
325	S1.12	S1.12	S1.12	S1.12
350	S1.12	S1.12	S1.12	S1.12

Lubricant Code:	Ind	Bench	Lab Code	Tightening No.:
Temperature, °C	S12	S12	S12	Mean
300	S1.12	S1.12	S1.12	S1.12
325	S1.12	S1.12	S1.12	S1.12
350	S1.12	S1.12	S1.12	S1.12

Lubricant Code:	Ind	Bench	Lab Code	Tightening No.:
Temperature, °C	S12	S12	S12	Mean
300	S1.12	S1.12	S1.12	S1.12
325	S1.12	S1.12	S1.12	S1.12
350	S1.12	S1.12	S1.12	S1.12

Temperature, °C	Mean	Mean
300	S1.12	S1.12
325	S1.12	S1.12
350	S1.12	S1.12

Code	Date	Test Number	Mean
CCCCCCCCCCCC	YYYYMMDD	CCCCCCCCCCCC	S1.12
CCCCCCCCCCCC			S1.12
CCCCCCCCCCCC	YYYYMMDD	CCCCCCCCCCCC	S1.12
CCCCCCCCCCCC			S1.12

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION
D4863 ASTM TC SEQUENCE II

SUMMARY OF ENGINE TEST RESULTS
YAMAHA CE50S TIGHTENING TEST

Lubricant Code: CCCCCCCCCCCCCCCCCC Test Number: CCCCCCCCCCCCCCCCCC E.O.T. Date: CCCCCCCC

Student T Test For Significance of Difference Between

	<u>Benchmark</u>	<u>Non-Reference</u>	
Code:	CCCCCCCCCCCCCCCCCC	CCCCCCCCCCCCCCCCCC	CCCCCCCCCCCCCCCCCC
Lab Code:	CCCCCCCCCCCCCCCCCC	CCCCCCCCCCCCCCCCCC	
Number of Data Points:	S12	S12	
Mean:	S1.12	S1.12	CCCC
Std. Dev. (n-1):	S1.1234	S1.1234	
Outlier Tightening Numbers:	CCCCCCCCCCCCCCCCCC	CCCCCCCCCCCCCCCCCC	
Variance:	S1.1234	S1.1234	
Combined Estimate of Std. Dev:	S1.1234		
Degrees of Freedom:	S12		
Critical Value t*:	S1.1234		
t Critical 0.05 (95% confidence):			
Confidence Level:	S1.123		

On the basis of the Student "T" test there is ^{CCC} a significant difference between the reference and non reference lubricants at the 95% confidence level.

t* is compared to the critical value of t, t critical, from table A4.1.

TABLE A4.1 Critical Values of the t -

Degrees of Freedom	Degrees of Confidence				
	90%	95%	97.5%	99%	99.5%
10	1.372	1.812	2.228	2.764	3.169
11	1.363	1.796	2.201	2.718	3.106
12	1.356	1.782	2.179	2.681	3.055
13	1.350	1.771	2.160	2.650	3.012
14	1.345	1.761	2.145	2.624	2.977
15	1.341	1.753	2.131	2.602	2.947
16	1.337	1.746	2.120	2.583	2.921
17	1.333	1.740	2.110	2.567	2.898
18	1.330	1.734	2.101	2.552	2.878
19	1.328	1.729	2.093	2.539	2.861
20	1.325	1.725	2.086	2.528	2.845
21	1.323	1.721	2.080	2.518	2.831
22	1.321	1.717	2.074	2.508	2.819
23	1.319	1.714	2.069	2.500	2.807
24	1.318	1.711	2.064	2.492	2.797
25	1.316	1.705	2.060	2.485	2.787
26	1.315	1.706	2.056	2.479	2.779
27	1.314	1.703	2.052	2.473	2.771
28	1.313	1.701	2.048	2.467	2.763
29	1.311	1.699	2.045	2.462	2.756
30	1.310	1.697	2.042	2.457	2.750

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION

SUMMARY OF ENGINE TEST RESULTS
YAMAHA CE50S TIGHTENING TEST

CCCCCCCCCCCCCCCCCC Lab Code: CCCCCCCCCC Tightening No.: CCCCCC

Operating Parameters

Miscellaneous

	S12	S12	S12	S12	S12	S12	S12	<u>Average</u>
Tightening No.	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1
Seconds	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
Fuel Flow, lb/h	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
Horsepower, ft-lbf.	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
Barometer Press., in. Hg	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

Temperature, °F

Ambient	S12	S12	S12	S12	S12	S12	S12	S12
Wet	S12	S12	S12	S12	S12	S12	S12	S12
Dry	S12	S12	S12	S12	S12	S12	S12	S12
Dynamometer	S12	S12	S12	S12	S12	S12	S12	S12
Intake Air	S12	S12	S12	S12	S12	S12	S12	S12
Fuel	S12	S12	S12	S12	S12	S12	S12	S12
Exhaust	S123	S123	S123	S123	S123	S123	S123	S123

Torque, lbf-in.

@ 170°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 200°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 300°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 325°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 350°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

Delta Torque, lbf-in.

@ 300°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 325°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 350°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION
D4863 ASTM TC SEQUENCE II

SUMMARY OF ENGINE TEST RESULTS
YAMAHA CE50S TIGHTENING TEST

CCCCCCCCCCCCCCCCCC Lab Code: CCCCCCCCCCCCCCC Lab Code: Tightening No.: CCCCCC

Operating Parameters

Miscellaneous

	S12	S12	S12	S12	S12	S12	S12	<u>Average</u>
Tightening No.	S12	S12	S12	S12	S12	S12	S12	S12
Seconds	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1
Fuel Flow, lb/h	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
Horsepower, ft-lbf.	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
Barometer Press., in. Hg	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

Temperature, °F

Ambient	S12	S12	S12	S12	S12	S12	S12	S12
Wet	S12	S12	S12	S12	S12	S12	S12	S12
Dry	S12	S12	S12	S12	S12	S12	S12	S12
Dynamometer	S12	S12	S12	S12	S12	S12	S12	S12
Intake Air	S12	S12	S12	S12	S12	S12	S12	S12
Fuel	S12	S12	S12	S12	S12	S12	S12	S12
Exhaust	S123	S123	S123	S123	S123	S123	S123	S123

Torque, lbf-in.

@ 170°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 200°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 300°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 325°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 350°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

Delta Torque, lbf-in.

@ 300°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 325°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 350°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION
D4863 ASTM TC SEQUENCE II

SUMMARY OF ENGINE TEST RESULTS
YAMAHA CE50S TIGHTENING TEST

CCCCCCCCGCCCCCECCCCCCCCCCCCCCCCCCCCG CCCCCCCCCC Tightening No.: CCCCCC
Lubricant Code: Lab Code:

Operating Parameters

Miscellaneous

	S12	S12	S12	S12	S12	S12	S12	<u>Average</u>
Tightening No. Seconds	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1	S12.1
Fuel Flow, lb/h	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
Horsepower, ft-lbf.	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
Barometer Press., in. Hg	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

Temperature, °F

Ambient	S12	S12	S12	S12	S12	S12	S12	S12
Wet	S12	S12	S12	S12	S12	S12	S12	S12
Dry	S12	S12	S12	S12	S12	S12	S12	S12
Dynamometer	S12	S12	S12	S12	S12	S12	S12	S12
Intake Air	S12	S12	S12	S12	S12	S12	S12	S12
Fuel	S12	S12	S12	S12	S12	S12	S12	S12
Exhaust	S123	S123	S123	S123	S123	S123	S123	S123

Torque, lbf-in.

@ 170°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 200°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 300°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 325°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 350°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

Delta Torque, lbf-in.

@ 300°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 325°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12
@ 350°C	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12	S1.12

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION

D4863 ASTM TC SEQUENCE II

Test Oil Code: CCCCCCCCCCCCCCCCCC	Test Number: CCCCCCCCCCCCCCCCCC	EOT Date: CCCCCCCCCCCCCCCCCC
--	--	---

Total Number of Remarks or Deviations

S12

Remark or Deviation

CC

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION

D4863 ASTM TC SEQUENCE II

Test Fuel Analysis (Last Batch)

Lab: CC	EOT Date: YYYYMMDD	End Time: HH:MM
Stand: CCCCC	Run Number: CCCCCCCCCCCCCC	
Formulation / Stand Code: CC-CCCCCCCCC-C-C-CCCCC-CC-CC-CCCC		
Supplier: CCCCCCCCCC	Batch Identifier: CCCCCCCCCCCCCC	

Measurement	Specs.	Analysis	Test Method
Gravity, °API		S1.1	
Color		CCCCCCCC	
Doctor Test		CCCCCCCC	
Copper Corrosion, 3 h @ 212 °F	1 Maximum	S123	D 130
Reid Vapor Pressure, psig		S.1	
Research Octane Number		S1.1	
Motor Octane Number		S1.1	
(Research + Motor) / 2		S1.1	
Total Sulfur, % Weight	0.04 - 0.05	S1.12	D 2622
Gum, mg/100 mL		S.1	
Oxidation Stability, min		S1234	
Lead, g/gal		S1.123	
Distillation, °C			
IBP	Report	S1234	D 86
10%	Report	S1234	D 86
50%	Report	S1234	D 86
90%	282 - 338	S1234	D 86
EP	Report	S1234	D 86
Recovery, %		S12.1	
Pona, % vol			
Paraffins + Napthenes		S12.1	
Olefin	Report	S12.1	D 1319
Aromatics % Vol.	28 - 33	S12.1	D 1319