

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION
ASTM TC SEQUENCE III

SUMMARY OF ENGINE TEST RESULTS
YAMAHA CE50S TIGHTENING TEST

Sponsor Code: CCCCCCCCCCCCCCCCCC	Test Number: CCCCCCCCCC	Start Date: CCCCCC
Lab Code: CCCCCCCCCC	Fuel Oil Ratio: CCCCC	E.O.T. Date: CCCCCC
Fuel Code: CCCCCCCCCC	Stand Number: CCCCC	Hours: CCCCC
Industry Oil Code: CCCCC		

Test Conditions Data

<u>Miscellaneous</u>	<u>Maximum</u>	<u>Minimum</u>	<u>Average</u>
Engine Speed, r/min	S1234	S1234	S1234
Observed Load, hp	S1.12	S1.12	S1.12
Corrected Load, hp*	S1.12	S1.12	S1.12
Fuel Flow, lb/h.	S1.12	S1.12	S1.12
Exhaust Back Press. in. H2O	S1.1	S1.1	S1.1
Barometer, in. Hg	S12.12	S12.12	S12.12

Temperature, °F

Spark Plug	S123	S123	S123
Combustion Chamber	S123	S123	S123
Exhaust	S123	S123	S123
Fuel	S12	S12	S12
Intake Air, Carburetor	S12	S12	S12
Ambient	S12	S12	S12
Wet	S12	S12	S12
Dry	S12	S12	S12

	<u>Preignition</u>		<u>Spark Plug</u>	<u>Exhaust</u>
	<u>Major</u>	<u>Minor</u>	<u>Change</u>	<u>Change</u>
Totals	S12	S12	S12	S12

Previous Reference Data

<u>Code</u>	<u>Test No.</u>	<u>Date</u>	<u>Preignition</u>	<u>Preignition</u>
			<u>Major</u>	<u>Minor</u>
CCCCCCCC	CCCCCCCC	CCCCYYMMDD	S12	S12
CCCCCCCC	CCCCCCCC	CCCCYYMMDD	S12	S12

^ACorrected To:
Barometric Pressure - 29.92
Temperature - 60°F

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION
ASTM TC SEQUENCE III

SUMMARY OF ENGINE TEST RESULTS
YAMAHA CE50S TIGHTENING TEST

CC CCC CCC
Sponsor Code: Lab Code: Test Number:

Test Conditions Data

<u>Test Hours</u>	<u>Preignition, °F</u>		<u>Spark Plug Change</u>	<u>Exhaust Change</u>
	<u>Major</u>	<u>Minor</u>		
S12.1	S12	S12	CCC	CCC

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION
ASTM TC SEQUENCE III Test Procedure

Test Oil Code: CCCCCCCCCCCCCCCCCC	Test Number: CCCCCCCCCCCCCCCCCC	EOT Date: CCCCCCCCCC
--	--	-----------------------------

Total Number of Remarks or Deviations

S12

Remark or Deviation

CC

TWO-STROKE-CYCLE GASOLINE ENGINE LUBRICANT EVALUATION
ASTM TC SEQUENCE III

SUMMARY OF ENGINE TEST RESULTS

Lab: CC	EOT Date: YYYYMMDD	End Time: HH:MM
Stand: CCCCC	Run Number: CCCC	
Oilcode: CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		
Formulation / Stand Code: CC-CCCCCCCCC-C-C-CCCCCC-CC-CC-CCCC		
Supplier: CCCCCCCCCCCCCCCCCC		Batch Identifier: CCCCCCCCCC

Measurement	Specs.	Analysis	Test Method
Gravity, °API		S1.1	
Color		CCCCCCCC	
Doctor Test		CCCCCCCC	
Copper Corrosion, 3 h @ 212 °F	1 Maximum	S123	D 130
Reid Vapor Pressure, psig		S.1	
Research Octane Number		S1.1	
Motor Octane Number		S1.1	
(Research + Motor) / 2		S1.1	
Total Sulfur, % Weight	0.04 - 0.05	S1.12	D 2622
Gum, mg/100 mL		S.1	
Oxidation Stability, min		S1234	
Lead, g/gal		S1.123	
Distillation, °C			
IBP	Report	S1234	D 86
10%	Report	S1234	D 86
50%	Report	S1234	D 86
90%	282 - 338	S1234	D 86
EP	Report	S1234	D 86
Recovery, %		S12.1	
Pona, % vol			
Paraffins + Napthenes		S12.1	
Olefin	Report	S12.1	D 1319
Aromatics % Vol.	28 - 33	S12.1	D 1319