TEST METHOD D6335 DETERMINATION OF HIGH TEMPERATURE DEPOSITS BY THERMO-OXIDATION ENGINE OIL SIMULATION TEST

VERSION TEOST VERSION 20020311

CONDUCTED FOR

С		V = VALID
		I = INVALID
•		
CC NR = Non Reference Oil Test		on Reference Oil Test
	RO = R	eference Oil Test

Test Number				
Instrument ID:	ccccccccccccccc	Test Run Number:	CCCCCCCCC	

Date Completed: YYY	YMMDD	EOT Time: HH:MM		
Oil Code: cccccccccccccccccccccccccccccccccccc				
Alternate Codes: ccccccccccc		ccccccccccc	cccccccccccc	

In my opinion this test CCCCCCC been conducted in a manner in accordance with the Test Method D6335 and the appropriate amendments through the information letter system. The remarks included in this report describe the anomalies associated with this test.

SUBMITTED BY:	ccccccccccccccccccccccccccccccccccccc
_	Testing Laboratory
_	Signature Image
_	Signature
_	ccccccccccccccccccccccccccccccccccccccc
_	Typed Name
	cccccccccccccccccccccccccccccccccccc
_	Title

TEST METHOD D6335 DETERMINATION OF HIGH TEMPERATURE DEPOSITS BY THERMO-OXIDATION ENGINE OIL SIMULATION TEST FORM 2 TEST RESULTS SUMMARY SHEET

Oil Code: C	CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
Lab Sample C	ode: ccccccccccccccc

Testing Lab: CC	TMC Reference Oil ID:	CCCCCC
Date Completed: YYYYMMDD	Time Completed:	HH:MM

Instrument ID:	ccccccccc	CCCCCCCC		
Test Run No.:	CCCCCCC	CCCC		
Date of Last TM	C Calibration:	YYYYMMDD	TMC Calibration Expiration Date:	YYYYMMDD

Instrument Conditions		Instrument Checks ^A	
Thermocouple Depth, cm: S123.12		Temperature Program:	C
Sample Flow Rate, g/min: S123.12		PID:	C
Amount Ferric Napthenate, µl: \$123		Strip Chart:	С
Reactor Chamber Temperature, °C: S123		Stirrer On:	С
Test Length, min: S1234		Thermocouple Connections:	С
Rod Serial Number: CCCCC		Air Flow, 3.5 ml/min:	C
		N ₂ O Flow, 3.5 ml/min:	C

Test Results				
Final Rod Wt, g:	S12.1234	Preclean Filter Wt, g:	S12.1234	
Initial Rod Wt, g:	S12.1234	1st Dry Filter Wt, g:	S12.1234	
Rod Deposits, mg:	S12.1	2nd Dry Filter Wt, g:	S12.1234	
		3rd Dry Filter Wt, g:	S12.1234	
		Final Filter Wt, g:	S12.1234	
		Initial (Post-Clean) Filter Wt, g:	S12.1234	
		Filter Deposits, mg:	S12.1	

Total Deposits, mg:	S12.1
---------------------	-------

 $^{^{}A}$ Y = checked to be correct, N = not checked

TEST METHOD D6335 DETERMINATION OF HIGH TEMPERATURE DEPOSITS BY THERMO-OXIDATION ENGINE OIL SIMULATION TEST FORM 3 COMMENTS

Oil Code: cccccccccccccccccccccccccccccccccccc				
Lab Sample Code:				
Testing Lab: CC	TMC Reference Oil ID: CCCCCC			
Date Completed: YYYYMMDD	Time Completed: HH:MM			
Instrument ID: CCCCCCCCCCCCCCCC				
Test Run No.: CCCCCCCCC				
Date of Last TMC Calibration: YYYYMMDD TMC Calibration Expiration Date: YYYYMMDD				

OUT-OF-LIMIT DATA AND TIME, TEST MODIFICATIONS AND COMMENTS

Number of Comment Lines	S1				
ccccccccccccccccccccc	ccccccccccccccccccccccccccccccccccccccc				