



## Test Monitoring Center

Carnegie Mellon University  
6555 Penn Avenue, Pittsburgh, PA 15206, USA

<http://astmtmc.cmu.edu>  
412-365-1000

EOAT Information Letter 12-1  
Sequence No. 3  
May 17, 2012

*ASTM consensus has not been obtained on this information letter. An appropriate ASTM ballot will be issued in order to achieve such consensus.*

TO: EOAT Mailing List  
SUBJECT: EOAT Specified Fuel Designation Change

As approved by email ballot the panel has updated the fuel designation information for the 0.04% sulfur fuel used in the EOAT test; the PC-9-HS designation has been added. Section 7.3 has been updated to reflect this change and is attached.

The attached changes to Test Method D6894 are effective May 3, 2012.

Heather DeBaun  
Lubricants and Coolants  
Navistar, Inc.

Frank M. Farber  
Administrator  
ASTM Test Monitoring Center

Attachment

c: [ftp://ftp.astmtmc.cmu.edu/docs/diesel/EOAT/procedure\\_and\\_ils/il12-1.pdf](ftp://ftp.astmtmc.cmu.edu/docs/diesel/EOAT/procedure_and_ils/il12-1.pdf)

Distribution: Email

**(Revises D6894-11)**

7.3 *Test Fuel*—Use fuel designated as either PC-9 or PC-9-HS containing 0.03 mass % to 0.05 mass % sulfur for this test.<sup>13,16</sup> All fuel shall meet the fuel specifications shown in Table 2. Include in the final report the fuel analysis, provided by the fuel supplier, for the last batch of fuel used for the test. If more than one batch is used during the test, note this in the comments section with the appropriate percentages of run time.