



Test Monitoring Center

@ Carnegie Mellon University
6555 Penn Avenue, Pittsburgh, PA 15206, USA

<http://astmtmc.cmu.edu>
412-365-1000

T-8 Information Letter 16-1
Sequence No. 24
June 9, 2016

TO: Mack Mailing List
SUBJECT: T-8 Sole Source Fuel Supply

During the June 1, 2016 Mack Surveillance Panel teleconference the panel unanimously agreed that the current fuel denoted in the test method is to be designated sole source. As a result, the attached revisions are necessary. Section 7.2 has been updated accordingly.

The attached changes to Test Method D5967-15a are effective with the release of this information letter.

Greg Shank
Manager
Volvo Group Truck Technology
Powertrain Engineering

Frank M. Farber
Director
ASTM Test Monitoring Center

Attachment

c: ftp://ftp.astmtmc.cmu.edu/docs/diesel/mack/procedure_and_ils/T-8/il16-1-T8.pdf

Distribution: Email

(Revises D 5967-15a)

7.2 Test Fuel— Use PC-9-HS test fuel⁶ from Chevron Phillips. The required fuel properties and tolerances are shown in Table 1.

Add the following footnote and renumber footnotes accordingly.

⁶ The sole source of supply for test fuel known to the committee at this time is PC-9-HS Reference Diesel Fuel from Chevron Phillips, Phillips 66 Co. Marketing Services Center, P.O. Box 968, Borger, TX 79008-096. If you are aware of alternative suppliers, please provide this information to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend.