



Test Monitoring Center

Carnegie Mellon University
6555 Penn Avenue, Pittsburgh, PA 15206, USA

<http://astmtmc.cmu.edu>
412-365-1000

Sequence IIIG Information Letter 08-2
Sequence No. 18
November 6, 2008

TO: Sequence III Mailing List
SUBJECT: Sequence IIIIGB Test Creation

The Sequence III Surveillance Panel approved, via electronic ballot, the creation of a new version of the Sequence IIIG test measuring only percent phosphorus retention. Appendix X3 has been added to Test Method D7320 to define the requirements for conducting this procedure, referred to as the Sequence IIIIGB. Sections 1.1.1, 1.4, and 2.1 have also been updated. This change is effective the date of this information letter.

Bruce Matthews
Engine Oil Test Development and Support
GM Powertrain Materials Engineering

John L. Zalar
Administrator
ASTM Test Monitoring Center

Attachment

c: ftp://ftp.astmtmc.cmu.edu/docs/gas/sequenceiii/procedure_and_ils/IIIG/IL08-2.pdf

Distribution: Electronic Mail

1.1.1 Additionally, with non-mandatory supplemental requirements, a IIIGA Test (Mini Rotary Viscometer and Cold Cranking Simulator measurements), a IIIGVS Test (EOT viscosity increase measurement), or a IIIGB Test (phosphorus retention measurement) can be conducted. These supplemental test procedures are contained in Appendixes X1, X2, and X3, respectively.

1.4 This test method is arranged as follows:

Subject	Section
Scope	1
Referenced Documents	2
Terminology	3
Summary of Test Method	4
Significance and Use	5
Apparatus	6
Laboratory	6.1
Drawings	6.2
Specified Equipment	6.3
Test Engine	6.4
Engine Parts	6.4.1
Engine Speed and Load Control	6.5
Fluid Conditioning Module	6.6
Engine Cooling System	6.6.1
Flushing Tank	6.7
Coolant Mixing Tank	6.8
Condenser Cooling Systems	6.9
Engine Oil-Cooling System	6.10
Fuel System	6.11
Induction Air Supply Humidity, Temperature, and Pressure	6.12
Temperature Measurement	6.13
Thermocouple Location	6.13.1
Air-to-Fuel Ratio Determination	6.14
Injector Flow Testing	6.14.1
Exhaust and Exhaust Back Pressure Systems	6.15
Blowby Flow Rate Measurement	6.16
Pressure Measurement and Sensor Location	6.17
Reagents and Materials	7
Test Fuel	7.1
Engine and Condenser Coolant	7.2
Coolant Additive	7.3
Coolant Preparation	7.4
Pre-Test Cleaning Materials	7.5
Sealing and Anti-seize Compounds	7.6
Test Oil Sample Requirements	8
Preparation of Apparatus	9
Condenser Cleaning	9.1
Intake Manifold Cleaning	9.2
Cleaning of Engine Parts (other than the block and heads)	9.3
Connecting Rod Cleaning	9.4
Engine Block Cleaning	9.5
Cylinder Head Cleaning	9.6
Engine Build-up Procedure	9.7
General Information	9.7.1

Subject	Section
Special Parts	9.7.2
Hardware Information	9.7.3
Fastener Torque Specifications and Torquing	9.7.4
Procedures	
Main Bearing Cap Bolts	9.7.4.1
Cylinder Head Bolts	9.7.4.2
Torques for miscellaneous bolts, studs and nuts	9.7.4.3
Parts Replacement	9.8
Engine Block Preparation	9.9
Piston Fitting and Numbering	9.10
Piston Ring Fitting	9.10.1
Pre-Test Camshaft and Lifter Measurements	9.11
Camshaft Bearing Installation	9.12
Camshaft Installation	9.13
Main Bearings	9.14
Crankshaft Installation	9.14.1
Main Bearing Cap Installation	9.14.2
Crankshaft Sprocket	9.15
Camshaft Sprocket and Timing Chain	9.16
Crankshaft End Play	9.17
Piston Pin Installation	9.18
Piston Installation	9.18.1
Harmonic Balancer	9.19
Connecting Rod Bearings	9.20
Engine Front Cover	9.21
Coolant Inlet Adapter	9.22
Oil Dipstick Hole	9.23
Oil Pan	9.24
Cylinder Head Assembly	9.25
Adjustment of Valve Spring Loads	9.26
Cylinder Head Installation	9.27
Hydraulic Valve Lifters	9.28
Pushrods	9.29
Valve Train Loading	9.30
Intake Manifold	9.31
Rocker Covers	9.32
Water Inlet Adapter	9.33
Condenser	9.34
Coolant Outlet Adapter	9.35
Oil Filter Adapter	9.36
Oil Sample Valve	9.37
Ignition System	9.38
Throttle Body	9.39
Accessory Drive Units	9.40
Exhaust Manifolds, Water-Cooled	9.41
Engine Flywheel	9.42
Pressure Checking of Engine Coolant System	9.43
Lifting of Assembled Engines	9.44
Mounting the Engine on the Test Stand	9.45
External Cooling System Cleaning	9.46
Engine Coolant Jacket Cleaning (Flushing)	9.47
Coolant Charging	9.48
Test Oil Charging	9.49
Engine Oil Pump Priming	9.50

Subject	Section
Calibration	10
Laboratory and Engine Test Stand Calibration	10.1
Testing of Reference Oils	10.2
Reference Oil Test Frequency	10.3
Reporting of Reference Oil Test Results	10.4
Evaluation of Reference Oil Test Results	10.5
Status of Non-Reference Oil Tests Relative to Reference Oil Test	10.6
Status of Test Stands Used for Non-Standard Tests	10.7
Data Acquisition and Control	10.8
Sample Rate	10.8.1
Measurement Accuracy	10.8.2
Temperature	10.8.3
Pressure	10.8.4
Flow	10.8.5
Speed	10.8.6
Load	10.8.7
Measurement Resolution	10.8.8
System Time Response	10.8.9
Quality Index	10.8.10
Engine Operating Procedure	11
Dipstick and Hole Plug	11.1
Dipstick Hole O-ring	11.2
Engine Start-up and Shutdown Procedures	11.3
Start-up	11.4
Scheduled Shutdown	11.5
Non-Scheduled Shutdowns	11.6
Oil Sampling	11.7
Oil Leveling	11.8
Air-to-Fuel-Ratio Measurement and Control	11.9
Air-to-Fuel Ratio Verification	11.10
Blowby Flow Rate Measurement	11.11
NO _x Determinations	11.12
Data Recording	11.13
Initial Run (10 min)	11.14
Engine Oil Quality Testing (100 h)	11.15
Test Termination	11.16
Determination of Test Results	12
Engine Disassembly	12.2
Preparation of Parts for Rating of Sticking, Deposits, and Plugging	12.3
Piston Deposit Rating	12.4
Post-Test Camshaft and Lifter Wear Measurements	12.5
Viscosity Test	12.6
Testing Oil Samples for Wear Metals	12.7
Blowby Flow Rate Measurements	12.8
Oil Consumption Computation	12.9
Photographs of Test Parts	12.10
Retention of Representative Test Parts	12.11
Severity Adjustments	12.12
Determination of Operational Validity	12.13
Report	13
Report Forms	13.1
Use of SI Units	13.2
Precision of Reported Units	13.3

Subject	Section
Deviations from Test Operational Limits	13.4
Precision and Bias	14
Keywords	15
Annexes	
The Role of the ASTM Test Monitoring Center (TMC) and the Calibration Program	Annex A1
Sequence IIIG Test Parts Replacement Guidelines	Annex A2
Sequence IIIG Determination Volume of Engine Oil in Pan	Annex A3
Sequence IIIG Test Fuel Analysis	Annex A4
Sequence IIIG Test Reporting	Annex A5
Sequence IIIG Test Air-to-Fuel Ratio Control Flow Chart	Annex A6
Sequence IIIG Test Set Points and Control States	Annex A7
Sequence IIIG Quality Index Upper and Lower Values	Annex A8
Sequence IIIG Engine Oil Level Worksheet	Annex A9
Blowby Flow Rate Determination	Annex A10
Safety Hazards	Annex A11
Sequence IIIG Blueprint Listing	Annex A12
Fluid Conditioning Module Components	Annex A13
Engine Build Worksheets	Annex A14
Appendix	
Sequence IIIGA Test Procedure	Appendix X1
Sequence IIIGVS Test Procedure	Appendix X2
Sequence IIIGB Test Procedure	Appendix X3

2.1 ASTM Standards:¹

- D 86 Test Method for Distillation of Petroleum Products at Atmospheric Pressure
- D 130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D 235 Specification for Mineral Spirits (Petroleum Spirits) (Hydrocarbon Dry Cleaning Solvent)
- D 240 Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter
- D 323 Test Method for Vapor Pressure of Petroleum Products (Reid Method)
- D 381 Test Method for Gum Content in Fuels by Jet Evaporation
- D 445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)
- D 525 Test Method for Oxidation Stability of Gasoline (Induction Period Method)
- D 1319 Test Method for Hydrocarbon Types in Liquid Petroleum Products by Fluorescent Indicator Adsorption
- D 2699 Test Method for Research Octane Number of Spark-Ignition Engine Fuel
- D 2700 Test Method for Motor Octane Number of Spark-Ignition Engine Fuel
- D 3231 Test Method for Phosphorus in Gasoline
- D 3237 Test Method for Lead in Gasoline by Atomic Absorption Spectroscopy
- D 3244 Standard Practice for Utilization of Test Data to Determine Conformance with Specifications
- D 3338 Test Method for Estimation of Net Heat of Combustion of Aviation Fuels
- D 3343 Test Method for Estimation of Hydrogen Content of Aviation Fuels
- D 4052 Test Method for Density and Relative Density of Liquids by Digital Density Meter
- D 4175 Terminology Relating to Petroleum, Petroleum Products, and Lubricants
- D 4485 Specification for Performance of Engine Oils
- D 4684 Test Method for Determination of Yield Stress and Apparent Viscosity of Engine Oils at Low Temperature
- D 4815 Test Method for Determination of MTBE, ETBE, TAME, DIPE, tertiary-Amyl Alcohol and C₁ to C₄ Alcohols in Gasoline by Gas Chromatography

¹For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- D 5185 Test Method for Determination of Additive Elements, Wear Metals, and Contaminants in Used Lubricating Oils and Determination of Selected Elements in Base Oils by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES)
- D 5191 Test Method for Vapor Pressure of Petroleum Products (Mini Method)
- D 5293 Test Method for Apparent Viscosity of Engine Oils Between -5 and -35°C Using the Cold-Cranking Simulator
- D 5452 Test Method for Particulate Contamination in Aviation Fuels by Laboratory Filtration
- D 5453 Test Method for Determination of Total Sulfur in Light Hydrocarbons, Spark Ignition Engine Fuel, Diesel Engine Fuel, and Engine Oil by Ultraviolet Fluorescence
- D 5862 Test Method for Evaluation of Engine Oils in Two-Stroke Cycle Turbo-Supercharged 6V92TA Diesel Engine
- E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- E 191 Specification for Apparatus For Microdetermination of Carbon and Hydrogen in Organic and Organo-Metallic Compounds
- E 608/E 608M Specification for Mineral-Insulated, Metal-Sheathed Base Metal Thermocouples
- E 1119 Specification for Industrial Grade Ethylene Glycol
- IEEE/ASTM SI 10 Standard for Use of the International System of Units (SI): The Modern Metric System³

APPENDIX

X3. SEQUENCE IIIGB TEST PROCEDURE

X3.1 Overview

X3.1.1 The Sequence IIIGB supplement to the Sequence IIIG test was developed to generate used oil samples to measure the phosphorus retention of a test lubricant after 100 h of Sequence IIIG test operation. No parts ratings or measurements are required in the Sequence IIIGB test. A separate Sequence IIIGB Report Form Set is available from the TMC for reporting Sequence IIIGB test results. Do not use the Sequence IIIG Report Form Set to report Sequence IIIGB test results. The oil samples used for measurement of the phosphorus retention in the Sequence IIIGB test are the initial oil sample, removed from the engine following the initial run-in, and the end-of-test 100-h oil sample. The phosphorus retention calculation is:

$$\text{Phosphorus Retention} = (C_{a_i} / C_{a_{t100}}) \times (P_{t100} / P_i) \times 100$$

where C_{a_i} and P_i are analytical results from the initial oil sample and $C_{a_{t100}}$ and P_{t100} are analytical results from the end-of-test oil sample. Use Test Method D 5185 to measure calcium and phosphorus concentrations. For oils where calcium is not the highest concentration detergent metal, substitute the highest concentration detergent metal into the equation for calcium

X3.2 *Preparation of Apparatus* – Prepare the Sequence IIIGB test engine in the same manner as a Sequence IIIG or IIIGA test engine; except that the pre-test camshaft and lifter measurements are not required. No special preparations are required or permitted on test engines for Sequence IIIGB testing.

X3.3 Calibration

X3.3.1 There is no stand-alone calibration system for the Sequence IIIGB test. A stand that is calibrated for the Sequence IIIG is also calibrated for Sequence IIIGB testing. Conduct a Sequence IIIGB test simultaneously with each Sequence IIIG reference oil test.

X3.3.2 No special calibration of stand instrumentation is required for Sequence IIIGB testing.

X3.3.3 A Sequence IIIGB test counts as one run against the Sequence IIIG calibration period in which it was run. A test run as a combined Sequence IIIG, IIIGA, or IIIGB test counts as only one run against the calibration period.

X3.4 *Test Procedure* – The Sequence IIIG/B test can be conducted in one of two ways:

X3.4.1 *Stand-alone Sequence IIIGB Test* – If only a Sequence IIIGB test result is needed, conduct the test in the normal manner as detailed in Test Method D 7320 with the exception of ratings, wear measurements, or assessment of stuck rings. At the end of test, report all results as a stand-alone IIIGB test using the Sequence IIIGB Report Form Set.

X3.4.2 *Combined Sequence IIIG, IIIGA, IIIGB Sequence Test* – If Sequence IIIG, IIIGA, and IIIGB test results are desired on a non-reference oil, conduct the test in the normal manner as listed in Test Method D 7320, identify the test as a Combined Sequence IIIG, IIIGA, IIIGB on Report Form 1 and complete all forms in the standard Sequence IIIG, IIIGA, and IIIGB Report Form Sets including all ratings, measurements, and used oil analyses.

X3.5 *End-of-Test Oil Sample Testing*- The phosphorus and calcium elemental concentrations for all oil samples are to be reported in mg/kg as determined using Test Method D 5185. All samples, initial and end-of-test, are to be run sequentially, in duplicate, using the same calibration (i.e. as close in time as practical). Background correction, internal standard, and peristaltic pump are required. Use sample dilutions of at least 1:20. Once a dilution is established, use it for all samples from a test. Report the average of the two determinations as the final result. If the duplicate determinations are outside the repeatability calculations shown in Table 2 of Test Method D 5185, follow the procedure in Test Method D 3244 Section 6.2.

X3.6 *Quality Index* – Calculate quality index results for a Sequence IIIGB test in the same manner as for the Sequence IIIG.

X3.7 *Test Reporting* – Report Sequence IIIGB test results using the standard IIIGB Report Form Set, available from the TMC.

X3.8 *Precision and Bias* – The precision and bias of this test procedure for measuring phosphorus retention has yet to be determined.