

Test Monitoring Center

@ Carnegie Mellon University 6555 Penn Avenue, Pittsburgh, PA 15206, USA http://astmtmc.cmu.edu 412-365-1000

Sequence IIIG Information Letter 17-1 Sequence No. 45 April 26, 2017

ASTM consensus has not been obtained on this information letter. An appropriate ASTM ballot will be issued in order to achieve such consensus.

TO: Sequence III Mailing List

SUBJECT: Re-Use of Rocker Arm OHT3F-058-1

As a result of a recent Sequence III Surveillance Panel conference call, the panel agreed to allow the rocker arms, part number OHT3F-058-1, to be re-used as long as excessive wear or deformation is not present. This part number has been removed from Table A5.1 and is now shown in Table A5.2 and revised Tables A5.1 and A5.2 are attached. Cleaning requirements have been added to section 9.30. The change has been highlighted in red in Tables A5.1 and A5.2. Revisions to D7320-16a are attached and went into effect April 13, 2017.

Michael Raney

Michael P. Raney Engine Oil Test Development and Support GM Powertrain Materials Engineering

Frank m Faiber

Frank M. Farber Director ASTM Test Monitoring Center

Attachments

c: ftp://ftp.astmtmc.cmu.edu/docs/gas/sequenceiii/procedure_and_ils/IIIG/IL17-1_IIIG.pdf

Distribution: Electronic Mail

9.30 *Valve Train Loading*—Install the rocker arm pivot retainer and the precision roller rockers and torque the rocker arm pedestal bolts according to the Sequence IIIG Engine Assembly Manual, Section 6 Sheet 4. Rocker arm pivot retainers can be re-used as long as excessive wear or deformation is not present. When re-using rocker arms, clean the rocker arms using the procedure defined for the cylinder block in section 9.5.3.2, *If Using the Ultrasonic Cleaner Parts Washer, Parts (1) through (6).* After cleaning, soak the rocker arms in EF-411 for a minimum of 1 h prior to installation.

| Part Description Part Number | | |
|---------------------------------------------------------------|-----------------|--|
| Arm, Rocker with Pivot Bearing | OHT3F-058-1 | |
| BEARING, KIT, ENGINE | OHT3F-042-2 | |
| KIT INCLUDES: | | |
| BEARING, CONNECTING ROD, KIT, UPPER AND LOWER, OH-106 ASSY | 3F042-01 | |
| MAIN BEARING KIT, OH101 ASSY, INCLUDES: | 3F042-02 | |
| Bearing, Balance Shaft Front (part of 24502388) | SKF6205-2ZNRJEM | |
| BEARING, MAIN, LOWER, #1 AND 3 | OH-102 | |
| BEARING, MAIN, LOWER, #4 | OH-103 | |
| BEARING, MAIN, LOWER, FLANGE, #2 | OH-104 | |
| BEARING, MAIN, UPPER, FLANGE, #2 | OH-105 | |
| BEARING, CAM BUSHING, POSITIONS 1 & 4 | 3F028-09 | |
| BEARING, CAM BUSHING, POSITIONS 2 & 3 | 3F028-10 | |
| Bolt, Camshaft Sp rocket | 24501366 | |
| Bolt, Cylinder Head, Long | 25527831 | |
| Bolt, Cylinder Head, Short | 25533811 | |
| Bolt, Flywheel | 24505092 | |
| Bolt, Main Cap | 24503056 | |
| Bolt, Main Cap, Side | 24505576 | |
| Bolt, Rear Cover Housing | 24503970 | |
| Bolt, Rocker Arm, Special Test | 3F-058-02 | |
| Bolt/Screw, Thrust Plate retainer | 25519242 | |
| Camshaft, Special Test, including Manganese-phosphate coating | OHT3F-008-8 | |
| Cap, Valve Spring Retainer | 24502257 | |
| Chain, Timing | 24504668 | |
| Clip, Retainer, Piston Pin | OHT3F-012-1 | |
| | | |

TABLE A5.1 Parts to be Replaced Every Test

| Part Description | Part Number |
|------------------------------------------------------|------------------------|
| COOLER, OIL, NICKEL PLATED, BYPASS CLOSED | OHT3F-030-2 |
| Damper, Timing Chain (includes bolt, retaining ring) | 24503893 |
| FILTER, PRO TEC | OHT3F-057-3 |
| Gasket kit, Intake Manifold lower | 89017816 |
| Gasket, Cylinder Head, left | 24503802 |
| Gasket, Cylinder Head, right | 24503801 |
| Gasket, Front Cover | 12587003 |
| Gasket, Oil Filter Adapter | 25534742 |
| Gasket, Oil Pan | OHT3G-093-1 |
| Gasket, Oil Pan | OHT3G-093-2 |
| Gasket, Oil Suction Tube | 24501259 or 12581570 |
| Gasket, Rear Cover Housing | 24507388 |
| Gasket, Rocker Cover | 25532619 |
| Gasket, Water Outlet | 24502433 |
| Gasket, Water Pump | 24501565 |
| Head, Cylinder | 24502260B or 24502260S |
| Key, Camshaft Sprocket | 24500618 |
| Key, Valve Stem Keeper | 10166345 |
| Lifter, Test ACI w/Flat (25338738A) | OHT3F-029-3 |
| PISTON, TEST, RUNS 1 & 2, GRADE 12 | OHT3F-053-1 |
| PISTON, TEST, RUNS 3 & 4, GRADE 34 | OHT3F-054-1 |
| PISTON, TEST, RUNS 5 & 6, GRADE 56 | OHT3F-055-1 |
| PLATE, CAMSHAFT THRUST, .1520 in. THICKNESS | OHT3F-011-2 |
| Plug, Engine Block Core Hole | 24500867 |
| Plug, Cylinder Head Cup | 24502262 |
| Plug, Engine Block, Oil Gallery | 3835577 |
| Plug, Ignition Spark | NGK TR-6 |
| Plunger, Oil Relief | 25530949 |
| PUSHROD, SPECIAL LENGTH, PKG. OF 12 | OHT3F-007-1 |
| RETAINER CLIP, PISTON PIN PKG. OF 12 | OHT3F-012-1 |
| 1 EA. RING, PISTON, RUN 1, ENGINE SET | OHT3F-050-RUN1 |
| 1 EA. RING, PISTON, RUN 2, ENGINE SET | OHT3F-050-RUN2 |
| 1 EA. RING, PISTON, RUN 3, ENGINE SET | OHT3F-051-RUN3 |
| 1 EA. RING, PISTON, RUN 4, ENGINE SET | OHT3F-051-RUN4 |
| 1 EA. RING, PISTON, RUN 5, ENGINE SET | OHT3F-052-RUN5 |
| 1 EA. RING, PISTON, RUN 6, ENGINE SET | OHT3F 052 RUN6 |
| ROCKER ARM ASSEMBLY (Includes: 3F058-02) | OHT3F-058-1 |
| Rod, Connecting (powdered metal) | 12593374 |
| Seal, Crankshaft Front Oil (24504098) | OHT3G-092-1 |
| Seal, Crankshaft Rear Oil (25534760) | OHT3G-091-1 |
| SEAL, EXHAUST VALVE STEM | OHT3F-061-1 |
| SEAL, INTAKE VALVE STEM | OHT3F-060-1 |
| Spring, Oil Relief Valve | 1262505 |
| SPRING, VALVE Special Test (COLOR CODE PINK) | OHT3G-059-1 |
| Sprocket, Camshaft | 24505306 |
| Valve, Exhaust (STD) | 12579949 |
| Valve, Intake (STD) | 12569550 |

TABLE A5.2 Parts to be Replaced As Needed

| | Part Description |
|------------------------------|------------------|
| ADAPTER BLOWBY BREATHER TUBE | |

Part Number

ADAPTER, BLOWBY BREATHER TUBE

OHT3F-040-1

| Part Description | Part Number |
|----------------------------------------------------------|-------------------------|
| ADAPTER, OIL FILTER | OHT3F-035-1 |
| Adapter, Oil Filter, with External Bypass | OHT3F-080-1 |
| Adapter, Throttle Body, Air Inlet | OHT3F-001-2 |
| Balancer, Harmonic | 12563267 |
| Bearing, Balance Shaft Front (part of 24502388) | SKF6205-2ZNRJEM |
| Block, Engine Assembly | 24502286 |
| Bolt, Connecting Rod | 11610158 |
| Bolt, Counter Balance Gear | 24501367 |
| Bolt, Counter Balance Shaft Retainer | 24500055 |
| Bolt, Engine Front Cover | 24504712 |
| Bolt, Harmonic Balancer | 24504736 |
| Bolt, Lower Intake | 9440227 |
| Bolt, Oil Filter Adapter | 24504713 |
| Bolt, Oil Pan | 1160052 |
| Bolt, Oil Suction Tube | 24505570 |
| Bolt, Rear Cover Housing | 11518075 |
| Bolt, Rocker Cover | 24502164 |
| Bolt, Screw Camshaft Sensor | 25526395 |
| Bolt, Screw, Oil Gearotor, Cover | 25519242 |
| Bolt, Stud Type, Front Cover & Crankshaft Sensor (long) | 24504718 |
| Bolt, Stud Type, Front Cover & Crankshaft Sensor (short) | 24504717 |
| Bolt, Upper Intake Long | 24505205 |
| Bolt, Upper Intake Short | 24506498 |
| Bolt, Upper Intake, Stud | 24502453 |
| BRACKET, BREATHER TUBE | OHT3F-041-1 |
| BREATHER TUBE, S.S. MATERIAL | OHT3F-075-1 |
| Bushing, Balance Shaft Rear | 24503193 |
| BUSHING, ROCKER COVER | OHT3F-028-1 |
| BUSHING, ROCKER COVER | OHT3F-028-2 |
| Coil, Ignition | 10472401 or 89056799 |
| - | OHT3F-039-2 |
| CONNECTOR, MODIFIED FOR LENGTH, GM PN 24502883 | OHT3G-085-1 |
| | |
| COVER, Rear, crankshaft rear seal housing | OHT3G-088-1 25521935 |
| Cover, Oil Gearotor | 12590366 |
| Cover, Rocker Arm Valve Cover Left Side Plastic | |
| Crankshaft | 24502168 |
| | 24502260S |
| | OHT3G-064-1 |
| | OHT3F-043-1 |
| FLYWHEEL, MANUAL, MODIFIED P.N. 24503285 | OHT3F-020-2 |
| GASKET, EXHAUST, END PLATE | OHT3F-009-1 |
| GASKET, EXHAUST, FLANGE, METAL | OHT3F-018-1 |
| Gasket, Manifold, Upper Intake | 89017556 |
| GASKET, OIL COOLER, PKG. OF 50 | OHT3F-074-1 |
| GASKET, OIL FILTER, PKG. OF 50 | OHT3F-062-1 |
| Gear, Balanceshaft Drive | 24504792 |
| Gear, Balanceshaft Driven | 24503524 |
| Gear, Counter Balance Drive | 24504792 |
| Gear, Counter Balance Shaft | 24503524 |
| Grommet, Rocker Arm Valve cover bolt | 25534749 |
| HARNESS, COIL PACK SEGMENT | 3F022-2 |
| HARNESS, FUEL INJECTOR SEGMENT | 3F022-1 |

| Part Description | Part Number |
|---------------------------------------------------------------|----------------------|
| HARNESS, WIRING, DYNO W/ OHT3F-056-1 SENSOR | OHT3F-022-1 |
| HOUSING, ASSEMBLY, BYPASS VALVE | OHT3F-084-1 |
| njector, Fuel | 17120601 |
| Key, Crankshaft | 12563282 |
| Magnet, Camshaft Position Sensor | 10456195 |
| MANIFOLD, CAST IRON | OHT3F-003-0 |
| MANIFOLD, EXHAUST, WATER COOLED ASSY (ONE BANK) | OHT3F-003-1 |
| ASSEMBLY INCLUDES: | |
| 1 EA. RUNNER, EXHAUST MANIFOLD | OHT3F-004-1 |
| 1 EA. PLATE, REAR, EXHAUST MANIFOLD | OHT3F-005-1 |
| 1 EA. ELBOW, EXHAUST, MODIFIED | OHT3F-005A-1 |
| 1 EA. PLATE, FRONT, EXHAUST MANIFOLD | OHT3F-006-1 |
| 2 EA. GASKET, EXHAUST, END PLATE | OHT3F-009-1 |
| 1 EA. GASKET, EXHAUST, FLANGE, METAL | OHT3F-018-1 |
| Manifold, Lower Intake | 24508923 |
| Manifold, Upper Intake | 89017272 |
| METER, BLOWBY | RX-116169-A1 REV N |
| Vodule, Coil Pack | 12617924 |
| MOUNT FRONT ENGINE W/ BOLT PATTERN FOR COIL PACK | OHT3F-026-1 |
| MOUNT, REAR ENGINE HOUSING W/AIR STARTER, MUFFLER & SHIM PACK | OHT3F-025-1 |
| ASSEMBLY INCLUDES: | 011101-020-1 |
| STARTER, AIR | 3F025-03 |
| | |
| MUFFLER, STARTER, AIR | 3F025-04 |
| SHIM PACK, STARTER, AIR | 3F025-05 |
| MUFFLER, STARTER, AIR | 3F025-04 |
| Nut, Throttle Body Fuel Rail Retainer | 3530297 |
| Nut, Throttle body Retainer | 3530297 |
| DIL FILTER HOUSING ASSEMBLY, NO BYPASS, IMPREGNATED | OHT3G-080-1 |
| | OHT3F-034-1 |
| PAN, IIIF TEST, NICKEL PLATED | OHT3F-073-1 |
| PCM, SPECIAL | OHT3F-021-1 |
| PCV, DUMMY | OHT3F-002-1 |
| Pin, Cylinder Head Locating | 25536320 |
| Pin, Front Cover Lower | 25536323 |
| Pin, Front Cover Upper | 25536323 |
| PIN, PISTON WRIST, PKG. OF 6 | OHT3F-014-1 |
| PLATE, EGR BLOCKOFF | OHT3F-024-1 |
| PLATE, FRONT, EXHAUST MANIFOLD | OHT3F-006-1 |
| PLATE, REAR, EXHAUST MANIFOLD | OHT3F-005-1 |
| PLATE, WATER PUMP HOUSING | OHT3F-031-1 |
| Plug, Auto Hex, Socket, (Main Oil Gallery Block Off) | 444777 |
| PLUG, DIP STICK | OHT3F-065-1 |
| PLUG, DRAIN, MODIFIED | OHT3F-063-1 |
| Pump, Oil, Gearoter Set | 24505433 |
| Rail, Fuel Injector | 12587077 |
| REAMER, DIP STICK AND DIP STICK HOLE PLUG | OHT3F-071-1 |
| Regulator, Fuel Pressure, on Rail | 89017530 or 89060416 |
| Retainer, Counter Balance, Timing Chain Oiler | 24500374 |
| Retainer, Rocker arm (replace after 6 tests) | 24502278 |
| ROCKER ARM ASSEMBLY (Includes: 3F058-02) | OHT3F-058-1 |
| RUNNER, EXHAUST MANIFOLD | OHT3F-004-1 |
| Screen, Oil pump (w/suction pipe) | 24505569 |

| Part Description | Part Number |
|------------------------------------------------|----------------------|
| Seal, Ignition Coil | 1989579 |
| Seal, oil pan drain plug (o ring) | 3536966 |
| Sensor, Camshaft Position | 10456148 |
| Sensor, Crankshaft Position | 10456161 |
| Sensor, MAF | 19112543 or 19179715 |
| SENSOR, MODIFIED COOLANT TEMPERATURE | OHT3F-056-1 |
| Shaft Assembly, Counter Balance | 24506557 |
| Shield, Crankshaft Position Sensor | 24506440 or 12591982 |
| SHIM PACK, STARTER, AIR | 3F025-05 |
| SHIM, STEEL, 0.127 mm THICK, 10 PER PKG. | OHT3F-072-005 |
| SHIM, STEEL, 0.254 mm THICK, 10 PER PKG. | OHT3F-072-010 |
| SHIM, STEEL, 0.381 mm THICK, 10 PER PKG. | OHT3F-072-015 |
| SHIM, STEEL, 0.508 mm THICK, 10 PER PKG. | OHT3F-072-020 |
| SHIM, STEEL, 0.787 mm THICK, 10 PER PKG. | OHT3F-072-031 |
| SLEEVE, VALVE STEM PROTECTORS (PKG. OF 100) | OHT3F-070-1 |
| SPROCKET, CRANKSHAFT, SPECIAL 2 PC | OHT3F-036-1 |
| STARTER, AIR | 3F025-03 |
| Stud, front cover (2) | 24504717 |
| Stud, front cover (2) | 24504718 |
| Support, throttle body | 24504697 |
| Throttle Body (2 Bolt Mass Air Flow Sensor) | 24507235 |
| TOOL, CAMSHAFT BUSHING INSTALLATION | OHT3F-019-2 |
| TOOL, OIL PUMP PRIMER | OHT3F-038-1 |
| Tube, throttle body to fuel pressure regulator | 24505671 |