



Test Monitoring Center

@ Carnegie Mellon University
6555 Penn Avenue, Pittsburgh, PA 15206, USA

<http://astmtmc.cmu.edu>
412-365-1000

Sequence VG Information Letter 14-1
Sequence No. 38
January 7, 2014

ASTM consensus has not been obtained on this information letter. An appropriate ASTM ballot will be issued in order to achieve such consensus.

TO: Sequence VG Mailing List

SUBJECT: Changing Fuel Batches

As a result of a recent electronic ballot, the Sequence VG Surveillance Panel approved a change to define the procedure on how to switch from one fuel batch to another. Section 8.2.4.3 has been added to describe when and how to move the new fuel batch into tank(s) containing a previous fuel batch. These changes are effective October 18, 2013.

Ron Romano
FCSD, Service Product Development, SEO
Ford Motor Company

Frank M. Farber
Director
ASTM Test Monitoring Center

Attachment

c: ftp://ftp.astmtmc.cmu.edu/docs/gas/sequencev/procedure_and_ils/vgil14-1-38.pdf

Distribution: Email

(Revises Test Method D6593-13b, as amended by information letter 13-02)

8.2.4.3 Add fuel from a new batch to a laboratory's fuel tank when the current fuel level is below 10 % of the final fuel (new and previous) mixture's total volume.