



Address 100 Barr Harbor Drive
PO Box C700
W. Conshohocken, PA
19428-2959 | USA

Phone 610.832.9500
Fax 610.832.9666
Web www.astm.org

Committee D02 on PETROLEUM PRODUCTS AND LUBRICANTS

Chairman: KENNETH O. HENDERSON, Cannon Instrument Co., 2139 High Tech Road, State College, PA 16803, (814) 353-8000, Fax: (814) 353-8007, e-mail: kenohenderson@worldnet.att.net
First Vice-Chairman: BEN R. BONAZZA, TI Group Automotive Systems, Caro Research Center, 326 Green Street, Caro, MI, 48723 (989) 673-8181 ext. 227, Fax: (989) 673-3241, e-mail: bbonazza@us.tiauto.com
Second Vice-Chairman: JANET L. LANE, ExxonMobil Research & Engrg., 600 Billingsport Rd, Paulsboro, NJ 08066-0480 (856) 224-3302, Fax: (856) 224-3616, e-mail: janet.l.lane@exxonmobil.com
First Secretary: RALPH A. CHERRILLO, Shell Global Solutions (US) Inc., Westhollow Tech Ctr., 3333 Highway 6 South, Houston, TX 77082 (281) 544-8789, Fax: (281) 544-8150, e-mail: ralph.cherrillo@shell.com
Second Secretary: MICHAEL A. COLLIER, Petroleum Analyzer Co. LP, PO Box 206, Wilmington, IL 60481, (815) 458-0216, Fax: (815) 458-0217, e-mail: macvarlen@aol.com
Staff Manager: DAVID R. BRADLEY, (610) 832-9681, Fax: (610) 832-9668, e-mail: dbradley@astm.org

Issued: September 15, 2015
Reply to: Dan Worcester
Southwest Research Institute
6220 Culebra Rd.
San Antonio, TX 78238
Phone: 210.522.2405
Email: dworcester@swri.org

These are the unapproved minutes of the 09.15.2015 Sequence VI Surveillance Panel call.

This document is not an ASTM standard; it is under consideration within an ASTM technical committee but has not received all approvals required to become an ASTM standard. It shall not be reproduced or circulated or quoted, in whole or in part, outside of ASTM committee activities except with the approval of the chairman of the committee having jurisdiction and the president of the society. Copyright ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

The meeting was called to order at 8:00 AM Central Time by Chairman Nathan Moles.

Agenda

The Agenda is the included as **Attachment 1**.

1.0 Roll Call

The Attendance list is **Attachment 2**.

2.0 Approval of minutes

- 2.1 Approval of the minutes of the 09.01.2015 meeting.

MOTION: Approve the minutes from the 09.01.2015 conference call.

[Dan Worcester, Nathan Moles, second] Approved unanimous.

3.0 Action Item Review

- 3.1 OHT to provide update on current VIE inventory and service engine order. –OHT
There are 58 of the original order of engines remaining, and 144 service engines.
- 3.2 Labs reported VID engine inventory and expected depletion date of VID engines.
-Expected life of engines range from 2016 Q1 to 2018
Lab1: 2 engines
Lab2: 2 engines
Lab3: 3 engines
Lab4: 1 engines This will be an on-going effort.

4.0 Old Business

- 4.1 List of items to be reviewed after the Precision Matrix
Do we really need to run three RO tests to establish the new engine for LTMS?
Discussion of reducing the new reference requirement to two oils, then a third oil run after a defined number of candidates.
Discussion of using FEI 2 and FEI Sum for references to match candidate pass/fail criteria.
Discussion of evaluating 80/20 ratio of BL before to after for FEI 1 and 10/90 for FEI 2.
Should the acceptance bands value of 1.96 be rounded up? Due to the rounding on FEI 1 and 2 the actual pass limit is 1.91 and 1.92.
-SP chair and test sponsor to investigate what is needed to establish VID equivalent limits for VIE.
This will be an on-going effort.
- 4.2 Update on progress of 5W-30 Tech1 in VIE testing. –Labs
-FEI1/2 = 1.09/1.05 @ 349 hours This test exceeded the procedure limit of -0.2 to 0.4 BLB Delta.
- FEI1/2 = 0.29/0.37 @ 2059 hours This test was later declared invalid.
-FEI1/2 = 0.79/1.25 @ 592 hours This was a Lubrizol run.
- 4.3 Engine hours needs to be addressed in the precision matrix and there is concern in the industry that the current design does not adequately address this. Two design approaches were selected for the stats group to investigate further. –Jo Martinez
There are several versions that were considered. See Attachment 3. There were more slides for matrix variations. AOAP has approved the VIE Precision Matrix. The BOI/VGRA will not be in the initial matrix design. There were 3 options considered without BOI/VGRA. There were concerns of engine response with as much as 2900 hours on a test engine. There do need to be two engines at SwRI and IAR to help detect engine differences. One of each of those engines will have high hours.

MOTION: Proceed with the Precision Matrix using version 2.5ai.
[Nathan Moles, William Buscher, second] 13 yes, 0 no, 2 waive.

4.4 Discussion on third reference oil for precision matrix (replacement for 1011). 5W-30 version of Tech1 was recommended by SP.
ILSAC discussed Tech 1 oil in 5W-30 viscosity as a reference oil for the Seq VIE precision matrix and ILSAC agreed it's the best replacement for the 0W-16 Tech 1. We recommend the VIE SP include 5W-30 Tech 1 in the PM.
There was discussion on whether to use reference oil blend 542-2 or wait for 542-3. There is enough 542-2 for both the VIE and VIF matrices and the resultant reference period after stand calibrations. It will be about a month before the 5W-30 Tech 1 is available.

4.5 Discussion, what batch of 542 should be used for PM and VIF tests?
Current TMC inventory of 542-2 (~550 gallons, 90 - tests)

MOTION: Use reference oil blend 542-2 for the VIE Precision Matrix.
[Dave Glaenzer, Rich Grundza, second] 13 yes, 0 no, 2 waive.

NOTE: Hirano-san agrees that 542-2 will be used for the VIF Matrix as well.

4.6 Request that the Sequence VI Surveillance Panel update Section 6.6.5.5 of ASTM D7589, the Sequence VID procedure as well as Sections 6.6.5.5 of the August 24, 2015 Draft of the Sequence VIE procedure to include the alternate part number (attachments). –Dave Glaenzer **See Attachments 4 and 5.** The difference in the parts is a mounting bracket on the recommended change part number.

MOTION: Update Section 6.6.5.5 of ASTM D7589, the Sequence VID procedure as well as Sections 6.6.5.5 of the August 24, 2015 Draft of the Sequence VIE procedure with the new heat exchanger part number. 5-694-10-020-002 is an acceptable alternate to 5-686-04-020-002.

[Dave Glaenzer, Nathan Moles, second] 14 yes, 0 no, 2 waive.

4.5 Update from task force, to investigate alternative test procedure Sequence “VIF” that would improve 0W-16. – Dan Worcester/Satoshi Hirano **Nathan did the Task Force presentation at the AOAP meeting. There was clear direction to continue with a VIF version of the fuel economy test from AOAP and PCEOCP.**

4.6 Update from task force to investigate option to prolong usable life of the available VIE engines. –Adrian Alfonso/Bill Buscher **There will be a kick off meeting the Thursday morning, 09.17.2015. An agenda with Scope and Objectives will be available. The meeting will be at 8:00 AM so Hirano-san can attend.**

5.0 New Business

5.1 None

6.0 Next Meeting

These meeting will now occur weekly to develop and run the Precision Matrix. Each Tuesday at 9:00 AM Eastern, 8:00 AM Central times.

The meeting adjourned at 8:42 AM.

Sequence VI Surveillance Panel Conference Call Agenda September 15 @ 9:00-10:00AM EST

Call-in information is included below:

Call-in Number: 866-528-2256
Conference Code: 3744024

1.0) Roll Call

Do we have any membership changes or additions?

2.0) Approval of minutes

2.1 Approve the minutes from the September 1, 2015 Sequence VI Surveillance Panel.

<ftp://ftp.astmtmc.cmu.edu/docs/gas/sequencevi/minutes/VIMinutes20150901%20Conference%20call.pdf>

3.0) Action Item Review

3.1 OHT to provide update on current VIE inventory and service engine order. –OHT

3.2 Update of VID engine inventory and expected depletion date of VID engines.

-Expected life of engines range from 2016 Q1

Lab1: 2 engines

Lab2: 2 engines

Lab3: 3 engines

Lab4: 1 engines

4.) Old Business

4.1 List of items to be reviewed after the Precision Matrix

-Do we really need to run three RO tests to establish the new engine for LTMS?

-Discussion of reducing the new reference requirement to two oils, then a third oil run after a defined number of candidates.

- Discussion of using FEI 2 and FEI Sum for references to match candidate pass/fail criteria.
- Discussion of evaluating 80/20 ratio of BL before to after for FEI 1 and 10/90 for FEI 2.
- Should the acceptance bands value of 1.96 be rounded up? Due to the rounding on FEI 1 and 2 the actual pass limit is 1.91 and 1.92.
- SP chair and test sponsor to investigate what is needed to establish VID equivalent limits for VIE

4.2 Update on progress of 5W-30 Tech1 in VIE testing. –Labs
-FEI1/2 = 1.09/1.05 @ 349 hours This test exceeded the procedure limit of -0.2 to 0.4 BLB Delta.
- FEI1/2 = 0.29/0.37 @ 2059 hours This test was later declared invalid.
-FEI1/2 = 0.79/1.25 @ 592 hours

4.3 Engine hours needs to be addressed in the precision matrix and there is concern in the industry that the current design does not adequately address this. Two design approaches were selected for the stats group to investigate further (presentation). –Jo Martinez

4.4 Discussion on third reference oil for precision matrix (replacement for 1011). 5W-30 version of Tech1 was recommended by SP.
ILSAC discussed Tech 1 oil in 5W-30 viscosity as a reference oil for the Seq VIE precision matrix and ILSAC agreed it's the best replacement for the 0W-16 Tech 1. We recommend the VIE SP include 5W-30 Tech 1 in the PM.

4.5 Discussion, what batch of 542 should be used for PM and VIF tests?
Current TMC inventory of 542-2 (~550 gallons, 90 - tests)

4.6 Request that the Sequence VI Surveillance Panel update Section 6.6.5.5 of ASTM D7589, the Sequence VID procedure as well as Sections 6.6.5.5 of the August 24, 2015 Draft of the Sequence VIE procedure to include the alternate part number (attachments). –Dave Glaenger

4.7 Update from task force, to investigate alternative test procedure Sequence “VIF” that would improve 0W-16. – Dan Worcester/Satoshi Hirano

4.8 Update from task force to investigate option to prolong usable life of the available VIE engines. –Adrian Alfonso/Bill Buscher

5.) New Business

5.1 None

6.) Next Meeting

Next Tuesday (reoccurring weekly meeting)

7.) Meeting Adjourned

ASTM SEQUENCE VI

Name	Address	Phone/Fax/Email	Attendance
Adrian Alfonso Voting Member	Intertek Automotive Research	Phone: (210) 838-0431 adrian.alfonso@intertek.com	ATTEND
Jason Bowden Voting Member	OH Technologies	Phone: (440) 354-7007 jhbowden@ohtech.com	ATTEND
Timothy Caudill Voting Member	Ashland	Phone: (606) 329-5708 Tlcaudill@ashland.com	ATTEND
Tim Cushing Voting Member	General Motors	Phone: (248) 881-3518 timothy.cushing@gm.com	ATTEND
David Glaenzer Voting Member	Afton	Phone: (804) 788-5214 Dave.Glaenzer@aftonchemical.com	ATTEND
Rich Grundza Voting Member	ASTM TMC	Phone: (412) 365-1034 reg@astmtmc.cmu.edu	ATTEND
Jeff Hsu Voting Member	Shell	Phone: (832) 419-3482 j.hsu@shell.com	ATTEND
Tracey King Voting Member	Haltermann	Phone: tking@jhaltermann.com	ATTEND
Teri Kowalski Voting Member	Toyota	Phone: (734) 995-4032 teri.kowalski@tema.toyota.com	
Dan Lanctot Voting Member	TEI	dlanctot@tei-net.com Phone: (210) 690-1958	ATTEND
Brian Marks Voting Member	BP Castrol	Phone: (973)686-3325 Brian.Marks@bp.com	ATTEND
Nathaniel Moles Voting Member	Lubrizol	Phone: (440) 347-4472 Nathaniel.Moles@Lubrizol.com	ATTEND
Mark Mosher Voting Member	ExxonMobil	Phone: (856) 224-2132 mark_r_mosher@exxonmobil.com	
Andy Ritchie Voting Member	Infineum	Phone: (908) 474-2097 Andrew.Ritchie@infineum.com	
Ron Romano Voting Member	Ford Motor	Phone: (313) 845-4068 rromano@ford.com	
Kaustav Sinha Voting Member	Chevron Oronite	Phone: (713) 432-6642 LFNQ@chevron.com	
Haiying Tang Voting Member	Chrysler	Phone: (248) 512-0593 HT146@Chrysler.com	
Dan Worcester Voting Member	Southwest Research Institute	Phone: (210) 522-2405 dan.worcester@swri.org	ATTEND

ASTM SEQUENCE VI

Name	Address	Phone/Fax/Email	Attendance
Ed Altman	ed.altman@aftonchemical.com	Afton	
Bob Campbell	Bob.Campbell@aftonchemical.com	Afton	
Todd Dvorak	todd.dvorak@aftonchemical.com	Afton	
Christian Porter	Christian.porter@aftonchemical.com	Afton	
Terry Hoffman	Terry.Hoffman@aftonchemical.com	Afton	
Jeremy Styer	Jeremy.styer@aftonchemical.com	Afton	
Greg Guinther	greg.guinther@aftonchemical.com	Afton	
Amol Savant	ACSavant@ashland.com	Ashland	ATTEND
Don Smolenski	donald.j.smolenski@gm.com	Evonik	ATTEND
Clifford Salvesen	clifford.r.salvesen@exxonmobil.com	ExxonMobil	ATTEND
Doyle Boese	Doyle.boese@infineum.com Phone: (908) 474-3176	Infineum	ATTEND
Mike McMillan	mmcmillan123@comcast.net	Infineum	ATTEND
Gordon Farnsworth	gordon.farnsworth@infineum.com	Infineum	ATTEND
Mike Warholic	Michael.warholic@Infineum.com Phone: 908.474.2065	Infineum	
Jordan Pastor	Jordan.pastor@Infineum.com Phone: (313) 348-3120	Infineum	
Bob Olree	olree@netzero.net	Intertek	
Addison Schweitzer	addison.schweitzer@intertek.com	Intertek	
William Buscher	william.buscher@intertek.com	Intertek	ATTEND
Al Lopez	Al.Lopez@intertek.com	Intertek	
Charlie Leverett	charlie.leverett@intertek.com Phone: (210) 647-9422	Intertek	
Angela Willis	angela.p.willis@gm.com	GM	
Jeff Kettman	Jeff.kettman@gm.com	GM	
Mike Raney	Michael.p.raney@gm.com Phone: (248) 408-5384	GM	
Andy Buczynsky	andrew.buczynsky@gm.com	GM	
Bruce Matthews	bruce.matthews@gm.com	GM	
Jerry Brys	Jerome.brys@lubrizol.com	Lubrizol	ATTEND
Jessica Buchanan	Jessica.Buchanan@Lubrizol.com	Lubrizol	
Michael Conrad	Michael.Conrad@Lubrizol.com	Lubrizol	ATTEND
Joe Gleason	Jog1@lubrizol.com	Lubrizol	
G. Szappanos	George.Szappanos@lubrizol.com	Lubrizol	
Kevin O'Malley	Kevin.OMalley@lubrizol.com	Lubrizol	ATTEND
Scott Rajala	srajala@ILAcorp.com	Idemitsu	ATTEND

GF-6 VIE PRECISION MATRIX

Statisticians Task Force

Sep. 10, 2015

GF-6 PM Design Statisticians Task Force

- Doyle Boese, Infineum
- Kevin O'Malley, Lubrizol
- Todd Dvorak, Afton Chemical
- Jo Martinez, Chevron Oronite
- Ricardo Affinito, Chevron Oronite
- Arthur Andrews, Exxon Mobil
- Martin Chadwick, Intertek
- Eric Liu, SwRI
- Rich Grundza, TMC

Objective:

- Modify Approach 2.5 design presented on 8/25/2015 in such a way that maximum engine hours will be between 2000 to 2500.
- Matrix Oils
 - 542-2; 0w20
 - 1010-1; 5w20
 - Tech 1; 5w30

Design Assumptions:

- 8 stands; 6 labs
- Funding for 53 matrix tests (Most likely 50 tests per MOA)
- Funding for 12 BOI/VGRA matrix tests (Design still applicable without BOI/VGRA runs)
- BOI/VGRA oils can be interspersed within the PM oils if the BOI/VGRA oils have the same DI as the PM oils or proof is provided that there's no carry over from BOI/VGRA oils
- Step 1 Run Order will be finalized when we know more about the BOI/VGRA oils
- Step 2 Run Order will be determined once the health of the engines are identified after Step 1 tests

	Planned Test Stands						Stands	TEST Cost	GF-6 Precision Matrix ONLY			
	Afton	LZ	XOM	Ashland	IAR	SwRI			Total Runs	Cal Runs	Cal \$'s	Total \$'s
Chrysler Oxid. (Seq. IIIH Rep)	1	1	None	1	2	2	7	\$57,250	28	14	\$801,500	\$1,603,000
Sequence IVB (Toyota)	None	1	None	None	2	2	5	\$49,250	20	10	\$492,500	\$985,000
Sequence V-V8	1	1	None	1	2	2	7	\$63,000	28	14	\$882,000	\$1,764,000
LSPI (Ford)	None	1	None	None	2	2	5	\$14,250	20	10	\$142,500	\$285,000
Chain Wear Test (Ford)	1	None	None	1	2	2	6	\$45,750	24	12	\$549,000	\$1,098,000
Sequence VIE	1	1	1	1	2	2	8	\$32,750	53	24	\$786,000	\$1,735,750
											\$3,653,500	\$7,470,750

IAR and SwRI have 2 Stands for Each Test

Seq. IIIH, Seq. IVB, Seq. V, LSPI, Chain Wear are 4 Tests per Stand

Seq. VIE, 7 tests per stand for the first stand + 4 test per stand for the second.

Seq. IIIH, Seq. IVB, Seq. V, LSPI, Chain Wear have 2 Calibration Tests/Stand

Seq. VIE has 3 Calibration Tests/Stand

Test Funding - Total	\$7,470,750
Donated Tests - Total	\$3,653,500
Industry Funding MOA - Total	\$3,817,500
Actual Matrix Cost	\$3,817,250
Extra Funding	\$250

VIE Approach 2.5

- BOI/VGRA interspersed within matrix
- 2 engines run longer; 6 end earlier
- Maximum engine hours: 2750 (2950 if additional funding is available)
- Average engine hours: 1200

Run Order to be finalized:

Step	Run Order	SW1	SW2	IAR1	IAR2	LZ	Afton	Ashland	XOM	
	SOT Engine Hours	150	150	150	150	150	150	150	150	Engine Hrs
1	1	542-2	1010-1	5w30T1	542-2	5w30T1	1010-1	5w30T1	1010-1	350
	2	5w30T1	542-2	1010-1	1010-1	1010-1	542-2	542-2	5w30T1	550
	3	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	750
	4	BOI/VGRA	5w30T1	BOI/VGRA	5w30T1	BOI/VGRA	BOI/VGRA	BOI/VGRA	BOI/VGRA	950
	5	BOI/VGRA	1010-1	BOI/VGRA	542-2	BOI/VGRA	BOI/VGRA	BOI/VGRA	BOI/VGRA	1150
	6	1010-1	542-2	542-2	1010-1	542-2	5w30T1	1010-1	542-2	1350
2	7		5w30T1		1010-1					1550
	8		542-2		5w30T1					1750
	9		542-2		5w30T1					1950
	10		1010-1		542-2					2150
	11		5w30T1		5w30T1					2350
	12		542-2		5w30T1					2550
	13		1010-1		1010-1					2750
	14		5w30T1		1010-1					2950
	EOT Engine Hours	1350	2950	1350	2950	1350	1350	1350	1350	Total Runs
	Runs/Engine	6	14	6	14	6	6	6	6	64

VIE Approach 2.5a

- BOI/VGRA interspersed within matrix
- 3 engines run longer; 5 end earlier
- Maximum engine hours: 2350 (2550 if additional funding is available)
- Average engine hours: 1150

Run Order to be finalized:

Step	Run Order	SW1	SW2	IAR1	IAR2	LZ	Afton	Ashland	XOM	Engine Hrs
	SOT Engine Hours	150	150	150	150	150	150	150	150	
1	1	542-2	1010-1	5w30T1	542-2	5w30T1	1010-1	5w30T1	1010-1	350
	2	5w30T1	542-2	1010-1	1010-1	1010-1	542-2	542-2	5w30T1	550
	3	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	750
	4	BOI/VGRA	5w30T1	BOI/VGRA	5w30T1	BOI/VGRA	BOI/VGRA	BOI/VGRA	BOI/VGRA	950
	5	BOI/VGRA	1010-1	BOI/VGRA	542-2	BOI/VGRA	BOI/VGRA	BOI/VGRA	BOI/VGRA	1150
	6	1010-1	542-2	542-2	1010-1	542-2	5w30T1	1010-1	542-2	1350
2	7		5w30T1		1010-1	1010-1				1550
	8		542-2		5w30T1	5w30T1				1750
	9		542-2		5w30T1	1010-1				1950
	10		1010-1		542-2	542-2				2150
	11		5w30T1		5w30T1	1010-1				2350
	12		542-2		1010-1					2550
	EOT Engine Hours	1350	2550	1350	2550	2350	1350	1350	1350	Total Runs
	Runs/Engine	6	12	6	12	11	6	6	6	65

VIE Approach 2.5b

- BOI/VGRA interspersed within matrix
- 4 engines run longer; 4 end earlier
- Maximum engine hours: 2150 (2350 if additional funding is available)
- Average engine hours: 1100

Run Order to be finalized:

Step	Run Order	SW1	SW2	IAR1	IAR2	LZ	Afton	Ashland	XOM	
	SOT Engine Hours	150	150	150	150	150	150	150	150	Engine Hrs
1	1	542-2	1010-1	5w30T1	542-2	5w30T1	1010-1	5w30T1	1010-1	350
	2	5w30T1	542-2	1010-1	1010-1	1010-1	542-2	542-2	5w30T1	550
	3	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	750
	4	BOI/VGRA	5w30T1	BOI/VGRA	5w30T1	BOI/VGRA	BOI/VGRA	BOI/VGRA	BOI/VGRA	950
	5	BOI/VGRA	1010-1	BOI/VGRA	542-2	BOI/VGRA	BOI/VGRA	BOI/VGRA	BOI/VGRA	1150
	6	1010-1	542-2	542-2	1010-1	542-2	5w30T1	1010-1	542-2	1350
2	7		5w30T1		1010-1	1010-1	5w30T1			1550
	8		542-2		5w30T1	5w30T1	5w30T1			1750
	9		542-2		5w30T1	1010-1	542-2			1950
	10		1010-1		542-2					2150
	11		542-2		1010-1					2350
	EOT Engine Hours	1350	2350	1350	2350	1950	1950	1350	1350	Total Runs
	Runs/Engine	6	11	6	11	9	9	6	6	64

VIE Approach 2.5i

- 2 engines run longer; 6 end earlier
- Maximum engine hours: 2750 (2950 if additional funding is available)
- Average engine hours: 1200

Run Order to be finalized:

Step	Run Order	SW1	SW2	IAR1	IAR2	LZ	Afton	Ashland	XOM	
	SOT Engine Hours	150	150	150	150	150	150	150	150	Engine Hrs
1	1	542-2	1010-1	5w30T1	542-2	5w30T1	1010-1	5w30T1	1010-1	350
	2	5w30T1	542-2	1010-1	1010-1	1010-1	542-2	542-2	5w30T1	550
	3	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	750
	4	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	950
2	5		1010-1		542-2					1150
	6		542-2		1010-1					1350
	7		5w30T1		1010-1					1550
	8		542-2		5w30T1					1750
	9		542-2		5w30T1					1950
	10		1010-1		542-2					2150
	11		5w30T1		5w30T1					2350
	12		542-2		5w30T1					2550
	13		1010-1		1010-1					2750
	14		5w30T1		1010-1					2950
	EOT Engine Hours	950	2950	950	2950	950	950	950	950	Total Runs
	Runs/Engine	4	14	4	14	4	4	4	4	52

VIE Approach 2.5ai

- 3 engines run longer; 5 end earlier
- Maximum engine hours: 2150 (2350 if additional funding is available)
- Average engine hours: 1000

Run Order to be finalized:

Step	Run Order	SW1	SW2	IAR1	IAR2	LZ	Afton	Ashland	XOM	
	SOT Engine Hours	150	150	150	150	150	150	150	150	Engine Hrs
1	1	542-2	1010-1	5w30T1	542-2	5w30T1	1010-1	5w30T1	1010-1	350
	2	5w30T1	542-2	1010-1	1010-1	1010-1	542-2	542-2	5w30T1	550
	3	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	750
	4	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	950
2	5		1010-1		542-2	1010-1				1150
	6		542-2		1010-1	5w30T1				1350
	7		5w30T1		1010-1	1010-1				1550
	8		542-2		5w30T1	542-2				1750
	9		542-2		5w30T1	1010-1				1950
	10		5w30T1		542-2	5w30T1				2150
	11		542-2		1010-1					2350
	EOT Engine Hours	950	2350	950	2350	2150	950	950	950	Total Runs
	Runs/Engine	4	11	4	11	10	4	4	4	52

VIE Approach 2.5bi

- 4 engines run longer; 4 end earlier
- Maximum engine hours: 1950 (2150 if additional funding is available)
- Average engine hours: 1000

Run Order to be finalized:

Step	Run Order	SW1	SW2	IAR1	IAR2	LZ	Afton	Ashland	XOM	
	SOT Engine Hours	150	150	150	150	150	150	150	150	Engine Hrs
1	1	542-2	1010-1	5w30T1	542-2	5w30T1	1010-1	5w30T1	1010-1	350
	2	5w30T1	542-2	1010-1	1010-1	1010-1	542-2	542-2	5w30T1	550
	3	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	750
	4	1010-1	5w30T1	542-2	5w30T1	542-2	5w30T1	1010-1	542-2	950
2	5		1010-1		542-2	1010-1	5w30T1			1150
	6		542-2		1010-1	5w30T1	5w30T1			1350
	7		5w30T1		1010-1	1010-1	542-2			1550
	8		542-2		5w30T1	542-2	5w30T1			1750
	9		1010-1		542-2					1950
	10		542-2		1010-1					2150
	EOT Engine Hours	950	2150	950	2150	1750	1750	950	950	Total Runs
	Runs/Engine	4	10	4	10	8	8	4	4	52

Guidelines on Running the PM

1. If engine fails before the matrix finishes, move remaining tests to another matrix engine.
2. After all labs run the first 5-6 tests, reassess engine “health” at the labs to determine the engines that will run additional tests to reach higher engine hours.



Southgate Process Equipment, Inc.

87 Hickory Springs Industrial Drive

Canton, GA 30115

Phone: (770) 345-0010

Fax: (770) 345-4299

Email: sales@southgateprocess.com

**Part # 5-686-04-020-002,
Model BP410-20, Non ASME Code**

Xylem, Standard Xchange (Formally ITT Standard / American Standard)

Units have stainless steel plates with copper brazing.

2.8 - 22.5 sq. ft. of surface area.

Connection size 1" MPT's

Max 50 GPM

Greater Pressure Drop=Greater Performance

ASME Code, Low Cost ASME Code and Non Code Units

Units ship within 1-2 weeks after order is received.

Please contact us for better delivery.

Specifications

Model	BP410-20
Non Code/Code	Non ASME Code Stamped
Surface Area	5.6 ft ²
Max. GPM	50
Connections	1 Inch MPT
Min. Design Temp	-310 °F
Max. Design Temp	450 °F
Design Pressure	435 psig



Southgate Process Equipment, Inc.

87 Hickory Springs Industrial Drive

Canton, GA 30115

Phone: (770) 345-0010

Fax: (770) 345-4299

Email: sales@southgateprocess.com

**Part # 5-694-10-020-002, ITT / Xylem Standard Xchange
Hydronic Brazed Plate Heat Exchanger Model BP410-MT**

Xylem, Standard Xchange (Formally ITT Standard / American Standard)

Units have stainless steel plates with copper brazing.

2.8 - 22.5 sq. ft. of surface area.

Connection size 1" MPT's

Max 50 GPM

Greater Pressure Drop=Greater Performance

Units have mounting tabs

ASME Code, Low Cost ASME Code and Non Code Units

Units ship within 1-2 weeks after order is received.

Please contact us for better delivery.

Specifications

Model	BP410-20 MT
Non Code/Code	Non ASME Code Stamped
Surface Area	5.6 ft ²
Max. GPM	50
Connections	1 Inch MPT
Min. Design Temp	-310 °F
Max. Design Temp	450 °F
Design Pressure	435 psig