



## Test Monitoring Center

@ Carnegie Mellon University  
6555 Penn Avenue, Pittsburgh, PA 15206, USA

<http://astmtmc.cmu.edu>  
412-365-1000

Sequence VIE Information Letter 20-1  
Sequence Number 7  
February 3, 2020

TO: Sequence VI Surveillance Panel  
SUBJECT: Requirement for Changing Fuel Batches

During the January 16, 2020 Sequence VI Surveillance Panel Conference call, the panel agreed to add a requirement to add a new fuel batch only when the laboratory's fuel tank is below 10 % of the final fuel. As a result, section 7.2.3 has been added to define the new requirement.

These revised text and or section(s) have been highlighted in red and are effective January 16, 2020.

Aleise Gauer  
Materials Engineer – Fluids & Lubricants  
GM Global Propulsion Systems

Frank M. Farber  
Director  
ASTM Test Monitoring Center

Attachment

c: [http://www.astmtmc.cmu.edu/ftp/docs/gas/sequencevi/procedure\\_and\\_ils/VIE/il20-1\\_vie.pdf](http://www.astmtmc.cmu.edu/ftp/docs/gas/sequencevi/procedure_and_ils/VIE/il20-1_vie.pdf)

Distribution: Email

## **Revises D8114-19b**

Section 7.2.3: When switching to a new fuel batch, do not add the new fuel until the laboratory's fuel tank is below 10 % of the total tank volume. After the new fuel batch is added, the resulting volume of fuel is to consist of no more than 10 % of the current batch and at least 90 % of the new batch.