



Test Monitoring Center

@ Carnegie Mellon University
6555 Penn Avenue, Pittsburgh, PA 15206, USA

<http://astmtmc.cmu.edu>
412-365-1000

Sequence VIF Information Letter 20-3
Sequence Number 7
August 31, 2020

TO: Sequence VI Surveillance Panel
SUBJECT: Correction/Clarification to Intake Air Pressure Sensor

During the August 25, 2020 Sequence VI Surveillance Panel Conference call, it was brought to the panel's attention that the reference figure depicting the intake air pressure sensor location was incorrect and that it also did not reference the probe and its orientation. Section 6.12.6 has been revised to show the correct figure for the probe and its location.

Attached are the revised sections of Test Method D8226 and these changes are effective with the issuance of this letter.

Aleise Gauer
Materials Engineer – Fluids & Lubricants
GM Global Propulsion Systems

Frank M. Farber
Director
ASTM Test Monitoring Center

Attachment

c: http://www.astmtmc.cmu.edu/ftp/docs/gas/sequencevi/procedure_and_ils/VIF/il20-3_vif.pdf

Distribution: Email

Revises D8226-20 as Amended by Information Letter 20-2

6.12.6 *Intake Air*—Measure the intake air pressure at the location shown in Fig. A5.12, using the probe shown in Figure A5.16 and a sensor/readout accuracy of 2 % of full scale with resolution of 5.0 Pa. Orient the probe in the center of the direction of flow.