



Test Monitoring Center

6555 Penn Avenue
Pittsburgh, PA 15206-4489
(412) 365-1000

SEQUENCE VIII INFORMATION LETTER NO. 08-1

Sequence No. 9

April 16, 2008

ASTM consensus has not been obtained on this information letter. An appropriate ASTM ballot will be issued in order to achieve such consensus.

TO: Sequence VIII Mailing List

SUBJECT: Revision to Rocker Cover Inlet Air Connection

During the March 20, 2008 conference call, the Sequence VIII Surveillance Panel agreed to remove the rocker cover inlet air connection, detailed in Figure 4, and replace it with a reservoir to facilitate oil additions during test operation. The design of this reservoir is left to the discretion of the laboratory. Section 6.2.2.4 has been revised to delete the reference to Figure 4 and to specify a reservoir. Figure 4 has been deleted and existing Figures 5 through 9 have been renumbered as Figures 4 through 8. These changes are effective March 20, 2008.

Fred Gerhart
Chairman
Sequence VIII Surveillance Panel

John L. Zalar
Administrator
ASTM Test Monitoring Center

Attachment

c: ftp://ftp.astmtmc.cmu.edu/docs/gas/sequenceviii/procedure_and_ils/il08-1.pdf

Distribution: Electronic mail

6.2.2.4 Install a reservoir, to facilitate oil additions during test operation at the rocker cover inlet for the crankcase ventilation air. The construction of the reservoir is left up to the laboratory, but the reservoir needs to be air tight between oil additions and have an outlet to attach to the rocker cover air control system.

Delete Figure 4

Renumber Figures 5 through 9 as Figures 4 through 8