



Test Monitoring Center

6555 Penn Avenue
Pittsburgh, PA 15206-4489
(412) 365-1000

High Temperature Cyclic Durability Information Letter 04-1
Sequence No. 11
November 18, 2004

ASTM consensus has not yet been obtained on this information letter. An appropriate ASTM ballot will be issued in order to achieve such consensus.

TO: High Temperature Cyclic Durability Mailing List

SUBJECT: One Quart Test Oil EOT Save Requirement Dropped

At the November 3, 2004 High Temperature Cyclic Durability Surveillance Panel meeting, the panel approved a motion to revise the oil drain procedure so that it is no longer necessary to save one quart of test oil at the end of test. A revised Section 11.3.3 of Test Method D 5579 is attached. The effective date for this change is November 3, 2004.

A handwritten signature in black ink, appearing to read 'Brian Koehler'.

Brian Koehler
Chairman
HTCT Surveillance Panel

A handwritten signature in black ink, appearing to read 'John L. Zalar'.

John L. Zalar
Administrator
ASTM Test Monitoring Center

Attachment

c: ftp://ftp.astmtmc.cmu.edu/docs/gear/htct/procedure_and_ils/il04-1.pdf

Distribution: Email

(Revises Test Method D 5579-04)

11.3.3 Drain the test oil from the transmission and heater.