



Test Monitoring Center

6555 Penn Avenue
Pittsburgh, PA 15206-4489
(412) 365-1000

L-60-1 Information Letter 07-1
Sequence Number 34
November 15, 2007

ASTM consensus has not been obtained on this information letter. An appropriate ASTM ballot will be issued in order to achieve such consensus.

TO: L-60-1 Mailing List
SUBJECT: Revised Downtime Wording

At the November 7, 2007 L-60-1 Surveillance Panel meeting, the panel approved a motion to revise the downtime wording in Test Method D 5704. A revised Section 10.7 and new Sections 10.7.1 and 10.7.2 of Test Method D 5704 are attached. Old Section 10.7.1 has been renumbered to 10.7.3. This change is effective the date of this information letter.

Chris Schenkenberger
Chairman
L-60-1 Surveillance Panel

John L. Zalar
Administrator
ASTM Test Monitoring Center

Attachment

c: ftp://ftp.astmtmc.cmu.edu/docs/gears/1601/procedure_and_ils/il07-1.pdf

Distribution: Email

(Revises Test Method D 5704-07)

10.7 Run the test at the conditions specified for 50.0 ± 0.1 h. Terminate the test if more than 5 min of total downtime occurs during the test period. Record any downtime on Form 4, Annex A5.

10.7.1 A downtime occurrence is defined as the time at which the test is shut down until the time the test returns to test operating specifications.

10.7.2 Do not calculate percent deviations during downtime occurrences.

Renumber old 10.7.1 to 10.7.3