



Test Monitoring Center

203 Armstrong Drive, Freeport, PA 16229, USA

www.astmtmc.org
412-365-1000

L-60-1 Information Letter 24-1
Sequence Number 54
February 20, 2024

ASTM consensus has not been obtained on this information letter. An appropriate ASTM ballot will be issued in order to achieve such consensus.

TO: L-60-1 Surveillance Panel

SUBJECT: Addition of Wording for Extension of Test Length For Non-Reference Tests

On February 7, 2024, The L-60-1 Surveillance Panel approved the addition of wording into section 10.7 of the test method. This additional wording will allow for non-reference tests to extend beyond the 50h test length specified for reference tests. This additional wording is necessary since a 300hr version of the test can be required by the LRI review committee. This change is effective immediately following the conclusion of the surveillance panel vote.

Nick Schaup
Chairman
L-60-1 Surveillance Panel

Jeff Clark
Executive Director
ASTM Test Monitoring Center

Attachments

cc: https://www.astmtmc.org/ftp/docs/gear/l601/procedure_and_ils/il24-1_L601.pdf

Distribution: Email

(Revises Test Method D 5704-22a)

Replace the text of section 10.7 with the following:

10.7 Run the test at the conditions specified for 50.0 h ~~6 0.1 h~~. Terminate the test if more than 5 min of total downtime occurs during the test period. Record any downtime on Form 4, Annex A8. **Non-reference oil tests may run longer than 50h provided that all post test measurements required are performed at the extended EOT and the additional EOT h are reported on the appropriate forms. The same 50h requirements for rating and oil analysis apply to extended EOT tests. Extending the test from 50h does not invalidate the test.**