

Obs	effective_date	info_letter_number	event
1	19930527		Oil 1004 15-test Targets
2	19940201		Oil 1004-1 introduced
3	19940309	94-1	Use a CG-4 quality oil following solvent flush to prevent rust during engine lay up
4	19940401	94-1	LTMS used for test acceptance
5	19940401	94-1	Discrimination tests to be run on oil 1001; once per year per stand
6	19940727	94-2	Kinematic Viscosity at 100°C Measurement Procedure added to test procedure
7	19940727	94-2	Enhanced Detroit Diesel TGA Procedure added to test procedure
8	19940901	94-1	Data Dictionary and Report Form Revisions - Version 199400503
9	19941017		Oil 1004-1 10-test Targets
10	19950405	95-1	Viscosity measurement bath soak window changed to $\pm 30$ seconds
11	19950626		Oil 1004-1 21-test Targets
12	19950901		Oil 1004-2 introduced
13	19950904	95-1	Data Dictionary and Report Form Revisions - Version 19950606
14	19960601		Oil 1004-1 targets for 6.5L
15	19960601		Oil 1004-2 targets for 6.5L
16	19960701	96-1	Data Dictionary and Report Form Revisions - Version 19960323
17	19961201	96-2	Data Dictionary and Report Form Revisions - Version 19960828
18	19970414		Oil 1005 introduced as a reference oil
19	19980101		Oil 1004-2 targets for 6.5L - 10 test targets
20	19980502		Oil 1005-1 introduced
21	19980930	98-1	Requirement to run discrimination tests eliminated
22	20001101		Oil 1005-1 targets for 6.5 L - 5 test targets