

LUBRIZOL CORPORATION
 29400 LAKELAND BOULEVARD
 44092-2298, WICKLIFFE
 United States



Attention of : Mr. T. Catanese

Analysis Report

Report number : 13051/00068890.1/L/24 Submitted date : 06-20-2024
 Sample submitted at : Saybolt LP, Deer Park
 Report Date : 06-24-2024 Date received : 06-20-2024
 Date of issue : 06-24-2024 Date completed : 06-24-2024
 Sample object : Lubrizol Sample number : 16471461
 Sample type : Submitted
 Sample submitted as : Gasoline
 Marked : OS394755H

NAME	METHOD	UNIT	RESULT
API Gravity	ASTM D 4052	°API	58.8
Distillation	ASTM D 86		
Initial boiling point		°F	86.3
5% Evaporated		°F	112.2
10% Evaporated		°F	125.3
20% Evaporated		°F	144.5
30% Evaporated		°F	166.6
40% Evaporated		°F	194.4
50% Evaporated		°F	218.1
60% Evaporated		°F	229.3
70% Evaporated		°F	239.7
80% Evaporated		°F	256.6
90% Evaporated		°F	312.9
95% Evaporated		°F	335.8
Final boiling point		°F	397.7
Recovery		vol %	98.1
Residue		vol %	0.8
Loss		vol %	1.1
Evaporated at 200 °F		vol %	41.9
Evaporated at 300 °F		vol %	88.6
Heat Of Combustion, Net	ASTM D 3338	Btu/lb	18351
Hydrocarbon Type FIA	ASTM D 1319		
Aromatics		vol %	37.1
Olefins		vol %	0.6
Saturates		vol %	67.3
Sulfur	ASTM D 5453	mg/kg	3.1
Vapor Pressure	ASTM D 5191		

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability for the supplied information. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.

Saybolt expressly disclaims any representation in this report, whether express or implied, as to the origin of the crude or refined product identified herein. Any designation as to origin is made solely by the party submitting the sample for analysis. Saybolt has not verified the tested parameters against any supplied specification for purposes of establishing origin. Further, any certification provided is solely as to the physical and chemical properties of the sample identified in this report.

LUBRIZOL CORPORATION
29400 LAKELAND BOULEVARD
44092-2298, WICKLIFFE
United States



Attention of : Mr. T. Catanese

Analysis Report

Report number : 13051/00068890.1/L/24 Submitted date : 06-20-2024
Sample submitted at : Saybolt LP, Deer Park
Report Date : 06-24-2024 Date received : 06-20-2024
Date of issue : 06-24-2024 Date completed : 06-24-2024
Sample object : Lubrizol Sample number : 16471461
Sample type : Submitted
Sample submitted as : Gasoline
Marked : OS394755H

NAME	METHOD	UNIT	RESULT
Vapor Pressure, EPA Eq.		psi@100F	8.69
Vapor Pressure, ASTM Eq.		psi@100F	8.57

Signed by: Sandra Kaluza - Laboratory Coordinator
Issued by: Saybolt LP
Place and date of issue: Deer Park - 06-24-2024

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability for the supplied information. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.

Saybolt expressly disclaims any representation in this report, whether express or implied, as to the origin of the crude or refined product identified herein. Any designation as to origin is made solely by the party submitting the sample for analysis. Saybolt has not verified the tested parameters against any supplied specification for purposes of establishing origin. Further, any certification provided is solely as to the physical and chemical properties of the sample identified in this report.