

| Attention of |  |
|--------------|--|
|--------------|--|

: Mr. P. Rubas

## Analysis Report

| Report number       | : 13072/00016782.1/L/23         | Submitted date      | : 07-24-2023            |
|---------------------|---------------------------------|---------------------|-------------------------|
|                     |                                 | Sample submitted at | : Saybolt LP, Deer Park |
| Report Date         | : 07-25-2023                    | Date received       | : 07-24-2023            |
| Date of issue       | : 07-25-2023                    | Date completed      | : 07-25-2023            |
| Sample object       | : ExxonMobil - Annandale        | Sample number       | : 15018098              |
| Sample type         | : Submitted                     |                     |                         |
| Sample submitted as | : Gasoline                      |                     |                         |
| Marked              | : 23-035597-0 2H2023 VIE Fuel S | Sample              |                         |

| NAME                    | METHOD      | UNIT   | RESULT |
|-------------------------|-------------|--------|--------|
| API Gravity             | ASTM D 4052 | °API   | 58.9   |
| Distillation            | ASTM D 86   |        |        |
| Initial boiling point   |             | °F     | 86.8   |
| 5% Evaporated           |             | °F     | 113.2  |
| 10% Evaporated          |             | °F     | 125.9  |
| 20% Evaporated          |             | °F     | 145.4  |
| 30% Evaporated          |             | °F     | 168.5  |
| 40% Evaporated          |             | °F     | 195.5  |
| 50% Evaporated          |             | °F     | 217.5  |
| 60% Evaporated          |             | °F     | 229.6  |
| 70% Evaporated          |             | °F     | 239.5  |
| 80% Evaporated          |             | °F     | 257.4  |
| 90% Evaporated          |             | °F     | 313.4  |
| 95% Evaporated          |             | °F     | 336.6  |
| Final boiling point     |             | °F     | 399.0  |
| Recovery                |             | vol %  | 97.6   |
| Residue                 |             | vol %  | 1.2    |
| Loss                    |             | vol %  | 1.2    |
| Evaporated at 200 °F    |             | vol %  | 41.7   |
| Evaporated at 300 °F    |             | vol %  | 88.4   |
| Heat Of Combustion, Net | ASTM D 3338 | Btu/lb | 18434  |
| Hydrocarbon Type FIA    | ASTM D 1319 |        |        |
| Aromatics               |             | vol %  | 31.2   |
| Olefins                 |             | vol %  | 0.5    |
| Saturates               |             | vol %  | 68.3   |
| Sulfur                  | ASTM D 5453 | mg/kg  | 2.9    |
| Vapor Pressure          | ASTM D 5191 |        |        |

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability for the supplied information. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.

Saybolt expressly disclaims any representation in this report, whether express or implied, as to the origin of the crude or refined product identified herein. Any designation as to origin is made solely by the party submitting the sample for analysis. Saybolt has not verified the tested parameters against any supplied specification for purposes of establishing origin. Further, any certification provided is solely as to the physical and chemical properties of the sample identified in this report.



Attention of

: Mr. P. Rubas

## Analysis Report

| Report number       | : 13072/00016782.1/L/23      | Submitted date<br>Sample submitted at | :07-24-2023<br>:Saybolt LP, Deer Park |
|---------------------|------------------------------|---------------------------------------|---------------------------------------|
| Report Date         | : 07-25-2023                 | Date received                         | : 07-24-2023                          |
| Date of issue       | : 07-25-2023                 | Date completed                        | : 07-25-2023                          |
| Sample object       | : ExxonMobil - Annandale     | Sample number                         | : 15018098                            |
| Sample type         | : Submitted                  |                                       |                                       |
| Sample submitted as | : Gasoline                   |                                       |                                       |
| Marked              | : 23-035597-0 2H2023 VIE Fue | I Sample                              |                                       |

| NAME                     | METHOD | UNIT     | RESULT |
|--------------------------|--------|----------|--------|
| Vapor Pressure, EPA Eq.  |        | psi@100F | 8.93   |
| Vapor Pressure, ASTM Eq. |        | psi@100F | 8.81   |

Signed by: Sandra Kaluza - Laboratory Coordinator Issued by: Saybolt LP Place and date of issue: Deer Park - 07-25-2023

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability for the supplied information. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.

Saybolt expressly disclaims any representation in this report, whether express or implied, as to the origin of the crude or refined product identified herein. Any designation as to origin is made solely by the party submitting the sample for analysis. Saybolt has not verified the tested parameters against any supplied specification for purposes of establishing origin. Further, any certification provided is solely as to the physical and chemical properties of the sample identified in this report.